


Adjustable Precision Shunt Regulators

TL431XM3



SOT-89

Description

The TL431XM3 series are three-terminal adjustable regulators with guaranteed thermal stability over applicable temperature range. The output voltage may be set to any value between V_{REF} (approximately 2.495 volts) and 36 volts with two external resistors. These devices have a typical dynamic output impedance of 0.2Ω . Active output circuitry provides a very sharp turn-on characteristic, making these devices excellent replacement for zener diodes in many applications.

Features

- Programmable output voltage
- Temperature coefficient is 50ppm/°C typical
- Temperature compensated for operation over full temperature range
- Low output noise voltage
- Fast turn on response

Classification

Rank	A	B	C
V_{REF}	$2.495 \pm 0.5\%$	$2.495 \pm 1\%$	$2.495 \pm 2\%$


Absolute Maximum Ratings

(Operating temperature range applies unless otherwise specified)


Characteristics	Symbol	Value	Unit
Cathode Voltage	V_{KA}	37	V
Cathode Current Range (Continuous)	I_K	-100~+150	mA
Reference Input Current Range	I_{REF}	0.05~+10	mA
Power Dissipation	P_D	770	mW
Operating Temperature Range	T_{opr}	0~+70	°C
Storage Temperature Range	T_{stg}	-65~+150	°C

Functional Block Diagram & Symbol

Functional Block Diagram :



Symbol :



Test Circuits




Fig1. Test Circuit for $V_Z = V_{REF}$




Fig 2. Test Circuit for $V_Z > V_{REF}$
Note : $V_Z = V_{REF}(1 + R_1/R_2) + I_{REF}R_1$





Fig3. Test Circuit for Off-State Current

Electrical Characteristics ($T_a = 25^\circ\text{C}$ unless otherwise specified)


Characteristics	Symbol	Test Conditions	Min	Typ	Max	Unit
Reference Input Voltage TL431A TL431B TL431C	V_{REF}	$V_{KA} = V_{REF}$, $I_K = 10\text{mA}$	2.445 2.470 2.480	2.495 2.495 2.495	2.545 2.520 2.510	V
Deviation of Reference Input Voltage Over-Temperature	$V_{REF(\text{dev})}$	$V_{KA} = V_{REF}$, $I_K = 10\text{mA}$ $T_{\min} \leq T_a \leq T_{\max}$	-	4	17	mV
Ratio of Change in Reference Input Voltage to the Change in Cathode Voltage	$\Delta V_{REF} / \Delta V_{KA}$	$I_K = 10\text{mA}$, $\Delta V_{KA} = 10\text{V} - V_{REF}$	-	-1.4	-2.7	mV
		$I_K = 10\text{mA}$, $\Delta V_{KA} = 36\text{V} - 10\text{V}$	-	-1.0	-2.0	V
Reference Input Current	I_{REF}	$I_K = 10\text{mA}$, $R_1 = 10\text{k}\Omega$, $R_2 = \infty$	-	2	4	μA
Deviation of Reference Input Current Over Full Temperature Range	$I_{REF(\text{dev})}$	$I_K = 10\text{mA}$, $R_1 = 10\text{k}\Omega$, $R_2 = \infty$, $T_a = \text{Full Range}$	-	0.4	1.2	μA
Minimum Cathode Current for Regulation	$I_{K(\min)}$	$V_{KA} = V_{REF}$	-	0.4	1.0	mA
Off-State Cathode Current	$I_{K(\text{off})}$	$V_{KA} = 36\text{V}$, $V_{REF} = 0$	-	0.1	1.0	μA
Dynamic impedance	Z_{KA}	$V_{KA} = V_{REF}$, $f \leq 1.0\text{KHz}$ $I_K = 1$ to 100mA	-	0.2	0.5	Ω

Characteristic Curves


**CATHODE CURRENT vs
CATHODE VOLTAGE**




**CATHODE CURRENT vs
CATHODE VOLTAGE**




**REFERENCE INPUT VOLTAGE
vs AMBIENT TEMPERATURE**




**REFERENCE INPUT CURRENT
vs AMBIENT TEMPERATURE**



**CATHODE VOLTAGE vs REFERENCE
INPUT VOLTAGE**




DYNAMIC IMPEDANCE vs FREQUENCY






**OPEN-LOOP VOLTAGE GAIN
vs FREQUENCY**



SOT-89 Dimension



*: Typical

DIM	Inches		Millimeters		DIM	Inches		Millimeters	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	0.1732	0.1811	4.40	4.60	F	0.0583	0.0598	1.48	1.527
B	0.1594	0.1673	4.05	4.25	G	0.1165	0.1197	2.96	3.04
C	0.0591	0.0663	1.50	1.70	H	0.0551	0.0630	1.40	1.60
D	0.0945	0.1024	2.40	2.60	I	0.0138	0.0161	0.35	0.41
E	0.01417	0.0201	0.36	0.51					

Notes: 1. Controlling dimension: millimeters.

2. Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.

3. If there is any question with packing specification or packing method, please contact your local CYStek sales office.

Material:

- Lead: 42 Alloy ; solder plating
- Mold Compound: Epoxy resin family, flammability solid burning class: UL94V-0

Important Notice:

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of CYStek.
- CYStek reserves the right to make changes to its products without notice.
- CYStek **semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- CYStek assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.