

HER151G THRU HER158G


CURRENT 1.5 Amperes
VOLTAGE 50 to 1000 Volts

Features

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Low forward voltage drop
- High current capability
- High reliability
- Low power loss, high efficiency
- Glass passivated junction
- High speed switching
- Low leakage

Mechanical Data

- Case : JEDEC DO-15 molded plastic body
- Epoxy : UL94V-0 rate flame retardant
- Lead : Plated axial lead solderable per MIL-STR-750, method 2026
- Polarity : Color band denotes cathode end
- Mounting Position : Any
- Weight : 0.014 ounce, 0.39 gram



Maximum Ratings And Electrical Characteristics

(Ratings at 25 °C ambient temperature unless otherwise specified, Single phase, half wave 60Hz, resistive or inductive load. For capacitive load, derate by 20%)

	Symbols	HER 151G	HER 152G	HER 153G	HER 154G	HER 155G	HER 156G	HER 157G	HER 158G	Units
Maximum recurrent peak reverse voltage	V _{RRM}	50	100	200	300	400	600	800	1000	Volts
Maximum RMS voltage	V _{RMS}	35	70	140	210	280	420	560	700	Volts
Maximum DC blocking voltage	V _{DC}	50	100	200	300	400	600	800	1000	Volts
Maximum average forward rectified current 0.375"(9.5mm) lead length @ at T _A =55 °C	I _(AV)	1.5								Amps
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC mothod)	I _{FSM}	50.0								Amps
Maximum instantaneous forward voltage at 2.0A	V _F	1.0			1.3		1.7			Volts
Maximum DC reverse current at rated DC blocking voltage at T _A =25 °C	I _R	5.0								μ A
Maximum DC reverse current at rated DC blocking voltage at T _A =125 °C		100								
Maximum reverse recovery time (Note 1)	T _{rr}	50					75			ns
Typical junction capacitance (Note 2)	C _J	50					30			pF
Operating junction and storage temperature range	T _J T _{STG}	-55 to +150								°C

Notes:

- (1) Test conditions: I_F=0.5A, I_R=1.0A, I_{rr}=0.25A.
- (2) Measured at 1MHz and applied reverse voltage of 4.0 Volts.

RATINGS AND CHARACTERISTIC CURVES HER151G THRU HER158G

FIG.1-TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC




FIG.2-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.3-TYPICAL FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.5-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.6-TYPICAL JUNCTION CAPACITANCE

