

50A Glass Passivated Bridge Rectifier

Features

- Glass passivated chip junction
- Low reverse leakage current
- Low power loss; high efficiency
- Electrically isolated epoxy case for Max. heat dissipation
- This series is UL recognized under component index, File number E194718
- RoHS Compliant



Mechanical Data

Case:	GBPC35, Molded plastic with heatsink, available in both low profile and standard case
Epoxy:	Plastic package has UL flammability classification 94V-0
Terminals:	Plated faston lugs or wire leads.
Polarity:	As marked on case
Mounting Position	See note 2
Mounting Torque	23 cm-kG (20in.-lbs) Max.
Weight:	21 grams

Maximum Ratings And Electrical Characteristics ($T_{amb}=25^{\circ}C$)

Symbol	Description	GBPC 50-005	GBPC 50-01	GBPC 50-02	GBPC 50-04	GBPC 50-06	GBPC 50-08	GBPC 50-10	Unit	Conditions
VRRM	Max. Repetitive Peak Reverse Voltage	50	100	200	400	600	800	1000	V	
VRMS	Max. RMS Voltage	35	70	140	280	420	560	700	V	
VDC	Max. DC blocking voltage	50	100	200	400	600	800	1000	V	
IF(AV)	Max. Average Forward Rectified Output Current	50.0							A	$T_c=50^{\circ}C$, See Fig.1
IFSM	Peak Forward Surge Current	450							A	8.3ms single half sine-wave superimposed on rated load (JEDEC method)



50A Glass Passivated Bridge Rectifier

GBPC50-005 - GBPC50-10

V_F	Max. Instantaneous Forward Voltage drop per leg	1.1	V	I _{F(AV)} =25A
I_R	Max. Reverse DC Current At Rated DC Blocking Voltage per leg	5.0	μA	T _C = 25°C
		500	μA	T _C = 125°C
I²t	Rating for Fusing (1ms<t<8.3ms)	800	A ² s	
C_J	Typical junction capacitance	400	pF	f=1MHz V _R = 4V
R_{thjc}	Typical Thermal Resistance per leg	1.0	°C / W	Note 1
T_J,T_{STG}	Operating Junction and Storage Temperature Range	-65 to +150	° C	

Note: 1. Thermal Resistance from junction to Case per leg.
2. Mounted on 229 × 102 × 117mm Al. finned plate.

Typical Characteristics Curves



50A Glass Passivated Bridge Rectifier

GBPC50-005 - GBPC50-10

Fig.3-Typical Instantaneous Forward Characteristic Per Leg




Fig.4-Typical Reverse Characteristics Per Leg






Fig.5-Typical Junction Capacitance Per Leg



50A Glass Passivated Bridge Rectifier

GBPC50-005 - GBPC50-10

Dimensions in inch (mm)



GBPC35

How to contact us

US HEADQUARTERS

28040 WEST HARRISON PARKWAY, VALENCIA, CA 91355-4162

Tel: (800) TAITRON (800) 824-8766 (661) 257-6060

Fax: (800) TAITFAX (800) 824-8329 (661) 257-6415

Email: taitron@taitroncomponents.com

Http://www.taitroncomponents.com

TAITRON COMPONENTS MEXICO, S.A .DE C.V.

BOULEVARD CENTRAL 5000 INTERIOR 5 PARQUE INDUSTRIAL ATITALAQUIA, HIDALGO C.P.

42970 MEXICO

Tel: +52-55-5560-1519

Fax: +52-55-5560-2190

TAITRON COMPONENTS INCORPORATED REPRESENTAÇÕES DO BRASIL LTDA

RUA DOMINGOS DE MORAIS, 2777, 2.ANDAR, SALA 24 SAÚDE - SÃO PAULO-SP 04035-001 BRAZIL

Tel: +55-11-5574-7949

Fax: +55-11-5572-0052

TAITRON COMPONENTS INCORPORATED, SHANGHAI REPRESENTATIVE OFFICE

CROSS REGION PLAZA, 899 LINGLING ROAD, SUITE 18C, SHANGHAI, 200030, CHINA

Tel: +86-21-5424-9942

Fax: +86-21-5424-9931