



Micro Commercial Components

Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

MBR30150PT

Features

- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- High Junction Temperature Capability
- Low forward voltage, high current capability
- High surge capacity
- Low power loss, high efficiency
- Marking : type number

Maximum Ratings

- Operating Temperature: -50°C to +150°C
- Storage Temperature: -50°C to +150°C

MCC Part Number	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
MBR30150PT	150V	105V	150V


Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	$I_{F(AV)}$	35 A	$T_C = 125^\circ\text{C}$
Peak Forward Surge Current	I_{FSM}	250A	10ms single or 6ms Rect. pulse
Maximum Instantaneous Forward Voltage	V_F	0.85V 0.75V	$I_{FM} = 15A; T_C = 25^\circ\text{C}$ $T_C = 125^\circ\text{C}$
Maximum DC Reverse Current At Rated DC Blocking Voltage	I_R	50 μ A 10mA	$T_C = 25^\circ\text{C}$ $T_C = 125^\circ\text{C}$
Voltage Rate of Change	dV/dt	10KV/ μ s	Rated V_R
Typical Thermal Resistance, Junction to Case	$R_{th(j-c)}$	2.0°C/W	Per diode

*Pulse Test: Pulse Width 380 μ sec, Duty Cycle 2%

30 Amp Power Schottky Rectifier 150 Volts

T0-247AD



DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	.780	.819	19.80	20.80	
B	.807	.846	20.50	21.50	
C	.606	.638	15.40	16.20	
D	.138	.150	3.50	3.80	
E	.226	.242	5.75	6.15	
F	.209	.224	5.30	5.70	
G	.077	.085	1.95	2.15	
H	.163	.175	4.15	4.45	
I	.591	.622	15.00	15.80	
J	.043	.051	1.10	1.30	
K	.197	.213	5.00	5.40	
L	.189	.205	4.80	5.20	
M	.024	.031	0.60	0.80	
N	.085	.096	2.15	2.45	
O	.079	.091	2.00	2.30	




Figure 1. Max. Forward Voltage Drop Characteristics (PerLeg)




Figure 2. Typical Values Of Reverse Current Vs. Reverse Voltage (PerLeg)




Figure 3. Typical Junction Capacitance Vs. Reverse Voltage (PerLeg)




Figure 4. Max. Thermal Impedance Z_{thJC} Characteristics (PerLeg)




Figure 5. Max. Allowable Case Temperature Vs. Average Forward Current (PerLeg)




Figure 6. Forward Power Loss Characteristics (PerLeg)




Figure 7. Max. Non-Repetitive Surge Current (PerLeg)

*****IMPORTANT NOTICE*****

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes .
Micro Commercial Components Corp. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp.* and all the companies whose products are represented on our website, harmless against all damages.

*****APPLICATIONS DISCLAIMER*****

Products offer by *Micro Commercial Components Corp.* are not intended for use in Medical,
Aerospace or Military Applications.