

SCHOTTKY BARRIER RECTIFIER

VOLTAGE RANGE: 30 - 100 V
CURRENT: 8.0 A


FEATURES

- ◇ High surge capacity.
- ◇ For use in low voltage, high frequency inverters, free wheeling, and polarity protection applications.
- ◇ Metal silicon junction, majority carrier conduction.
- ◇ High current capacity, low forward voltage drop.
- ◇ Guard ring for over voltage protection.

MECHANICAL DATA

- ◇ Case: JEDEC D²PAK, molded plastic body
- ◇ Terminals: Leads, solderable per MIL-STD-750, Method 2026
- ◇ Polarity: As marked
- ◇ Position: Any
- ◇ Weight: 0.087 ounces, 2.2 gram

D²PAK



inch(mm)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

		MBRB 830	MBRB 835	MBRB 840	MBRB 845	MBRB 850	MBRB 860	MBRB 880	MBRB 8100	UNITS
Maximum recurrent peak reverse voltage	V _{RRM}	30	35	40	45	50	60	80	100	V
Maximum RMS Voltage	V _{RMS}	21	25	28	32	35	42	56	70	V
Maximum DC blocking voltage	V _{DC}	30	35	40	45	50	60	80	100	V
Maximum average forw ard total device rectified current @T _C = 125°C	I _{F(AV)}	8.0								A
Peak forw ard surge current 8.3ms single half sine-w ave superimposed on rated load	I _{FSM}	150								A
Maximum forw ard voltage (Note 1)	(I _F =8.0A,T _C =125°C) (I _F =8.0A,T _C =25 °C) (I _F =16A,T _C =25 °C)	V _F	0.57 0.70 0.84			0.70 0.80 0.95		- 0.85 -		V
Maximum reverse current at rated DC blocking voltage	@T _C =25°C @T _C =125°C	I _R	0.1 15					0.5 50		m A
Maximum thermal resistance (Note 2)	R _{θJC}	3.0								K/W
Operating junction temperature range	T _J	- 55 ---- + 150								°C
Storage temperature range	T _{STG}	- 55 ---- + 150								°C

NOTE: 1. Pulse test: 300μs pulse width, 1% duty cycle.
2. Thermal resistance from junction to case.

www.galaxycn.com

FIG.1 – PEAK FORWARD SURGE CURRENT




FIG.2 – FORWARD DERATING CURVE




FIG.3 – TYPICAL FORWARD CHARACTERISTIC




FIG.4 – TYPICAL REVERSE CHARACTERISTIC

