

DC-6.0 GHz InGaP HBT MMIC Matched Gain Block Amplifier

April 2007 - Rev 04-Apr-07

Mimix
BROADBAND™
CGB7012-BD
RoHS

Features

- ✕ 36.0 dBm Output IP3 @ 850 MHz
- ✕ 4.3 dB Noise Figure @ 850 MHz
- ✕ 15.7 dB Gain @ 850 MHz
- ✕ 20.3 dBm P1dB @ 850 MHz
- ✕ Low Performance Variation Over Temperature
- ✕ 100% DC On-Wafer Testing
- ✕ ESD Protection on All Die: >1000V HBM
- ✕ Low Thermal Resistance: <80°C/Watt

Description


The CGB7012-BD is a Darlington Configured, high dynamic range, utility gain block amplifier. Designed for applications operating within the DC to 6.0 GHz frequency range, Mimix's broadband, cascadable, gain block amplifiers are ideal solutions for transmit, receive and IF applications.

These MMIC amplifiers are available in bare die form. Mimix's InGaP HBT technology and an industry low thermal resistance offers a thermally robust and reliable gain block solution.

The InGaP HBT die have extra pads to enable thorough DC testing. This unique test capability and the inclusion of ESD protection on all die, significantly enhances the quality, reliability and ruggedness of these products.

With a single bypass capacitor, optional RF choke and two DC blocking capacitors, this gain block amplifier offers significant ease of use in a broad range of applications.

Chip Layout



Absolute Maximum Ratings

Max Device Voltage	+6.0 V
Max Device Current	130 mA
Max Device Dissipated Power	0.65 W
RF Input Power	+17 dBm
Storage Temperature	-55°C to 150°C
Junction Temperature	150°C
Operating Temperature	-40°C to +85°C
Thermal Resistance	80° C/W
EDS (HBM)	1000 V

Operation of this device above any of these parameters may cause permanent damage.

Applications

- ✕ PA Driver Amp, IF Amp, LO Buffer Amp
- ✕ Cellular, PCS, GSM, UMTS
- ✕ Wireless Data and SATCOM
- ✕ Transmit and Receive Functions
- ✕ CATV

Typical Performance

Parameter	Temperature (°C)	850 MHz			1950 MHz			2400 MHz			3500 MHz			Units
		Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.	Min.	Typ.	Max.	
Small Signal Gain	+25	14.5	15.7	16.9	13.3	14.5	15.7	12.7	13.9	15.1		13.2		dB
	-40 to +85	14.3	15.7	17.1	13.1	14.5	15.9	12.5	13.9	15.3		13.2		dB
Output P1dB	+25	19.3	20.3		17.9	18.9		16.9	17.9			15.1		dBm
	-40 to +85	19.0	20.3		17.6	18.9		16.6	17.9			15.1		dBm
Output IP3	+25	34.5	36.0		31.5	33.0		29.8	31.3			27.2		dBm
	-40 to +85	33.0	36.0		30.5	33.0		28.8	31.0			27.2		dBm
Noise Figure	+25		4.3	5.1		4.5	5.3		4.6	5.4		4.7		dB
	-40 to +85		4.3	5.5		4.5	5.7		4.6	5.8		4.7		dB
Operating Current	+25	82	83	90	82	86	90	82	86	90		86		mA
	-40 to +85	77	86	95	77	86	95	77	86	95		86		mA
Input Return Loss	+25	17	21		11	16		12	15			13		dB
	-40 to +85	16	21		10	16		11	15			13		dB
Output Return Loss	+25	17.0	22.0		12.0	16.0		11.0	15.0			20.0		dB
	-40 to +85	16.0	22.0		11.0	16.0		10.0	15.0			20.0		dB
Pout @ -45 dBc, ACP IS-95, 9 Forward Channels	+25		14			13								dBm
	-40 to +85		14			13								dBm

Notes: 1. Performance in Mimix eval board, $V_s = 8\text{ V}$, $I_d = 86\text{ mA Typ.}$, $R_{bias} = 30\ \Omega$, $Z_s = Z_L = 50\ \Omega$, OIP3 tone spacing = 1 MHz, Pout per tone = 3 dBm.

2. Values reflect performance in recommended application circuit.

3. Only DC on-wafer test is done. Devices are not tested for RF performance.

Mimix Broadband, Inc., 10795 Rockley Rd., Houston, Texas 77099
Tel: 281.988.4600 Fax: 281.988.4615 mimixbroadband.com

Page 1 of 7

Characteristic Data and Specifications are subject to change without notice. ©2007 Mimix Broadband, Inc.
Export of this item may require appropriate export licensing from the U.S. Government. In purchasing these parts, U.S. Domestic customers accept their obligation to be compliant with U.S. Export Laws.


DC-6.0 GHz InGaP HBT MMIC Matched Gain Block Amplifier

Mimix
BROADBAND™

CGB7012-BD
RoHS

April 2007 - Rev 04-Apr-07

Typical S-Parameter and Noise Performance





DC-6.0 GHz InGaP HBT MMIC Matched Gain Block Amplifier

Mimix
BROADBAND™





April 2007 - Rev 04-Apr-07

CGB7012-BD
RoHS

Typical Power and Linearity Performance



Linearity Performance - Base Station ACP - IS-95



Mimix Broadband, Inc., 10795 Rockley Rd., Houston, Texas 77099
Tel: 281.988.4600 Fax: 281.988.4615 mimixbroadband.com

Page 3 of 7

Characteristic Data and Specifications are subject to change without notice. ©2007 Mimix Broadband, Inc.
Export of this item may require appropriate export licensing from the U.S. Government. In purchasing these parts, U.S. Domestic customers accept their obligation to be compliant with U.S. Export Laws.

DC-6.0 GHz InGaP HBT MMIC Matched Gain Block Amplifier

Mimix
BROADBAND™

April 2007 - Rev 04-Apr-07

CGB7012-BD
XRoHS

Typical Scattering Parameters (Vd = +5.48V, Icc = 81 mA, T = 23°C, device in a 50 ohm system)

Frequency (MHz)	S ₁₁		S ₂₁		S ₁₂		S ₂₂	
	(Mag)	(Ang)	(Mag)	(Ang)	(Mag)	(Ang)	(Mag)	(Ang)
100	0.013	-161.7	6.48	174.70	0.106	-1.03	0.083	-5.26
200	0.016	-142.3	6.45	169.50	0.106	-1.94	0.084	-11.08
300	0.020	-130.0	6.43	164.30	0.106	-2.89	0.085	-16.60
400	0.024	-123.5	6.40	159.20	0.107	-3.91	0.086	-21.79
500	0.029	-117.9	6.36	154.20	0.107	-4.78	0.088	-27.05
600	0.034	-115.0	6.32	149.20	0.108	-5.87	0.090	-32.45
700	0.040	-114.2	6.28	144.20	0.108	-6.79	0.091	-37.58
800	0.045	-113.7	6.23	139.20	0.109	-7.84	0.093	-42.49
900	0.051	-112.6	6.18	134.30	0.110	-8.93	0.095	-47.30
1000	0.058	-113.2	6.14	129.40	0.110	-9.97	0.098	-52.41
1100	0.064	-113.7	6.08	124.50	0.111	-11.07	0.100	-57.12
1200	0.070	-114.6	6.03	119.60	0.113	-12.27	0.102	-61.32
1300	0.077	-115.6	5.97	114.80	0.114	-13.40	0.105	-65.98
1400	0.084	-116.7	5.90	110.00	0.115	-14.59	0.107	-70.11
1500	0.090	-118.1	5.84	105.30	0.116	-15.81	0.110	-74.31
1600	0.097	-119.6	5.78	100.60	0.117	-17.07	0.112	-78.18
1700	0.104	-121.0	5.72	95.88	0.119	-18.33	0.116	-82.12
1800	0.112	-122.9	5.65	91.25	0.120	-19.70	0.118	-86.01
1900	0.119	-124.6	5.58	86.69	0.122	-21.06	0.121	-89.67
2000	0.126	-126.4	5.52	82.13	0.123	-22.40	0.124	-93.46
2100	0.133	-128.5	5.45	77.59	0.125	-23.77	0.127	-96.75
2200	0.140	-130.4	5.38	73.09	0.126	-25.33	0.129	-100.40
2300	0.147	-132.7	5.32	68.65	0.128	-26.84	0.132	-103.80
2400	0.153	-135.0	5.26	64.21	0.130	-28.32	0.134	-107.30
2500	0.160	-137.3	5.19	59.80	0.132	-29.85	0.137	-110.70
2600	0.166	-139.8	5.13	55.47	0.134	-31.54	0.139	-113.90
2700	0.172	-142.1	5.07	51.16	0.136	-33.14	0.141	-117.40
2800	0.177	-144.6	5.01	46.90	0.138	-34.76	0.143	-120.80
2900	0.183	-147.3	4.95	42.66	0.140	-36.44	0.146	-124.50
3000	0.189	-149.8	4.89	38.39	0.142	-38.08	0.147	-127.90
3100	0.195	-152.5	4.84	34.23	0.144	-39.81	0.150	-131.40
3200	0.200	-155.2	4.79	30.01	0.146	-41.66	0.151	-135.10
3300	0.206	-158.2	4.74	25.87	0.148	-43.38	0.154	-138.80
3400	0.212	-161.3	4.69	21.68	0.151	-45.31	0.155	-142.60
3500	0.217	-164.4	4.64	17.54	0.153	-47.19	0.158	-146.40
3600	0.222	-167.5	4.59	13.39	0.156	-49.13	0.160	-150.20
3700	0.227	-170.6	4.55	9.34	0.158	-51.01	0.161	-154.10
3800	0.231	-173.9	4.50	5.22	0.161	-53.00	0.162	-158.60
3900	0.236	-177.7	4.46	1.15	0.163	-55.03	0.163	-162.60
4000	0.240	178.8	4.42	-2.91	0.166	-57.00	0.164	-167.00
4100	0.244	175.1	4.39	-6.96	0.168	-59.10	0.165	-171.60
4200	0.246	171.4	4.35	-11.01	0.171	-61.21	0.166	-176.40
4300	0.248	167.4	4.32	-15.07	0.174	-63.34	0.167	178.60
4400	0.251	163.2	4.29	-19.13	0.177	-65.57	0.167	173.00
4500	0.253	158.9	4.25	-23.23	0.180	-67.77	0.167	167.70
4600	0.254	154.7	4.23	-27.28	0.183	-70.01	0.168	162.00
4700	0.256	150.4	4.20	-31.35	0.186	-72.29	0.169	156.30
4800	0.256	145.7	4.17	-35.43	0.189	-74.61	0.171	150.00
4900	0.258	140.7	4.15	-39.52	0.193	-77.04	0.173	143.30
5000	0.259	135.4	4.12	-43.69	0.196	-79.52	0.175	136.40

Continues Next Page. S-Parameter Data Files are available online at: www.mimixbroadband.com

Mimix Broadband, Inc., 10795 Rockley Rd., Houston, Texas 77099
Tel: 281.988.4600 Fax: 281.988.4615 mimixbroadband.com

Page 4 of 7

Characteristic Data and Specifications are subject to change without notice. ©2007 Mimix Broadband, Inc.
Export of this item may require appropriate export licensing from the U.S. Government. In purchasing these parts, U.S. Domestic customers accept their obligation to be compliant with U.S. Export Laws.

DC-6.0 GHz InGaP HBT MMIC Matched Gain Block Amplifier



April 2007 - Rev 04-Apr-07

CGB7012-BD
RoHS

Typical Scattering Parameters (Vd = +5.48V, Icc = 81 mA, T = 23°C, device in a 50 ohm system)

Frequency (MHz)	S ₁₁		S ₂₁		S ₁₂		S ₂₂	
	(Mag)	(Ang)	(Mag)	(Ang)	(Mag)	(Ang)	(Mag)	(Ang)
5100	0.260	130.30	4.10	-47.85	0.199	-82.00	0.177	129.80
5200	0.261	125.30	4.08	-51.96	0.202	-84.51	0.181	123.40
5300	0.262	119.80	4.06	-56.14	0.206	-87.03	0.186	116.40
5400	0.263	113.80	4.04	-60.40	0.209	-89.72	0.192	109.00
5500	0.265	107.60	4.02	-64.64	0.212	-92.39	0.197	101.40
5600	0.268	101.60	4.00	-68.89	0.215	-95.14	0.204	94.40
5700	0.271	95.22	3.98	-73.21	0.219	-97.93	0.213	87.51
5800	0.274	88.84	3.96	-77.61	0.222	-100.80	0.223	80.07
5900	0.276	81.84	3.94	-82.05	0.225	-103.80	0.234	72.50
6000	0.281	74.69	3.91	-86.47	0.228	-106.70	0.247	65.27
6100	0.287	67.52	3.89	-90.97	0.232	-109.80	0.261	58.12
6200	0.294	60.50	3.86	-95.52	0.234	-112.90	0.276	51.22
6300	0.301	53.44	3.83	-100.10	0.237	-116.10	0.292	44.65
6400	0.308	46.10	3.80	-104.70	0.239	-119.30	0.311	38.22
6500	0.317	38.63	3.77	-109.40	0.242	-122.60	0.330	31.66
6600	0.328	31.38	3.73	-114.10	0.243	-125.90	0.350	25.34
6700	0.340	24.53	3.69	-118.80	0.245	-129.20	0.370	19.41
6800	0.351	17.77	3.64	-123.50	0.246	-132.60	0.390	13.68
6900	0.362	10.98	3.60	-128.20	0.247	-136.00	0.412	8.13
7000	0.375	3.93	3.55	-133.00	0.248	-139.50	0.434	2.41
7100	0.389	-2.94	3.49	-137.80	0.248	-143.00	0.457	-3.17
7200	0.403	-9.28	3.43	-142.70	0.247	-146.40	0.478	-8.74
7300	0.416	-15.41	3.36	-147.40	0.247	-149.90	0.498	-13.88
7400	0.428	-21.57	3.30	-152.20	0.246	-153.30	0.518	-18.91
7500	0.440	-27.79	3.23	-156.90	0.245	-156.90	0.539	-23.95
7600	0.454	-33.91	3.16	-161.60	0.243	-160.30	0.560	-29.08
7700	0.468	-39.66	3.08	-166.40	0.240	-163.60	0.579	-34.03
7800	0.480	-44.95	3.00	-170.90	0.238	-167.00	0.596	-38.74
7900	0.491	-50.24	2.92	-175.50	0.235	-170.30	0.613	-43.24
8000	0.500	-55.61	2.85	-179.90	0.232	-173.40	0.629	-47.62
8100	0.511	-60.92	2.76	-175.40	0.229	-176.80	0.645	-52.06
8200	0.522	-65.91	2.68	-170.90	0.226	-179.90	0.660	-56.47
8300	0.531	-70.45	2.59	-166.60	0.222	-177.10	0.674	-60.57
8400	0.537	-74.80	2.52	-162.50	0.218	-174.10	0.685	-64.48
8500	0.541	-79.28	2.44	-158.20	0.215	-171.20	0.696	-68.27
8600	0.545	-83.82	2.36	-154.00	0.211	-168.30	0.707	-72.02
8700	0.552	-88.16	2.29	-149.90	0.207	-165.40	0.716	-75.79
8800	0.557	-92.05	2.21	-145.90	0.203	-162.80	0.725	-79.36
8900	0.558	-95.76	2.14	-142.00	0.199	-160.30	0.732	-82.68
9000	0.558	-99.57	2.07	-138.20	0.196	-157.60	0.738	-85.93
9100	0.514	-104.50	2.01	-132.60	0.192	-155.30	0.744	-89.22
9200	0.558	-107.60	1.94	-130.40	0.188	-152.60	0.750	-92.37
9300	0.511	-112.00	1.87	-124.80	0.185	-150.40	0.755	-95.62
9400	0.508	-115.30	1.81	-121.10	0.181	-148.00	0.761	-98.68
9500	0.504	-118.50	1.74	-117.50	0.178	-145.50	0.763	-101.40
9600	0.495	-121.90	1.68	-113.70	0.174	-143.30	0.766	-104.30
9700	0.491	-125.50	1.62	-109.90	0.171	-141.20	0.770	-107.20
9800	0.489	-128.60	1.56	-106.50	0.168	-138.90	0.773	-109.90
9900	0.483	-131.30	1.51	-103.00	0.165	-136.70	0.774	-112.60
10000	0.475	-133.80	1.46	-99.63	0.162	-134.90	0.776	-115.20

S-Parameter Data Files are available online at: www.mimixbroadband.com

Mimix Broadband, Inc., 10795 Rockley Rd., Houston, Texas 77099
Tel: 281.988.4600 Fax: 281.988.4615 mimixbroadband.com

Page 5 of 7

Characteristic Data and Specifications are subject to change without notice. ©2007 Mimix Broadband, Inc.
Export of this item may require appropriate export licensing from the U.S. Government. In purchasing these parts, U.S. Domestic customers accept their obligation to be compliant with U.S. Export Laws.

DC-6.0 GHz InGaP HBT MMIC Matched Gain Block Amplifier

Mimix
BROADBAND™

April 2007 - Rev 04-Apr-07


CGB7012-BD
RoHS

Application Circuit


Note: This schematic represents the topology of the application circuit recommended by Mimix.

Recommended Bias Resistor Values for $I_D = 86 \text{ mA}$				
Supply Voltage (V_s)	7V	8V	10V	12V
$R_{bias} (1/4W)$	18 Ω	30 Ω	—	—
$R_{bias} (1/2W)$	—	—	53 Ω	77 Ω

Note: R_{bias} provides DC bias stability over temperature.




Physical Dimensions



Notes:
RF OUT bonding pad is 75 μm x 155 μm .
All other pads are 75 μm x 75 μm .


Ref Designator	Value
C1, C2	1000 pF
C3	1.0 μF
L1	56 nH
R1	$R_{bias} = (V_s - V_d) / I_d$

Bonding Configuration



Caution: ESD Sensitive
Appropriate precautions in handling, packaging
and testing devices must be observed.

DC-6.0 GHz InGaP HBT MMIC Matched Gain Block Amplifier



April 2007 - Rev 04-Apr-07

Handling and Assembly Information

CAUTION! - Mimix Broadband MMIC Products contain gallium arsenide (GaAs) which can be hazardous to the human body and the environment. For safety, observe the following procedures:

- *Do not ingest.*
- *Do not alter the form of this product into a gas, powder, or liquid through burning, crushing, or chemical processing as these by-products are dangerous to the human body if inhaled, ingested, or swallowed.*
- *Observe government laws and company regulations when discarding this product. This product must be discarded in accordance with methods specified by applicable hazardous waste procedures.*

Life Support Policy - Mimix Broadband's products are not authorized for use as critical components in life support devices or systems without the express written approval of the President and General Counsel of Mimix Broadband. As used herein: (1) Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user. (2) A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ESD - Gallium Arsenide (GaAs) devices are susceptible to electrostatic and mechanical damage. Die are supplied in antistatic containers, which should be opened in cleanroom conditions at an appropriately grounded anti-static workstation. Devices need careful handling using correctly designed collets, vacuum pickups or, with care, sharp tweezers.

Die Attachment - GaAs Products from Mimix Broadband are 0.100 mm (0.004") thick. Microstrip substrates should be brought as close to the die as possible. The mounting surface should be clean and flat. If using conductive epoxy, recommended epoxies are Tanaka TS3332LD, Die Mat DM6030HK or DM6030HK-Pt cured in a nitrogen atmosphere per manufacturer's cure schedule. Apply epoxy sparingly to avoid getting any on to the top surface of the die. An epoxy fillet should be visible around the total die periphery. For additional information please see the Mimix "Epoxy Specifications for Bare Die" application note.

Wire Bonding - Windows in the surface passivation above the bond pads are provided to allow wire bonding to the die's gold bond pads. The recommended wire bonding procedure uses Gold 0.025 mm (0.001") diameter ball bonds. Aluminum wire should be avoided. Thermo-compression bonding is recommended though thermosonic bonding may be used providing the ultrasonic content of the bond is minimized. Bond force, time and ultrasonics are all critical parameters. Bonds should be made from the bond pads on the die to the package or substrate. All bonds should be as short as possible.

Part Number for Ordering

CGB7012-BD-000V

Description

RoHS compliant die packed in vacuum release gel paks