

## **-52V Dual Channel Differential DSL Line Driver**

The ISL1541 is a -52V dual channel differential amplifier designed for driving full rate ADSL signals at very low power dissipation. The high supply voltage allows operation from a single standard -52V negative battery supply. It contains two pairs of wideband, high voltage, current mode feedback amplifiers optimized for lower power consumption and highest performance in ADSL and ADSL2+ systems. The line drivers have fixed gain  $A_V = 48$  with integrated feedback and gain resistors. Its output clamping circuit eliminates the requirement for the Zener protection diodes.

These drivers achieve an MTPR distortion measurement of better than 70dB while consuming typically 3mA per DSL channel of total supply current.

The ISL1541 is supplied in a thermally-enhanced 6mm x 6mm 24 Ld QFN package and is specified for operating over the full -40°C to +85°C temperature range.

### **Ordering Information**

| PART NUMBER                  | TAPE & REEL | PACKAGE                               | PKG. DWG. # |
|------------------------------|-------------|---------------------------------------|-------------|
| ISL1541IRZ<br>(See Note)     | -           | 24 Ld QFN<br>(6mm x 6mm)<br>(Pb-free) | L24.6x6     |
| ISL1541IRZ-T7<br>(See Note)  | 7"          | 24 Ld QFN<br>(6mm x 6mm)<br>(Pb-free) | L24.6x6     |
| ISL1541IRZ-T13<br>(See Note) | 13"         | 24 Ld QFN<br>(6mm x 6mm)<br>(Pb-free) | L24.6x6     |

NOTE: Intersil Pb-free plus anneal products employ special Pb-free material sets; molding compounds/die attach materials and 100% matte tin plate termination finish, which are RoHS compliant and compatible with both SnPb and Pb-free soldering operations. Intersil Pb-free products are MSL classified at Pb-free peak reflow temperatures that meet or exceed the Pb-free requirements of IPC/JEDEC J STD-020.

**Get Full Datasheet**


### **Features**

- 100mA output current driving capability
- Operates from a single -40V to -60V power supply
- 800mW per channel total power dissipation
- MTPR of -70dB
- 96V<sub>P-P</sub> differential output swing
- Fixed gain, integrated gain resistors
- Current control pins
- Output clamp for lightning and surge protection
- Channel separation
  - 75dB @ 1MHz
- Pb-Free plus anneal available (RoHS compliant)

### **Applications**

- Dual port ADSL and ADSL2+ line drivers
- HDSL, HDSL2, HDSL 4 and SHDSL line drivers
- DSLAM, DLC, MDU/MTU line drivers
- Performance upgrade to Le87213, Le87213A, Le87220
- Pin to Pin replacement for Le87220

### **Pinout**



All Intersil U.S. products are manufactured, assembled and tested utilizing ISO9000 quality systems.  
Intersil Corporation's quality certifications can be viewed at [www.intersil.com/design/quality](http://www.intersil.com/design/quality)

*Intersil products are sold by description only. Intersil Corporation reserves the right to make changes in circuit design, software and/or specifications at any time without notice. Accordingly, the reader is cautioned to verify that data sheets are current before placing orders. Information furnished by Intersil is believed to be accurate and reliable. However, no responsibility is assumed by Intersil or its subsidiaries for its use; nor for any infringements of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Intersil or its subsidiaries.*

For information regarding Intersil Corporation and its products, see [www.intersil.com](http://www.intersil.com)