

Adjustable Shunt Regulators

- Features:**
- Programmable output voltage range from 2.5V to 36V (GM431) 1.24V to 16V(GM432)
 - Low dynamic output impedance 0.05Ω typical
 - Reference voltage tolerance : 0.5%, 1%
 - Sink current capability of 1.0~100mA (GM431) 80 μA~100mA(GM432)
 - Fast turn-on response
 - Temperature compensated within rated range of operation
 - Low output noise voltage

Application :
Switching Power Supply, Battery Chargers, AC - DCAdaptor, Amplifier, Monitor, VCD, TVs, Low Voltage Output of Linear Regulator (3.3V ~2.5V or 1.8V), Linear Regulator, Constant Current Source 1 Sink, Under/ Over-Voltage Protection, Crowbar, Zener Diode, Crowbar, Voltage Monitor, Instrumentation, Computer Disk Drives.

Part No.	Reference Voltage (V)	Max. V _{KA} Cathode (V)	Operation Current		Voltage Tolerance	Package
			Min.	Max.		
GM431A	2.5	36	1mA	100mA	0.5%	SOT-23, TO-92, SOT-89, SOP-8
GM431B	2.5	36	1mA	100mA	1.0%	SOT-23, TO-92, SOT-89, SOP-8
GM432A	1.24	16	80μA	100mA	0.5%	SOT-25, SOT-23, TO-92, SOT-89, SOP-8
GM432B	1.24	16	80μA	100mA	1.0%	SOT-25, SOT-23, TO-92, SOT-89, SOP-8
GM1431A	2.5	36	1mA	100mA	0.5%	SOT-23, TO-92, SOT-89, SOP-8
GM1431B	2.5	36	1mA	100mA	1.0%	SOT-23, TO-92, SOT-89, SOP-8

Voltage Regulators

- Feature:**
- Output voltage range from 5V~27V with Vin= max=35V
 - Output current up to 1.5A
 - Low dropout voltage = 500mV (max)
 - Over current and voltage protection
 - Short circuit protection
 - Thermal shut down
 - ON/ OFF function for sleep mode
 - Output transistor safe area protection

Application :
LCD Monitor / TV, Consumer Product, High Efficiency Linear Post- Regulator for Switching Power Supply, Bias Supply for Analog Circuits, Audio System, Instruments.

Part No.	Output Current (I _O)	Dropout Voltage Typ. (V)	Output Voltage (V)	Max. V _{IN} (V)	Package
GM78L00	100mA	1.7	5, 6, 8, 9, 10, 12, 15, 18, 24	35~40	TO-92, SOT-89, SOP-8
GM7800	1.5A	2.0V @ 1A	5, 6, 8, 9, 10, 12, 24, 27	35~40	TO-253-2, TO-263-2, TO-220

Low Dropout Voltage Regulators

- Feature:**
- Fixed or adjustable output voltage
 - Low dropout voltage- typical 1.15V
 - Output current range from 1A to 5A
 - Current limit protection
 - Thermal shutdown protection

Application :
Microprocessor Supply, Portable Consumer Electronic Devices, Desktop and Laptop PC, Post Regulators for SMPS, Battery Chargers, Telecommunication, Printer Supplies.

Part No.	Output Current (I _O)	Quiescent Current (Typ.)	Dropout Voltage Typ. (V)	Output Voltage (V)	Max. V _{IN} (V)	Package
GM1117	1.0A	7mA	1.15@1A	Adj, 1.8, 2.5 ,3.3,5.0	7	SOT-223, TO-252, TO-263 TO-220
GM1117S	1.0A	7mA	1.15@1A	Adj, 1.8, 2.5 ,3.3,5.0	15	SOT-223, TO-252, TO-263 TO-220
GM6603	3.0A	5mA	1.15@3A	Adj, 1.8, 2.5, 3.3,5.0	7	TO-252, TO-263, TO-220
GM6605	5.0A	5mA	1.15@5A	Adj, 1.8, 2.5, 3.3, 5.0	7	TO-263, TO-220

Ultra Low Dropout Voltage Regulators

- Features:**
- High output current capability up to 5A
 - Ultra Low - Dropout voltage : 350mA at full load
 - Fixed and adjustable output voltage
 - Accurate 1% guarantee tolerance
 - TTL/ CMOS compatible enable pin
 - Current limiting and thermal shut down
 - Fast transient response
 - Reversed- battery protection
 - Error flag pin indicates output out-of-regulation

Application:
Microprocessor Supply, VGA Cards, High Efficiency Linear Power Supplies, Post Regulators for Switching Power Supplies , Battery Powered Equipment, High Efficiency "Green" Computer, Low - Voltage Micro Controllers

Part No.	Output Current (I _O)	Quiescent Current (I _Q Typ.) (Supply)	Dropout Voltage Typ. (V)	Output Voltage (V)	Max. V _{IN} (V)	Shutdown Control	On/ Off Pin	Error Flag	Package
GM66102	1A	8mA	0.35	1.5, 1.8, 2.5, 3.0, 3.3, 5.0, 12	26				SOT-223, TO-252, TO-263, TO-220
GM66150	1.5A	8mA	0.35	1.5, 1.8, 2.5, 3.0, 3.3, 5.0, 12	26				SOT-223, TO-252, TO-263, TO-220
GM66151	1.5A	8mA	0.35	1.5, 1.8, 2.5, 3.0, 3.3, 5.0, 12	26	10μA	✓	✓	TO-263-5, TO-220-5
GM66152	1.5A	8mA		Adj.	26	10μA	✓		TO-263-5, TO-220-5
GM66153	1.5A	8mA		Adj.	26	10μA		✓	TO-263-5, TO-220-5
GM66300	3A			1.8, 2.5, 3.3	20	10μA			TO-220, TO-263
GM66301	3A		0.35	1.8, 2.5	20	10μA	✓	✓	TO-220-5, TO-263-5
GM66302	3A			Adj.	20	10μA	✓		TO-220-5, TO-263-5
GM66500	5A		0.4	1.8, 2.5, 3.3, 5.0	20	10μA			TO-220, TO-263
GM66501	5A		0.4	1.8, 2.5, 3.3, 5.0	20	10μA	✓	✓	TO-220-5, TO-263-5
GM78R00	1A	8mA	0.5 Max.	3.3, 5.0, 9.0, 12	26		✓		TO-220-4FPAB
GM78R00A	1A	10mA(Max)	0.5 Max.	3.3, 5.0, 9.0, 12	35		✓		TO-220-4FPAB

Ultra Low Noise CMOS LDOs

- Features:**
- Fixed or adjustable output voltage with 1%, 2% tolerance
 - Output current range from 150mA to 300mA with maximum Vin= 20V
 - Low quiescent and ultra low dropout voltage
 - Current limit and thermal shutdown
 - Reverse battery protection
 - Logic controlled enable/ disable
 - Extremely tight load and line regulation
 - Stable with minimum external components

Application:
Mobile Phone, WLAN Card , Notebook and Palm top Computers, Consumer Portable Devices, SMPS Post- Regulators, High Efficiency Linear Power Supplies, LCD Monitor/ LCM, Battery Powered Equipment

Part No.	Output Current (I _O)	Voltage Tolerance (Max)	Dropout Voltage Typ. (V)	Output Voltage (V)	Quiescent Current (I _Q Typ.) (Supply)	Max. V _{IN} (V)	On/ Off Pin	Package
GM6155	150mA	±1%	0.165	Adj, 2.5, 2.7, 2.8, 2.9, 3.0, 3.3, 3.6, 4.0, 4.2 , 5.0	0.01μA	16	✓	SOT-25
GM6156	150mA	±1%	0.165	Adj, 2.5, 2.7, 2.8, 3.0, 3.3, 3.6, 4.0, 5.0	0.01μA	16	✓	SOT-25
GM6250	250mA	±2%	0.4	1.5, 1.8, 2.5, 2.7, 2.8, 2.85, 3.0, 3.2, 3.3, 3.5, 3.6, 4.0, 4.4, 4.5, 5.0		12		SOT-23, SOT-89, TO-92
GM6251	250mA	±2%	0.4	1.8, 2.5, 2.7, 2.8, 3.0, 3.2, 3.3, 3.5, 3.6, 4.0, 4.4, 4.5, 5.0		12		SOT-25, SOT-89, TO-92
GM6350	300mA	±2%	0.6	1.5, 1.8, 2.5, 3.0, 3.3, 5.0		6.5		SOT-89