

DESCRIPTION

The LX1973A is a wide dynamic range light sensor with a very low dark current that is optimized for sensing low level light signals that typically occur under dark or darkening outdoor ambient lighting. The LX1973A has been optimized for automotive systems such as headlamp brightness control or rear view mirror contrast control. Its radical (fractional exponent) response when interfaced with an 8 bit DAC can detect levels down to 0.001 lux or levels as high as 500 lux.

The spectral response of the integrated light sensor closely emulates the human eye so it ignores light such as infrared which emits energy but doesn't aid vision. This eliminates the need for an Infrared filter required with competitor's light sensors.

The LX1973A internal circuitry consists of a diode array with Microsemi's *Best Eye*™ processing that provides a nearly perfect photopic light wavelength response curve. The sensor output feeds into a wide dynamic range compression amplifier that provides accurate resolution over five decades of ambient light. The integrated dark current cancellation circuit facilitates accurate sensing of light below 0.01 lux. The current source output of the LX1973A can be gain scaled using one external resistor.

The LX1973A is internally trimmed to an initial accuracy of 5% at room temperature and a light level of 10lux. Accuracy of 10% is maintained over the full temperature range (-40 to +85°C).



KEY FEATURES

- Nearly Perfect *Best Eye*™ Human Eye Spectral Response
- 25C Dark Current <0.005 lux
- 5 Decades Compressed Output
- 10% Accuracy Over Temperature
- Scalable Output Voltage
- No Optical Filters Needed

APPLICATIONS

- Auto headlamp control
- Auto mirror contrast control

IMPORTANT: For the most current data, consult MICROSEMI's website: <http://www.microsemi.com>
Protected By US Patents: 6,787,757; Patents Pending

PRODUCT HIGHLIGHT

PACKAGE ORDER INFO

T _A (°C)	DR	Plastic MSOP Reversed Form 8-Pin	DU	Plastic MSOP 8-pin
		RoHS Compliant / Pb-free		RoHS Compliant / Pb-free
-40 to 85		LX1973AIDR		LX1973AIDU

Note: Available in Tape & Reel. Append the letters "TR" to the part number. (i.e. LX1973AIDU-TR)

ABSOLUTE MAXIMUM RATINGS

V_{DD}	-0.3 to 6 V_{DC}
SNK/SRC (Output Compliance Voltage).....	-0.3 to $V_{DD} + 0.3V_{DC}$
SNK/SRC (Maximum Output Current).....	Internally Limited
Operating Temperature Range	-40 to +85°C
Storage Temperature Range	-40 to +100°C
RoHS / Pb-free Peak Package Solder Reflow Temperature (40 seconds maximum exposure).....	260° (+0, -5)

Notes: Exceeding these ratings could cause damage to the device. All voltages are with respect to Ground. Currents are positive into, negative out of specified terminal.

Solder reflow to follow: IPC/JEDEC J-STD-020B 7/02 Pb-SN Small Body Profile

THERMAL DATA
DR Plastic MSOP 8-Pin Reverse Form

THERMAL RESISTANCE-JUNCTION TO CASE, θ_{JC}	39°C/W
THERMAL RESISTANCE-JUNCTION TO AMBIENT, θ_{JA}	206°C/W

DU Plastic MSOP 8-Pin





THERMAL RESISTANCE-JUNCTION TO CASE, θ_{JC}	39°C/W
THERMAL RESISTANCE-JUNCTION TO AMBIENT, θ_{JA}	206°C/W

Junction Temperature Calculation: $T_J = T_A + (P_D \times \theta_{JA})$.

The θ_{JA} numbers are guidelines for the thermal performance of the device/pc-board system. All of the above assume no ambient airflow.

FUNCTIONAL PIN DESCRIPTION

Name	Description
V_{DD}	Power Supply Voltage
V_{SS}	Ground Reference for Power and Signal Output
OUT	Output Current

PACKAGE PIN OUT


RoHS / Pb-free 100% NiPdAu Finish


SIMPLIFIED BLOCK DIAGRAM


Figure 1 – Simplified block Diagram

ELECTRICAL CHARACTERISTICS

Unless otherwise specified, the following specifications apply over the operating ambient temperature $-40^{\circ}\text{C} \leq T_A \leq 85^{\circ}\text{C}$ except where otherwise noted and the following test conditions: See Note 1, $V_{DD} = 5\text{V}$.

Parameter	Symbol	Test Conditions	LX1973A			Units
			Min	Typ	Max	
Operational Voltage	V _{DD}		4.5		5.5	V
Supply Current	I _{DD}	E _V = 1.0 lux		0.2	0.25	mA
Power Supply Rejection Ratio	PSRR	V _{RIPPLE} = 100mV _{P-P} , f = 10kHz; C _{OUT} = 0.1μF	30	35		dB
Peak Spectral Response	λ _{PR}			580		nm
Infrared Response	$\frac{I_{DD}(\lambda)}{I_{DD}(\lambda_{PR})}$	E _{V(white)} = 100 lux, E _{V(810nm)} = 14.6μW/cm ² , Note 3	-5	1	5	%
Light to Current Gain	G _L	See application section for equation				
Saturation Current	I _{SAT}		570			μA
Radiant Sensitive Area				0.20		mm ²
Flat Top Package (note 5)						
Output Current	I _{OUT(0.01)}	E _V = 0.01 lux @ 25°C, Note 1,2	32	36	40	μA
Output Current	I _{OUT(1.0)}	E _V = 1.0 lux, Note 1,2	103	114	125	μA
Output Current	I _{OUT(10)}	E _V = 10 lux, Note 1,2	183	203	223	
Output Current	I _{OUT(100)}	E _V = 100 lux, Note 1,2	320	360	400	μA
Dark Current (equivalent lux)	I _{OUT (DARK)}	E _V = 0 lux, T _A = 20°C, Note 4		450	900	μLux
		E _V = 0 lux, T _A = 50°C, Note 4		2100	5000	
Dynamic Response Time (to 10% settling error point)	T _{DR}	1.0 lux to 0.01 lux		1.5	3	sec
		0.01 lux to 1.0 lux		0.2	0.5	sec
Reverse Form Package (note 6)						
Output Current	I _{OUT(0.01)}	E _V = 0.01 lux @ 25°C, Note 1,2	32	36	40	μA
Output Current	I _{OUT(1.0)}	E _V = 1.0 lux, Note 1,2	105	117	128	μA
Output Current	I _{OUT(10)}	E _V = 10 lux, Note 1,2,	187	208	229	
Output Current	I _{OUT(100)}	E _V = 100 lux, Note 1,2	333	370	407	μA
Dark Current (equivalent lux)	I _{OUT (DARK)}	E _V = 0 lux, T _A = 20°C, Note 4		450	900	μLux
		E _V = 0 lux, T _A = 50°C, Note 4		2100	5000	
Dynamic Response Time (to 10% settling error point)	T _{DR}	1.0 lux to 0.01 lux		1.5	3	sec
		0.01 lux to 1.0 lux		0.2	0.5	sec




Notes:

1. The input irradiance is supplied from a point source which is a white light emitting diode (LED); Fairchild Semiconductor part number MV8W00.
2. See Figure 2.
3. See Figure 3.

$$4. \text{ Dark Current equivalent lux at 0 lux: } EL = \left[\frac{I_{\text{OUT}}}{I_{\text{REF}}} \right]^4 \div (146 \times 10^{-9})$$

5. For Flat Top (DU Package), $I_{\text{REF}} = 5824\mu\text{A}$.

6. For Reverse Form (DR Package): $I_{\text{REF}} = 5985\mu\text{A}$

TEST CIRCUITS

Figure 2 – Operational Voltage Measurement Circuit

Figure 3 – IR Sensitivity Measurement Circuit
APPLICATION CIRCUITS

Figure 4 – Typical Application

APPLICATIONS**GENERAL DESCRIPTION**

The LX1973A produces an output current that is sensitive to the level of ambient light that falls onto the photosensitive area of the IC package. The sensitivity is amplified and compressed to provide ratio metric accuracy across several decades. The sensitivity function is:






$$I_{OUT}(P) = \frac{I_{ref}}{lux^{0.25}} \times [E_{DARK} + E_{AMBIENT}]^{0.25}$$

$I_{ref} = 113.8\mu A$ for the Flat Top package


$I_{ref} = 117\mu A$ for the Reverse Flat Top package


E_{DARK} = dark current equivalent lux expressed in lux from a white LED point source.

$E_{AMBIENT}$ = ambient illumination expressed in lux from a white LED point source.


SENSITIVITY

DARK CURRENT VS TEMP

NORMALIZED (PRE COMPRESSION)

100 LUX OUTPUT VOLTAGE (FLAT TOP)

I_{OUT} STEP RESPONSE (FLAT TOP)


Load = 10kΩ and 0µF; Photo Step = Direct Light Input of 1 lux to 0.01 lux.

I_{OUT} OVER TEMP @ 100 LUX, 10 LUX, 1 LUX


PACKAGE DIMENSIONS
DU 8-Pin Miniature Shrink Outline Package (MSOP)




Dim	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	—	1.10	—	0.043
A1	0.05	0.15	0.002	0.006
b	0.26	0.41	0.010	0.016
c	0.13	0.23	0.005	0.009
D	2.90	3.10	0.114	0.122
e	0.65 BSC		0.025 BSC	
E	4.75	5.05	0.187	0.198
E1	2.90	3.10	0.114	0.122
L	0.41	0.71	0.016	0.028
L1	0.95 BSC		0.037 BSC	
S	0.525 BSC		0.021 BSC	
Θ	3°		3°	

DR 8-Pin Miniature Shrink Outline Package (MSOP) Reversed Form


Dim	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	—	1.100	—	0.043
A1	0.050	0.150	0.002	0.006
b	0.280	0.380	0.011	0.015
C	0.130	0.230	0.005	0.009
D	2.900	3.100	0.114	0.122
E	4.750	5.050	0.187	0.198
E1	2.900	3.100	0.114	0.122
e	0.650 BSC		0.025 BSC	
L	0.406	0.686	0.016	0.027
L1	0.940 REF		0.037 REF	
Ø	8°		8°	

Note:


Dimensions do not include mold flash or protrusions; these shall not exceed 0.155mm(.006") on any side. Lead dimension shall not include solder coverage.

PACKAGE INFORMATION
Package Land Pattern




PRODUCTION DATA SHEET

www.Microsemi.COM



Page 9

MECHANICALS



LX1973A

Automotive Light Sensor

PRODUCTION DATA SHEET

NOTES

PRODUCTION DATA – Information contained in this document is proprietary to Microsemi and is current as of publication date. This document may not be modified in any way without the express written consent of Microsemi. Product processing does not necessarily include testing of all parameters. Microsemi reserves the right to change the configuration and performance of the product and to discontinue product at any time.