

M2001 Series

5x7 mm, 3.3 Volt, CMOS/LVPECL/LVDS, Clock Oscillator



- Low cost oscillator series with jitter performance optimized specifically for Fibre Channel applications. CMOS, LVPECL, and LVDS versions available.
- Ideal for Fibre Channel, Storage Area Networks (SAN), and HDD Control

Ordering Information		00.0000 MHz	
Product Series	M2001	1	5
Temperature Range	1: 0°C to +70°C 2: -40°C to +85°C 6: -20°C to +70°C 7: -0°C to +85°C 8: 0°C to +50°C	T	L
Stability	3: ±100 ppm 4: ±50 ppm 6: ±25 ppm 5: ±35 ppm	N	
Output Type	F: Fixed T: Tristate		
Symmetry/Output Logic Type	C: 45/55% CMOS L: 45/55% LVDS P: 45/55% PECL		
Package/Lead Configurations	N: Leadless Ceramic		
Frequency (customer specified)			

Electrical Specifications	PARAMETER	Symbol	Min.	Typ.	Max.	Units	Condition/Notes
	Frequency Range	F	53.125		125	MHz	CMOS
			53.125		156.25	MHz	PECL/LVDS
	Operating Temperature	T _A	(See Ordering Information)				
	Storage Temperature	T _s	-55		+125	°C	
	Frequency Stability	ΔF/F	(See Ordering Information)				See Note 1
	Aging						
	1st Year			±2		ppm	
	Thereafter (per year)			±1		ppm	
	Input Voltage	V _{cc} /V _{dd}	3.135	3.3	3.465	V	
	Input Current	V _{dd} /I _{dd}			60	mA	CMOS/LVDS
					100	mA	PECL
	Output Type						CMOS/PECL/LVDS
	Load		15 pF 50 Ohms to V _{cc} -2 VDC 100 Ohm differential load				CMOS (See Note 2) PECL (See Note 3) LVDS (See Note 4)
	Symmetry (Duty Cycle) (Per Symmetry Code)		45	50	55	%	50% V _{dd} (CMOS)
			45	50	55	%	V _{cc} -1.3 VDC (PECL)
			45	50	55	%	1.25 VDC (LVDS)
	Output Skew				200	ps	PECL
	Differential Voltage	V _o	250	340	450	mV	LVDS
	Logic "1" Level	V _{oh}	90% V _{dd} V _{cc} -1.02 1.375			V V V	CMOS PECL LVDS
	Logic "0" Level	V _{ol}			10% V _{dd} V _{cc} -1.63 1.125	V V V	CMOS PECL LVDS
	Output Current		-4		+4	mA	CMOS
	Rise/Fall Time	T _r /T _f		0.35 .50	3 0.55 1.0	ns ns ns	CMOS @ 20/80% LVPECL @ 20/80% LVDS @ 20/80%
	Tristate Function		80% V _{dd} min or floating: output active 20% V _{dd} max: output disables to high-Z				
	Start up Time		5				ms
	Peak to Peak Jitter (+/-)	T _J		10 15	15 20	ps ps	@ BER 1E-12 (See Note 5) CMOS PECL/LVDS


1. Inclusive of initial tolerance, deviation over temperature, shock, vibration, voltage, and aging.
2. See load circuit diagram #2.
3. See load circuit diagram #5.
4. See load circuit diagram #9.
5. See jitter test circuit in Figure 1.

MtronPTI reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application.


Please see www.mtronpti.com for our complete offering and detailed datasheets. Contact us for your application specific requirements: MtronPTI 1-800-762-8800.

M2001 Series


5x7 mm, 3.3 Volt, CMOS/LVPECL/LVDS, Clock Oscillator




CMOS Output



LVPECL/LVDS Output




SUGGESTED SOLDER PAD LAYOUT



Pin Connections

PIN	FUNCTION
1	Tristate/NC
2	Ground
3	Output
4	+Vdd


SUGGESTED SOLDER PAD LAYOUT



Pin Connections

PIN	FUNCTION
1	Tristate
2	N/C
3	Ground
4	Output1/ Q
5	Output2/ Q̅
6	+Vdd

Figure 1



MtronPTI Lead Free Solder Profile

