EMC1102

SST Compliant Hardware Monitor with Two Temperature Channels

PRODUCT FEATURES

Data Brief

GENERAL DESCRIPTION

The EMC1102 is a one-wire sensor that is capable of monitoring up to two temperature zones for an Intel PC platform containing an SST host. The two temperature zones consist of an internal temperature diode and an externally connected temperature diode. In cooperation with a host device, thermal management and fan control can be performed. Communication takes place over a one-wire SST based interface. The internal 11-bit delta-sigma ADC architecture provides superb linearity, high accuracy, and excellent noise immunity.

APPLICATIONS

- Desktop PCs, Servers and Workstations

FEATURES

- Single Wire Interface (SST based)
  - SST 1.0 compliant
  - Fixed Address, Discoverable Device
  - Nine programmable addresses
  - Supports FCS Abort functionality not available in SST 0.9 compliant devices
- Resistance Error Correction
- Ideality Configuration
- Beta Compensation
- External Temperature Monitor
  - 0.125°C resolution
  - ±1°C Accuracy (50°C to 70°C)
  - Diode Fault Reporting
- Internal Temperature Monitor
  - Range -40°C to +125°C
  - 0.125°C resolution
  - ±2°C Accuracy (40°C to 70°C)
- Supply
  - 3.0V to 3.6V

SIMPLIFIED BLOCK DIAGRAM



ORDER NUMBER:

EMC1102-ACZL-TR FOR 8 PIN, MSOP LEAD-FREE ROHS COMPLIANT PACKAGE

80 Arkay Drive
Hauppauge, NY 11788
(631) 435-6000
FAX (631) 273-3123

Package Outline



REVISION HISTORY

REVISION	DESCRIPTION	DATE	RELEASED BY
-	SEE SPEC FRONT PAGE FOR REVISION HISTORY	-	-

COMMON DIMENSIONS

SYMBOL	MIN	NOM	MAX	NOTE	REMARK
A	0.80	–	1.10	–	OVERALL PKG HEIGHT
A1	0.05	–	0.15	–	STANDOFF
A2	0.75	0.85	0.95	–	BODY THICKNESS
D	2.80	3.00	3.20	3	"X" BODY SIZE
E	4.65	4.90	5.15	–	LEAD SPAN
E1	2.80	3.00	3.20	3	"Y" BODY SIZE
L	0.40	–	0.80	4	LEAD FOOT LENGTH
L1		0.95 REF		–	LEAD LENGTH
b	0.22	–	0.38	2	LEAD WIDTH
c	0.08	–	0.23	–	LEAD FOOT THICKNESS
e		0.65 BSC		–	LEAD PITCH
ccc	–	–	0.10	–	COPLANARITY

NOTES:

1. ALL DIMENSIONS ARE IN MILLIMETER.
2. TOLERANCE ON THE TRUE POSITION OF THE LEADS IS ± 0.065mm MAXIMUM.
3. PACKAGE BODY DIMENSIONS "D" AND "E1" DO NOT INCLUDE MOLD PROTRUSIONS OR FLASH. MAXIMUM MOLD PROTRUSIONS OR FLASH IS 0.15 mm (0.006 INCHES) PER END AND SIDE. DIMENSIONS "D" AND "E1" ARE DETERMINED AT DATUM PLANE "H".
4. DIMENSION FOR FOOT LENGTH "L" IS MEASURED AT THE GAUGE PLANE 0.25mm ABOVE THE SEATING PLANE.
5. DETAILS OF PIN 1 IDENTIFIER ARE OPTIONAL, BUT MUST BE LOCATED WITHIN THE ZONE INDICATED.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS AND TOLERANCES ARE:
DECIMAL X.X ±0.1, X.XX ±0.05, X.XXX ±0.025 ANGULAR ±1°
DIM AND TOL PER ASME Y14.5M - 1994
MATERIAL -
FINISH -
PRINT WITH "SCALE TO FIT" DO NOT SCALE DRAWING

THIRD ANGLE PROJECTION

	NAME	DATE
DRAWN	S.K.ILIEV	7/05/04
CHECKED	S.K.ILIEV	7/05/04
APPROVED	S.K.ILIEV	7/07/04

80 ARKAY DRIVE HAUPPAUGE, NY 11788 USA
SMSC SUCCESS BY DESIGN

TITLE: PACKAGE OUTLINE 8 PIN TSSOP, 3x3 MM BODY, 0.65 MM PITCH
DWG NUMBER: MO-8-TSSOP-3x3 REV: D
SCALE: 1:1 STD COMPLIANCE: JEDEC: MO-187 / D SHEET: 1 OF 1

Figure 1 EMC1102 8-Pin MSOP Package Drawing