


CDBB320-G Thru CDBB3100-G

Reverse Voltage: 20 - 100 Volts
Forward Current: 3.0 Amp
RoHS Device




Features

- Ideal for surface mount applications
- Easy pick and place
- Plastic package has Underwriters Lab. flammability classification 94V-0
- Built-in strain relief
- Low forward voltage drop

Mechanical data

- Case: JEDEC DO-214AA molded plastic
- Terminals: solderable per MIL-STD-750, method 2026
- Polarity: Color band denotes cathode end
- Approx. Weight: 0.093 gram



Maximum Ratings and Electrical Characteristics

Parameter	Symbol	CDBB320-G	CDBB340-G	CDBB360-G	CDBB380-G	CDBB3100-G	Unit
Max. Repetitive Peak Reverse Voltage	V _{RRM}	20	40	60	80	100	V
Max. DC Blocking Voltage	V _{DC}	20	40	60	80	100	V
Max. RMS Voltage	V _{RMS}	14	28	42	56	70	V
Peak Surge Forward Current 8.3ms single half sine-wave superimposed on rate load (JEDEC method)	I _{FSM}	80					A
Max. Average Forward Current	I _o	3.0					A
Max. Instantaneous Forward Current at 3.0 A	V _F	0.50		0.75	0.85		V
Max. DC Reverse Current at Rated DC Blocking Voltage Ta=25°C Ta=100°C	I _R	0.5					mA
		20			10		
Max. Thermal Resistance (Note 1)	RθJA	50					°C/W
	RθJL	10					
Max. Operating Junction Temperature	T _j	125					°C
Storage Temperature	T _{STG}	- 65 to +150					°C

Note 1: Thermal resistance from junction to ambient and junction to lead P.C.B. Mounted on 0.2 x 0.2 inch² copper pad areas



Rating and Characteristic Curves (CDBB320-G Thru CDBB3100-G)

Fig. 1 - Reverse Characteristics




Fig. 2 - Forward Characteristics




Fig. 3 - Junction Capacitance




Fig. 4 - Current Derating Curve




Fig. 5 - Non Repetitive Forward Surge Current

