



SAW Components

Data Sheet B3520

Data Sheet

An abstract, grayscale graphic featuring a stylized, three-dimensional representation of the EPCOS logo. The letters "EPCOS" are rendered in a bold, sans-serif font, appearing to be part of a larger, curved structure that resembles a globe or a stylized wave. The background is dark and textured, with light reflecting off the surfaces of the logo.



SAW Components

B3520

Low Loss Filter for Automotive Telematics

1575,42 MHz

Data Sheet


Ceramic package **DCC6C**

Features

- RF low-loss filter for GPS application
- Package for **Surface Mounted Technology (SMT)**
- Hermetically sealed ceramic package
- No matching network required for operation at 50 Ω
- Extended temperature range for automotive application

Terminals


- Ni, gold plated



Dimensions in mm, approx. weight 0,1 g

Pin configuration

- 2 Input
- 5 Output
- 1,3,4,6 Ground



Type	Ordering code	Marking and Package according to	Packing according to
B3520	B39162-B3520-U410	C61157-A7-A56	F61074-V8070-Z000

Electrostatic Sensitive Device (ESD)

Maximum ratings

Operable temperature range	T_A	-40/+105	$^{\circ}\text{C}$	
Storage temperature range	T_{stg}	-40/+105	$^{\circ}\text{C}$	
DC voltage	V_{DC}	0	V	
Source power	P_S	0	dBm	source impedance 50 Ω



SAW Components

B3520

Low Loss Filter for Automotive Telematics

1575,42 MHz

Data Sheet

Characteristics

Reference temperature: $T_A = -40 \dots +85 \text{ }^\circ\text{C}$
 Terminating source impedance: $Z_S = 50 \Omega$
 Terminating load impedance: $Z_L = 50 \Omega$

		min.	typ.	max.	
Center frequency	f_c	—	1575,42	—	MHz
Maximum insertion attenuation					
1574,22 ...1576,62 MHz	$\alpha_{\max}$	—	1,3	1,8	dB
Amplitude ripple (p-p)	$\Delta\alpha$				
1574,22 ...1576,62 MHz		—	0,1	1,0	dB
Relative attenuation (relative to $\alpha_{\max}$)	α_{rel}				
100,00 ...1450,00 MHz		40	44	—	dB
1450,00 ...1520,00 MHz		30	34	—	dB
1640,00 ...1710,00 MHz		25	30	—	dB
1710,00 ...1750,00 MHz		35	43	—	dB
1750,00 ...1910,00 MHz		42	44	—	dB
1910,00 ...2000,00 MHz		40	45	—	dB
Temperature coefficient of frequency	TC_f	—	-30	—	ppm/K



SAW Components

B3520

Low Loss Filter for Automotive Telematics

1575,42 MHz

Data Sheet

Characteristics

Reference temperature: $T_A = -40 \dots +105 \text{ }^\circ\text{C}$
Terminating source impedance: $Z_S = 50 \Omega$
Terminating load impedance: $Z_L = 50 \Omega$

		min.	typ.	max.	
Center frequency	f_c	—	1575,42	—	MHz
Maximum insertion attenuation					
1574,22 ...1576,62 MHz	$\alpha_{\max}$	—	1,3	2,0	dB
Amplitude ripple (p-p)	$\Delta\alpha$				
1574,22 ...1576,62 MHz		—	0,1	1,0	dB
Relative attenuation (relative to $\alpha_{\max}$)	α_{rel}				
100,00 ...1450,00 MHz		40	44	—	dB
1450,00 ...1520,00 MHz		30	34	—	dB
1640,00 ...1710,00 MHz		25	30	—	dB
1710,00 ...1750,00 MHz		35	43	—	dB
1750,00 ...1910,00 MHz		42	44	—	dB
1910,00 ...2000,00 MHz		40	45	—	dB
Temperature coefficient of frequency	TC_f	—	-30	—	ppm/K



SAW Components


B3520

Low Loss Filter for Automotive Telematics


1575,42 MHz

Data Sheet

Transfer function



Transfer function (wideband)





SAW Components

B3520

Low Loss Filter for Automotive Telematics

1575,42 MHz

Data Sheet

Published by EPCOS AG

Surface Acoustic Wave Components Division, SAW CE AE PD

P.O. Box 80 17 09, D-81617 München

© EPCOS AG 2004. All Rights Reserved. Reproduction, publication and dissemination of this brochure and the information contained therein without EPCOS' prior express consent is prohibited.

The information contained in this brochure describes the type of component and shall not be considered as guaranteed characteristics. Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise agreed.

This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.