

LED lamp

φ1.8~φ3.1丸型フレームタイプLED

Lead frame type φ1.8~φ3.1 LED

Ta=25°C

機 種 名 Type No.		ピーク発光波長 Peak-emission wavelength nm (Color)	発 光 外 観 Lens appearance	絶対最大定格 Absolute maximum ratings				電気光学的特性 Electro-optical characteristics						半値角 Half-intensity angle θ 1/2 deg.
				If	V _r	P _o	T _{opr}	V _f Typ.	If	Luminous intensity Lv Typ.		In Max.		
										mA	V		mW	
φ1.8	SLP-144B-51	700 (R)	Color diffused	25	3	70	-25~+80	1.9	5	0.5	5	10	140	
	SLP-244B-51	565 (G)	Color diffused	25	3	70	-25~+80	2.1	20	1.2	20	10	140	
	SLP-444B-51	585 (Y)	Color diffused	25	3	70	-25~+80	2.1	20	5.0	20	10	140	
φ2.0	SLP-190B-51	700 (R)	Color diffused	25	3	70	-25~+80	1.9	5	0.7	5	10	125	
	SLP-290B-51	565 (G)	Color diffused	25	3	70	-25~+80	2.1	20	3.0	20	10	125	
	SLP-490B-51	585 (Y)	Color diffused	25	3	70	-25~+80	2.1	20	6.5	20	10	125	
φ2.4	SLP-177B-51	700 (R)	Color diffused	25	3	70	-25~+80	1.9	5	1.1	5	10	100	
	SLP-277B-51	565 (G)	Color diffused	25	3	70	-25~+80	2.1	20	3.5	20	10	100	
	SLP-477B-51	585 (Y)	Color diffused	25	3	70	-25~+80	2.1	20	8.0	20	10	100	
φ3.0	SLP-135B-51	700 (R)	Color diffused	25	3	70	-25~+80	1.9	5	1.2	5	10	55	
	SLP-235B-51	565 (G)	Color diffused	25	3	70	-25~+80	2.1	20	4	20	10	55	
	SLP-335A-51	567 (Y.G)	Clear	25	3	70	-25~+80	2.1	20	100	20	10	35	
	SLP-435B-51	585 (Y)	Color diffused	25	3	70	-25~+80	2.1	20	4.4	20	10	55	
	SLP-535A-51	580 (U.V.A)	Clear	25	3	70	-25~+80	2.1	20	7.0	20	10	55	
φ3.1	SLP-255A-51	565 (U.V.A)	Clear	25	3	70	-25~+80	2.1	20	2.0	20	10	55	
	SLP-189C-51	700 (R)	Colored clear	25	3	70	-25~+80	1.9	5	4	5	10	60	
	SLP-289C-51	565 (G)	Colored clear	25	3	70	-25~+80	2.1	20	28	20	10	60	
	SLP-489C-51	585 (Y)	Colored clear	25	3	70	-25~+80	2.1	20	30	20	10	60	

お知らせ

フロー対応の高耐熱仕様LEDランプも用意しておりますので、お問い合わせ下さい。

(機種概要 発光部形状: φ3.0、φ3.1

リードテーピング仕様: ストレートテーピング品、フォーミングテーピング品)

■外観図 Package dimensions

Tolerance : ±0.2
Unit : mm

