

DB LECTRO^U

■ DIMENSIONS

D x L (mm)

uF \ WV	4	6.3	10	16	25	35	50	63
0.1						]	4 x 7	4 x 7
0.22						]	4 x 7	4 x 7
0.33						]	4 x 7	4 x 7
0.47						]	4 x 7	4 x 7
1						]	4 x 7	4 x 7
2.2						]	4 x 7	4 x 7
3.3						]	4 x 7	4 x 7
4.7						]	4 x 7	4 x 7
10			]	4 x 7	4 x 7	4 x 7	5 x 7	5 x 7
22		]	4 x 7	4 x 7	5 x 7	5 x 7	6.3 x 7	6.3 x 7
33		]	4 x 7	4 x 7	5 x 7	6.3 x 7	8 x 7	
47		]	4 x 7	5 x 7	6.3 x 7	6.3 x 7		
100	5 x 7	5 x 7	5 x 7	6.3 x 7	6.3 x 7			
220	6.3 x 7	6.3 x 7	6.3 x 7	8 x 7				
330	6.3 x 7	8 x 7	8 x 7					
470	8 x 7	8 x 7						

■ PERMISSIBLE RIPPLE CURRENT

mA (rms) at 120Hz 85°C

uF \ WV	4	6.3	10	16	25	35	50	63
0.1						]	3	4
0.22						]	3	4
0.33						]	5	6
0.47						]	6	7
1						]	10	12
2.2						]	18	20
3.3						]	22	25
4.7						]	27	31
10			]	28	31	34	42	47
22		]	36	42	48	54	58	83
33		]	45	54	60	69	95	
47		]	56	65	86	91		
100	60	73	80	93	102			
220	112	135	145	170				
330	128	150	184					
470	155	190						