



SAW Components

SAW Tx filter

Cellular / WCDMA Band V

Series/type:	B9426
Ordering code:	B39841B9426M410
Date:	September 18, 2006
Version:	2.0


Data sheet

Application


- Low-loss RF filter for mobile telephone
Cellular and WCDMA systems, transmit path (TX)
- Impedance transformation from 200Ω to 50Ω
- Balanced to unbalanced operation
- Very low insertion attenuation
- Usable passband 25 MHz


Features

- Package size $1.4 \times 1.1 \times 0.4 \text{ mm}^3$
- Package code QCS5I
- RoHS compatible
- Approximate weight 0.003 g
- Package for **Surface Mount Technology (SMT)**
- Ni, gold-plated terminals
- **Electrostatic Sensitive Device (ESD)**


Pin configuration

- 1 Output, unbalanced
- 3,4 Input, balanced
- 2,5 To be grounded





SAW Components	B9426
SAW Tx filter	836.5 MHz

Data sheet



Characteristics

Temperature range for specification:	T = -30 °C to +85 °C
Terminating source impedance:	Z _S = 200 Ω 91 nH (balanced)
Terminating load impedance:	Z _L = 50 Ω

						B9426			
						min.	typ. @ 25 °C	max.	
Center frequency	f _C					—	836.5	—	MHz
Maximum insertion attenuation									
	824.0	...	849.0	MHz	α _{max}	—	1.6	2.3	dB
@f _{Carrier}	826.4	...	846.6	MHz	α _{WCDMA} ¹⁾	—	1.5	2.0	dB
Amplitude ripple (p-p)	Δα								
	824.0	...	849.0	MHz		—	0.5	1.2	dB
Error Vector Magnitude²⁾	EVM								
@f _{Carrier}	826.4	...	846.6	MHz		—	2.0		%
Input VSWR	824.0	...	849.0	MHz		—	1.7	2.0	
Output VSWR	824.0	...	849.0	MHz		—	1.7	2.0	
Output amplitude balance	(S ₃₁ /S ₂₁)								
	824.0	...	849.0	MHz		-1	-0.2 / 0.6	+1	dB
Output phase balance	(φ(S ₃₁) - φ(S ₂₁)+180°)								
	824.0	...	849.0	MHz		-8	-5 / 4	+8	°
Attenuation	α								
	0.0	...	800.0	MHz		35	40	—	dB
	869.0	...	894.0	MHz		38	40	—	dB
@f _{Carrier}	871.4	...	891.6	MHz	α _{WCDMA} ¹⁾		41	—	dB
	1574.4	...	1576.4	MHz		40	54	—	dB
	1638.0	...	1708.0	MHz		40	52	—	dB
	2462.0	...	2557.0	MHz		35	46	—	dB
	3286.0	...	3406.0	MHz		40	52	—	dB
	3406.0	...	4500.0	MHz		40	50	—	dB
	4500.0	...	6000.0	MHz		35	40	—	dB

¹⁾ Attenuation of WCDMA signal ("Powertransferfunction") determined by

$$\int_{-\infty}^{\infty} |S_{ds21}(f) H_{RRC}(f - f_{Carrier})|^2 df$$

f_{Carrier} according to 3GPP TS 25.101 (e.g. for Passband f_{Carrier} ranges from 826.4 MHz (lowest Tx channel) to 846.6 MHz (highest Tx channel)). H_{RRC}(f) is the transfer function of the root-raised cosine transmit pulse shaping filter according to 3GPP TS 25.101 with the following normalization:

$$\int_{-\infty}^{\infty} |H_{RRC}(f)|^2 df = 1$$


²⁾ Error Vector Magnitude (EVM) based on definition given in 3GPP TS 25.141

**SAW Components****B9426****SAW Tx filter****836.5 MHz****Data sheet****Maximum ratings**


Operable temperature range	T	−40/+85	°C	Machine model, 10 pulses
Storage temperature range	T _{stg}	−40/+85	°C	
DC voltage	V _{DC}	5	V	
ESD voltage	V _{ESD}	100 ¹⁾	V	
Input Power	P _{IN}	13	dBm	

¹⁾ acc. to JESD22-A115A (machine model), 10 negative & 10 positive pulses.

Transfer function (dashed: Powertransferfunction for WCDMA signals)



Transfer function (wideband)





Data sheet



Smith charts



S_{11} function (unbalanced output)

RHOIN



S_{22} function (balanced input)

RHOOUT



**SAW Components****B9426****SAW Tx filter****836.5 MHz**

Data sheet

**References**

Type	B9426
Ordering code	B39841B9426M410
Marking and package	C61157-A8-A3
Packaging	F61074-V8212-Z000
Date codes	L_1126
S-parameters	B9426_NB.s3p B9426_WB.s3p
Soldering profile	S_6001
RoHS compatible	defined as compatible with the following documents: "DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment. 2005/618/EC from April 18th, 2005, amending Directive 2002/95/EC of the European Parliament and of the Council for the purposes of establishing the maximum concentration values for certain hazardous substances in electrical and electronic equipment."
Moldability	Before using in overmolding environment, please contact your EPCOS sales office.

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com .

**Published by EPCOS AG
Surface Acoustic Wave Components Division
P.O. Box 80 17 09, 81617 Munich, GERMANY**

© EPCOS AG 2006. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

Please read *cautions and warnings and important notes* at the end of this document.



Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of passive electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of a passive electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of a passive electronic component.
3. The warnings, cautions and product-specific notes must be observed.
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as "hazardous")**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, CeraDiode, CSSP, PhaseCap, PhaseMod, SIFI, SIKOREL, SilverCap, SIMID, SIOV, SIP5D, SIP5K, TOPcap, UltraCap, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.