

CONAN®

High Density, Low Profile 1.00mm Pitch Mezzanine Connectors

C - Series for Demanding Commercial Electronics Applications

DESCRIPTION

The Conan 1.0mm mezzanine connector system provides a mechanically secure, high density electrical interface between parallel printed circuit boards.

Conan's mechanical features and palladium/nickel/gold plated electrical contacts qualify it for high reliability use in durable commercial electronic equipment and instruments.



FEATURES & BENEFITS

- "Snap" engagement contacts assure secure mating with an audible "click"
- Blade-on-beam contact design allows "peeling" disengagement and prevents contact stubbing
- Connector housings feature "lead-in" angles to assist in mating
- Surface mounted metal hold-downs reinforce connector retention to the printed circuit board
- Mating polarization prevents backward connections
- PCB polarization prevents errors during printed circuit board assembly
- Pick and place caps with tape and reel packaging support automated assembly processes
- Header height options support a range of PCB stack heights: 4.15mm to 7mm
- 9 part sizes: 9 to 69 contacts
- Lead-free RoHS compatible products satisfy environmental regulations

TARGET MARKETS / APPLICATIONS

- Portable meters / instruments
- Medical diagnostics
- Point-of-sale equipment, scanning
- Machine-to-Machine (M2M)
- Energy controllers / modules / displays
- Communications and networking equipment
- Electronic security
- Office equipment

MEZZ Select™

C - Series for Demanding Commercial Electronics Applications

MATERIALS

- Contact base metal
 - Header: Phosphor bronze
 - Receptacle: Copper Alloy, High Spring
- Contact area finish: gold or GXT
- Solder area finish: Pure tin over 1.27µm (50uin.) nickel
- Housing material: Cream-colored LCP (UL 94V-0)

MECHANICAL PERFORMANCE

- Mating force: 125g per contact max
- Unmating force: 25g per contact min
- Retention force (connector to PCB): 44 N (10lbf) min
- Contact wipe: 0.64mm (0.025 in.)
- Durability: 30 mating cycles

ELECTRICAL PERFORMANCE

- Insulation resistance: 1000 MΩ min
- Contact resistance: 30 mΩ max
- Withstanding voltage: 500 V ac, rms, 60 Hz
- Current rating: 1.0 amp continuous (per contact, all contacts powered)
- Signal Integrity (differential pairs, connector only)
 - Impedance: 100Ω +/- 10% @ 50 ps edge (10-90%)
 - Insertion Loss: < 1dB to 5GHz
 - NEXT: ≤3.5% for a 50 ps edge (10-90%)
 - FEXT: ≤2.5% for a 50 ps edge (10-90%)

ENVIRONMENTAL PERFORMANCE

- IMFG per EIA 364-65 class 2a without SO₂, 20 days mated
- High temperature life 105°C

SPECIFICATIONS

- GS-12-0977

PACKAGING

- Tape and reel with vacuum pickup caps

PART NUMBERS

10118744 - T 133 Y ZZ LF


LEAD FREE

TYPE	T
PLUG WITH PEGS	1
RECEPTACLE WITH PEGS	3

Y	HEADER HEIGHT	RECEPTACLE HEIGHT	MATED HEIGHT
1	.034 [.86]	.129 [3.28]	.163 [4.15]
2	.048 [1.23]	SEE Y=1 FOR ALL RECEPTACLES	.177 [4.50]
3	.068 [1.73]		.197 [5.00]
4	.107 [2.72]		.236 [6.00]
5	.1465 [3.721]		.276 [7.00]

ZZ	NUMBER OF POSITIONS
09	9
11	11
15	15
21	21
25	25
31	31
41	41
51	51
69	69

For additional configurations and packaging please consult print 91900 at www.fciconnect.com



Mated connector max.width: .220" (5.59mm)

For more information please contact: elxcommunications@fci.com

www.fciconnect.com/conan