

**Solid State Devices, Inc.**

14701 Firestone Blvd \* La Mirada, Ca 90638  
 Phone: (562) 404-4474 \* Fax: (562) 404-1773  
 ssdi@ssdi-power.com \* www.ssdi-power.com

**SPD502-SPD506  
 and  
 SPD502SMS - SPD506SMS**

**DESIGNER'S DATA SHEET****Part Number / Ordering Information<sup>1/</sup>****SPD5**

**Screening**<sup>2/</sup> = None  
                   TX = TX Level  
                   TXV = TXV Level  
                   S = S Level

**Package**

\_\_\_\_\_ = Axial Leaded  
 \_\_\_\_\_ = SMS = Surface Mount Square Tab

**Voltage**

02 = 200 V  
 03 = 300 V  
 04 = 400 V  
 05 = 500 V  
 06 = 600V

**5 AMP  
 200–600 Volts  
 40 nsec  
 HYPER FAST RECTIFIER**

**Features:**



- Hyper Fast Recovery: 40 nsec Max.
- PIV to 600 Volts
- Low Forward Voltage Drop
- Void Free Construction
- Hermetically Sealed Surface Mount Package
- For High Efficiency Applications
- Single Chip Construction
- TX, TXV, and S-Level Screening Available<sup>2/</sup>

Maximum Ratings		Symbol	Value	Units
<b>Peak Repetitive Reverse and DC Blocking Voltage</b>	<b>SPD502</b>	$V_{RRM}$	200	<b>Volts</b>
	<b>SPD503</b>		300	
	<b>SPD504</b>	$V_{RWM}$	400	
	<b>SPD505</b>		500	
	<b>SPD506</b>	$V_R$	600	
<b>Average Rectified Forward Current</b> (Resistive Load, 60 Hz, Sine Wave, $T_A = 25^\circ\text{C}$ )		$I_o$	5	<b>Amps</b>
<b>Surge Current</b> (8.3 ms Pulse, Half Sine Wave Superimposed on $I_o$ , Allow Junction to Reach Equilibrium between Pulses, $T_A = 25^\circ\text{C}$ )		$I_{FSM}$	100	<b>Amps</b>
<b>Operating &amp; Storage Temperature</b>		<b>Top &amp; Tstg</b>	-65 to +175	<b>°C</b>
<b>Maximum Thermal Resistance</b>	Junction to Lead, $L=3/8"$	$R_{\theta JL}$	15	<b>°C/W</b>
	Junction to End Tab	$R_{\theta JE}$	10	

**Notes:**

<sup>1/</sup> For Ordering Information, Price, Operating Curves, and Availability – Contact Factory.

<sup>2/</sup> Screening Based on MIL-PRF-19500. Screening Flows Available on Request.

**Axial Leaded****SMS**

**NOTE:** All specifications are subject to change without notification.  
 SCD's for these devices should be reviewed by SSDI prior to release.

**DATA SHEET #: RH0105B****DOC**



**Solid State Devices, Inc.**

14701 Firestone Blvd \* La Mirada, Ca 90638


Phone: (562) 404-4474 \* Fax: (562) 404-1773

ssdi@ssdi-power.com \* www.ssdi-power.com

**SPD502-SPD506  
and  
SPD502SMS - SPD506SMS**


Electrical Characteristics	Symbol	Max	Units
<b>Instantaneous Forward Voltage Drop</b> ( $I_F = 5 \text{ A}_{dc}$ , $T_A = 25^\circ\text{C}$ , 300 $\mu\text{s}$ pulse)	$V_F$	1.6	Vdc
<b>Instantaneous Forward Voltage Drop</b> ( $I_F = 5 \text{ A}_{dc}$ , $T_A = -55^\circ\text{C}$ , 300 $\mu\text{s}$ pulse)	$V_F$	1.75	Vdc
<b>Reverse Leakage Current</b> (Rated $V_R$ , $T_A = 25^\circ\text{C}$ , 300 $\mu\text{s}$ pulse minimum)	$I_R$	10	$\mu\text{A}$
<b>Reverse Leakage Current</b> (Rated $V_R$ , $T_A = 100^\circ\text{C}$ , 300 $\mu\text{s}$ pulse minimum)	$I_R$	1	mA
<b>Junction Capacitance</b> ( $V_R = 10 \text{ Vdc}$ , $T_A = 25^\circ\text{C}$ , $f = 1\text{MHz}$ )	$C_J$	50	pF
<b>Reverse Recovery Time</b> ( $I_F = 500 \text{ mA}$ , $I_R = 1 \text{ A}$ , $I_{RR} = 0.25 \text{ A}$ , $T_A = 25^\circ\text{C}$ )	$t_{rr}$	40	nsec

**Case Outline: (Axial)**



DIMENSIONS		
DIM	MIN	MAX
A	.140"	.170"
B	.170"	.230"
C	.047"	.053"
D	1.00"	---

**Case Outline: Surface Mount Square Tab**



DIMENSIONS		
DIM	MIN	MAX
A	.172"	.180"
B	.220"	.270"
C	.020"	.035"
D	.002"	---

**NOTE:** All specifications are subject to change without notification.  
SCD's for these devices should be reviewed by SSDI prior to release.

**DATA SHEET #: RH0105B**

**DOC**