



Solid State Devices, Inc.

14701 Firestone Blvd * La Mirada, Ca 90638
Phone: (562) 404-4474 * Fax: (562) 404-1773
ssdi@ssdi-power.com * www.ssdi-power.com

SPD5817SM Thru SPD5819SM

Designer's Data Sheet

Part Number/Ordering Information^{1/}

SPD _ _ _

L Screening^{2/}

_ = Not Screened
TX = TX Level
TXV = TXV
-S = S Level

Package Type

SM = Surface Mount Round Tab

Voltage/Family

5817 = 20V
5818 = 30V
5819 = 40V

**1 AMP
20 – 40 VOLTS
SCHOTTKY RECTIFIER**

FEATURES:


- Extremely Low Forward Voltage Drop
- Hermetically Sealed Surface Mount Package
- For High Efficiency Applications
- High Surge Capability
- Axial Lead Versions Available
TX, TXV, or Space Level Screening Available^{2/}

MAXIMUM RATINGS^{3/}

RATING	SYMBOL	VALUE	UNIT
Peak Repetitive Reverse Voltage and DC Blocking Voltage SPD5817SM SPD5818SM SPD5819SM	V_{RRM} V_{RWM} V_R	20 30 40	Volts
Average Rectified Output Current (Resistive Load, 60Hz, Sine Wave, $T_A=25^\circ\text{C}$)	I_O	1	Amps
Peak Surge Current ^{3/} (8.3 ms Pulse, Half Sine Wave, superimposed on I_O , allow junction to reach equilibrium between pulses, $T_A=25^\circ\text{C}$)	I_{FSM}	25	Amps
Operating and Storage Temperature	T_{OP} & T_{STG}	-55 to +125	$^\circ\text{C}$
Maximum Thermal Resistance Junction to End Tab	$R_{\theta JE}$	40	$^\circ\text{C/W}$

NOTES:

- ^{1/} For ordering information, Price, and Availability- Contact Factory.
^{2/} Screening based on MIL-PRF-19500. Screening flows available on request
^{3/} Unless otherwise specified, all electrical ratings/characteristics @ 25°C .



SURFACE MOUNT ROUND TAB

NOTE: All specifications are subject to change without notification.
SCD's for these devices should be reviewed by SSDI prior to release.

DATA SHEET #: RS0111M

DOC



Solid State Devices, Inc.



14701 Firestone Blvd * La Mirada, Ca 90638
Phone: (562) 404-4474 * Fax: (562) 404-1773
ssdi@ssdi-power.com * www.ssdi-power.com

SPD5817SM Thru SPD5819SM

ELECTRICAL CHARACTERISTICS ^{3/}

CHARACTERISTICS		SYMBOL	MAXIMUM	UNIT
Instantaneous Forward Voltage Drop ($I_F = 1 \text{ Adc}$, $T_A = 25^\circ\text{C}$, 300-500 μs Pulse)	SPD5817SM	V_{F1}	0.55	Vdc
	SPD5818SM		0.65	
	SPD5819SM		0.70	
Instantaneous Forward Voltage Drop ($I_F = 1 \text{ Adc}$, $T_A = -55^\circ\text{C}$, 300-500 μs Pulse)	SPD5817SM	V_{F2}	0.57	Vdc
	SPD5818SM		0.67	
	SPD5819SM		0.72	
Reverse Leakage Current (Rated V_R , $T_A = 25^\circ\text{C}$, 300 μs Pulse Minimum)		I_{R1}	0.50	mA
Reverse Leakage Current (Rated V_R , $T_A = 100^\circ\text{C}$, 300 μs Pulse Minimum)		I_{R2}	10	mA
Junction Capacitance ($V_R = 5 \text{ Vdc}$, $T_A = 25^\circ\text{C}$, $f = 1 \text{ MHz}$)		C_J	120	pF

Case Outline- Surface Mount Round Tab*



DIMENSIONS

Dimension	Minimum	Maximum
ØA	.090"	.105"
B	.189"	.205"
C	.016"	.022"

Note: Dimensions are prior to solder dipping

* For information on curves, contact the Factory Representative for Engineering Assistance.

NOTE: All specifications are subject to change without notification.
SCD's for these devices should be reviewed by SSDI prior to release.

DATA SHEET #: RS0111M

DOC