



SAW Components

SAW band–stop filter

DVB–H, ISDB–TB

Series/type:	B8763
Ordering code:	B39901-B8763-P810
Date:	June 30, 2010
Version:	2.0

**SAW Components****B8763****SAW band-stop filter****897.50 MHz**


Data Sheet

**Revision history: changes compared to previous iteration issue**

ISSUE	ORIGINATOR	DETAILED SPECIFICATION CHANGES	DATE
LP92H_v1.0	M. Jungkunz	initial release	Oct 17, 2008
B8763_v1.0	M. Jungkunz	introduction of filter type name added reference to ISDB-TB added power durability value for GSM850 Tx	Feb 13, 2009
B8763_v2.0	TAY Wee Chuan	ordering code added	Jun 30, 2010


Application

- Low-loss RF band-stop filter for DVB-H and ISDB-TB
- GSM900 Tx suppression
- Very low insertion loss
- Very low amplitude ripple and group delay ripple
- Usable passband of 280 MHz up to 328 MHz
- Impedance at input and output 50 Ω
- Unbalanced to unbalanced operation




Features

- Package size $1.4 \times 1.1 \times 0.4$ mm³
- Maximum height of 0.45 mm
- Package code QCS5P
- RoHS compatible
- Approximate weight 0.003 g
- Package for Surface Mount Technology (SMT)
- Ni, gold-plated terminals
- **Electrostatic Sensitive Device (ESD)**



Pin configuration

- 1 Input unbalanced
- 4 Output unbalanced
- 3 External coupling coil
- 2,5 Case ground





SAW Components

B8763

SAW band-stop filter

897.50 MHz

Data Sheet



Characteristics

Temperature range for specification:

$T = +25\text{ °C} \pm 2\text{ °C}$

Terminating source impedance:


$Z_S = 50\ \Omega$ and matching network

Terminating load impedance:

$Z_L = 50\ \Omega$ and matching network

		min.	typ. @ 25 °C	max.	
Nominal center frequency	f_N	—	897.50	—	MHz
Minimum insertion attenuation	$\alpha_{\max}$	—	1.0	1.2	dB
470.00 ... 798.00 MHz		—	1.0	1.2	dB
Maximum insertion attenuation	$\alpha_{\max}$	—	1.6	1.9	dB
470.00 ... 750.00 MHz		—	1.6	1.9	dB
750.00 ... 798.00 MHz		—	2.1	2.4	dB
Attenuation	α				
47.00 ... 68.00 MHz		58.0	66.0		dB
174.00 ... 230.00 MHz		28.0	30.0	—	dB
880.00 ... 915.00 MHz		44.0	48.0	—	dB
1710.00 ... 1785.00 MHz		32.0	37.0	—	dB
1920.00 ... 1980.00 MHz		48.0	54.0	—	dB
Group delay ripple (p-p)	$\Delta\tau$				
470.00 ... 750.00 MHz		—	4	—	ns
470.00 ... 798.00 MHz		—	6	—	ns

Matching network



$L_{s1} = 18\text{ nH}$

$L_{p2} = 20\text{ nH}$

$L_{s3} = 13\text{ nH}$

$C_{s4} = 0.50\text{ pF}$

Q factor of inductors:
40 @ 770 MHz



SAW Components

B8763

SAW band-stop filter

897.50 MHz

Data Sheet



Characteristics

Temperature range for specification:

$T = -30\text{ °C to }+85\text{ °C}$

Terminating source impedance:


$Z_S = 50\ \Omega$ and matching network

Terminating load impedance:

$Z_L = 50\ \Omega$ and matching network

		min.	typ. @ 25 °C	max.	
Nominal center frequency	f_N	—	897.50	—	MHz
Minimum insertion attenuation	$\alpha_{\max}$	—	1.0	1.3	dB
	470.00 ... 798.00 MHz	—	1.0	1.3	dB
Maximum insertion attenuation	$\alpha_{\max}$	—	1.6	2.0	dB
	470.00 ... 750.00 MHz	—	1.6	2.0	dB
	750.00 ... 798.00 MHz	—	2.1	2.6	dB
Attenuation	α	—	—	—	dB
	47.00 ... 68.00 MHz	52.0	66.0	—	dB
	174.00 ... 230.00 MHz	25.0	30.0	—	dB
	880.00 ... 915.00 MHz	42.0	48.0	—	dB
	1710.00 ... 1785.00 MHz	30.0	37.0	—	dB
	1920.00 ... 1980.00 MHz	45.0	54.0	—	dB
Group delay ripple (p-p)	$\Delta\tau$	—	4	—	ns
	470.00 ... 750.00 MHz	—	4	—	ns
	470.00 ... 798.00 MHz	—	6	—	ns

Matching network



$L_{s1} = 18\text{ nH}$

$L_{p2} = 20\text{ nH}$

$L_{s3} = 13\text{ nH}$


$C_{s4} = 0.50\text{ pF}$

Q factor of inductors:
40 @ 770 MHz

**SAW Components****B8763****SAW band-stop filter****897.50 MHz****Data Sheet****Maximum ratings**

Operable temperature range	T	-30/+85	°C	
Storage temperature range	T _{stg}	-40/+85	°C	
DC voltage	V _{DC}	5	V	
ESD voltage	V _{ESD}	100 ¹⁾	V	machine model, 10 pulses
Source power at				
824.00 ... 849.00 MHz	P _S	24	dBm	peak power of GSM signal,
880.00 ... 915.00 MHz				duty cycle 4:8

¹⁾ according to JESD22-A115A (machine model), 10 negative & 10 positive pulses.

Transfer function



SAW Components

B8763


SAW band-stop filter

897.50 MHz


Data Sheet



Transfer function (pass band)



Transfer function (wide band)



Please read *cautions and warnings* and *important notes* at the end of this document.

**SAW Components****B8763****SAW band-stop filter****897.50 MHz**

Data Sheet

**References**

Type	B8763
Ordering code	B39901-B8763-P810
Marking and package	C61157-A8-A9
Packaging	F61074-V8212-Z000
Date codes	L_1126
S-parameters	LP92H_WB_UN.s3p (unmatched) LP92H_WB.s2p (matched)
Soldering profile	S_6001
RoHS compatible	defined as compatible with the following documents: "DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment. 2005/618/EC from April 18th, 2005, amending Directive 2002/95/EC of the European Parliament and of the Council for the purposes of establishing the maximum concentration values for certain hazardous substances in electrical and electronic equipment."
Moldability	Before using in overmolding environment, please contact your EPCOS sales office.
Matching coils	See http://www.tdk.co.jp/tefe02/coil.htm#aname1 http://www.tdk.co.jp/etvcl/index.htm for a large variety of matching coils.

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com.

Published by EPCOS AG**Surface Acoustic Wave Components Division****P.O. Box 80 17 09, 81617 Munich, GERMANY**

© EPCOS AG 2010. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

Please read *cautions and warnings and important notes* at the end of this document.



Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order.
We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CSMP, CSSP, CTVS, DeltaCap, DigiSiMic, DSSP, FormFit, MiniBlue, MiniCell, MKD, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SiMic, SIMID, SineFormer, SIOV, SIP5D, SIP5K, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.