



SAW Components

SAW filter

TD-SCDMA 2100

Series/Type:	B9467
Ordering code:	B39202B9467P810
Date:	Sep 21, 2010
Version:	2.1



SAW Components

B9467

SAW Filter

2017.5 MHz

Data sheet




Application

- Low-loss RF filter for mobile telephone TD-SCDMA systems
- Impedance transformation from 50 Ω to 200 Ω
- Unbalanced to balanced operation
- Low amplitude ripple
- Usable passband 15 MHz




Features

- Package size 1.4 x 1.1 x 0.4 mm³
- RoHS compatible
- Approx. weight 0.003g
- Package for Surface Mount Technology (SMT)
- Ni, gold-plated terminals
- Electrostatic Sensitive Device (ESD)
- Moisture Sensitive Level 3



Pin configuration

- 1 Input, unbalanced
- 3,4 Output, balanced
- 2,5 Case-ground





SAW Components

B9467

SAW Filter

2017.5 MHz

Data sheet



Characteristics

Temperature range for specification: $T = -30\text{ °C to }+85\text{ °C}$
Terminating source impedance: $Z_S = 50\ \Omega$
Terminating load impedance: $Z_L = 200\ \Omega$

		min.	typ. @ 25°C	max.	
Center frequency	f_C	—	2017.5	—	MHz
Maximum insertion attenuation	$\alpha_{\max}$	—	1.6	2.6	dB
2010.0 ... 2025.0 MHz					
Amplitude ripple (p-p)	$\Delta\alpha$	—	0.2	1.2	dB
2010.0 ... 2025.0 MHz					
Input VSWR		—	1.5	2.0	
2010.0 ... 2025.0 MHz					
Output VSWR		—	1.4	2.0	
2010.0 ... 2025.0 MHz					
Group delay ripple (p-p)		—	4	20	ns
2010.0 ... 2025.0 MHz					
Common mode rejection ratio		20	29	—	dB
2010.0 ... 2025.0 MHz					
Attenuation	α				
0 ... 1840.0 MHz		50	56	—	dB
1840.0 ... 1935.0 MHz		25	36	—	dB
1935.0 ... 1970.0 MHz		22	25	—	dB
1970.0 ... 1980.0 MHz		15	25	—	dB
1980.0 ... 1990.0 MHz		6	12	—	dB
2045.0 ... 2085.0 MHz		3	14	—	dB
2085.0 ... 2120.0 MHz		22	26	—	dB
2120.0 ... 2160.0 MHz		27	33	—	dB
2160.0 ... 2300.0 MHz		34	38	—	dB
2300.0 ... 2700.0 MHz		35	40	—	dB
2700.0 ... 2900.0 MHz		35	37	—	dB
2900.0 ... 6000.0 MHz		35	49	—	dB





SAW Components		B9467
SAW Filter		2017.5 MHz
Data sheet	SMD	

Maximum ratings

Operable temperature range	T	−40/+85	°C	machine model, 1 pulses
Storage temperature range	T _{stg}	−40/+85	°C	
DC voltage	V _{DC}	3	V	
ESD voltage	V _{ESD}	50 ¹⁾	V	
Input Power at 2010.0...2025.0 MHz	P _{IN}	12	dBm	effective power in the on-state, duty cycle 4:8

¹⁾ acc. to JESD22-A115A (machine model), 1 negative & 1 positive pulses.

**Transfer function (narrowband)****Transfer function (wideband)**



SAW Components

B9467

SAW Filter



2017.5 MHz

Data sheet





Smith chart

S_{11} function



S_{22} function



**SAW Components****B9467****SAW Filter****2017.5 MHz**

Data sheet

**References**

Type	B9467
Ordering code	B39202B9467P810
Marking and package	C61157-A8-A14
Packaging	F61074-V8237-Z000
Date codes	L_1126
S-parameters	B9467_NB.s2p B9467_WB.s2p see file header for port/pin assignment table
Soldering profile	S_6001
RoHS compatible	defined as compatible with the following documents: "DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment. 2005/618/EC from April 18th, 2005, amending Directive 2002/95/EC of the European Parliament and of the Council for the purposes of establishing the maximum concentration values for certain hazardous substances in electrical and electronic equipment."
Moldability	Before using in overmolding environment, please contact your EPCOS sales office.
Matching coils	See http://www.tdk.co.jp/tefe02/coil.htm#aname1 http://www.tdk.co.jp/etvcl/index.htm for a large variety of matching coils.

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com.

Published by EPCOS AG**Surface Acoustic Wave Components Division****P.O. Box 80 17 09, 81617 Munich, GERMANY**

© EPCOS AG 2010. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

Please read *cautions and warnings and important notes* at the end of this document.



Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of an electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as hazardous)**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order.
We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CSMP, CSSP, CTVS, DeltaCap, DigiSiMic, DSSP, FormFit, MiniBlue, MiniCell, MKD, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseCube, PhaseMod, PhiCap, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SiMic, SIMID, SineFormer, SIOV, SIP5D, SIP5K, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.