

Electro-Optical Characteristics :

$I_F @ 20mA, T_a 25^{\circ}C$

Code for Parts	Lighting Color	Material	V _F (V)		λ (nm)			I _v *(mcd)
			typ.	max.	λ_D	λ_P	$\Delta \lambda$	typ.
MLM-110PG	Pure Green	GaP	2.2	2.6	563	557	24	4.0
MLM-110UG	Super Green	GaP	2.2	2.6	567	565	24	11
MLM-110G	Green	GaP	2.2	2.6	567	565	26	8.0
MLM-110YG	Yellow Green	GaP	2.2	2.6	572	570	30	13
MLM-110Y	Yellow	GaAsP	2.1	2.6	590	589	40	8.0
MLM-110D	Amber	GaAsP	2.1	2.6	606	610	40	7.0
MLM-110SD	Super Bright Orange	GaAsP	2.1	2.6	632	642	40	13
MLM-110UR	Super Bright Red	AlGaAs	1.9	2.6	643	660	20	20
MLM-110HR	High Bright Red	AlGaAs	1.9	2.6	643	660	20	30
MLM-110R	Red	GaP	2.2	2.6	643	700	100	2.7

*NIST standards

Absolute Maximum Ratings :


$(T_a = 25^{\circ}C)$

Series	P _d (mW)	I _F (mA)	I _{FP} (mA)	V _R (V)	T _{OP} (°C)	T _{ST} (°C)
MLM-110 Series	65	25	100**	5	-30 to +80	-40 to +85
MLM-110 UR/HR	78	30				

**Condition for I_{FP} is pulse of 1/10 duty and 0.1msec width


Package Outline Dimensions :

Unit: mm Tolerance: ± 0.1



1. Soldering terminal may shift in x, y direction.
2. Polarity referring onto the cathode line is reversed on the UR / HR.

• Recommended Soldering Pattern for Reflow Soldering



To avoid LED from rotation after assembly (reflow), soldering on the fixing pad is suggested












MICRO ELECTRONICS LTD.

G/F, 38 Hung To Road, Kwun Tong, Kowloon, Hong Kong.


Kwun Tong P.O. BOX 69477, Hong Kong. TEL: (852) 23430181 FAX: (852) 23410321

Homepage: <http://www.microelectr.com.hk> E-MAIL ADDRESS: common@microelectr.com.hk


Characteristics of MLM-110 Series :



Directive Characteristics



Directive Characteristics



MICRO ELECTRONICS LTD.

G/F, 38 Hung To Road, Kwun Tong, Kowloon, Hong Kong.

Kwun Tong P.O. BOX 69477, Hong Kong. TEL: (852) 23430181 FAX: (852) 23410321

HOME PAGE: <http://www.microelectr.com.hk> E-MAIL ADDRESS: common@microelectr.com.hk