


3.0A Fast Recovery Rectifier

Features

- Fast switching for high efficiency
- High surge current capability
- High temperature soldering guaranteed 250°C/10 seconds
/.0375" (9.5mm) lead length, 5lbs (2.3kg) tension
- RoHS Compliance



DO-201AD



Mechanical Data

Case:	JEDEC DO-201AD, molded plastic body
Epoxy:	Plastic package has UL flammability classification 94V-0
Terminals:	Plated axial leads, solderable per MIL-STD-750, Method 2026
Polarity:	Color band denotes cathode end
Weight:	1.1 grams

Maximum Ratings and Electrical Characteristics ($T_A=25^\circ\text{C}$ unless noted otherwise)

Symbol	Description	MR850	MR851	MR852	MR854	MR856	MR858	Unit	Conditions
VRRM	Maximum Repetitive Peak Reverse Voltage	50	100	200	400	600	800	V	
VRMS	Maximum RMS Voltage	35	70	140	280	420	560	V	
VDC	Maximum DC Blocking Voltage	50	100	200	400	600	800	V	
IF(AV)	Maximum Average Forward Rectified Current	3.0						A	$T_A=90^\circ\text{C}$
IFSM	Peak Forward Surge Current	200						A	8.3ms single half sine-wave superimposed on rated load (JEDEC method)

3.0A Fast Recovery Rectifier

MF850 – MR858

Symbol	Description	MR850	MR851	MR852	MR854	MR856	MR858	Unit	Conditions
V _F	Maximum Instantaneous Forward Voltage	1.3						V	I _F =3.0 A
I _R	Maximum DC Reverse Current at Rated DC Blocking Voltage	10						μA	T _A =25° C
		150		200	250	300	500		T _A =100° C
T _{rr}	Typical Reverse Recovery Time	150				250	500	nS	I _F =0.5A, I _R =1A, I _{rr} =0.25A
R _{thJA} R _{thJL}	Typical Thermal Resistance	22 8.0						°C / W	Note
C _J	Typical Junction Capacitance	28						pf	V _R =4V, f=1MHz
T _J	Operating Temperature range	-50 to +150						° C	
T _{STG}	Storage Temperature Range	-50 to +150							

Note: Thermal resistance from junction to ambient and from junction to lead at 0.375"(9.5mm) lead length, with both leads equally heat sink.

Typical Characteristics Curves

Fig.1-Max. Forward Current Derating Curve





Fig.2-Max. Non-Repetitive Forward Surge Current



3.0A Fast Recovery Rectifier

MF850 – MR858

Fig.3- Typical Forward Characteristics






Fig.4- Typical Junction Capacitance



Dimensions in inches (mm)



D0-201AD

3.0A Fast Recovery Rectifier

MF850 – MR858

How to contact us:

US HEADQUARTERS

28040 WEST HARRISON PARKWAY, VALENCIA, CA 91355-4162

Tel: (800) TAITRON (800) 824-8766 (661) 257-6060

Fax: (800) TAITFAX (800) 824-8329 (661) 257-6415

Email: taitron@taitroncomponents.com

Http://www.taitroncomponents.com

TAITRON COMPONENTS MEXICO, S.A .DE C.V.

BOULEVARD CENTRAL 5000 INTERIOR 5 PARQUE INDUSTRIAL ATITALAQUIA, HIDALGO C.P.
42970 MEXICO

Tel: +52-55-5560-1519

Fax: +52-55-5560-2190

TAITRON COMPONETS INCORPORATED E REPRESENTAÇÕES DO BRASIL LTDA

RUA DOMINGOS DE MORAIS, 2777, 2.ANDAR, SALA 24 SAÚDE - SÃO PAULO-SP 04035-001 BRAZIL

Tel: +55-11-5574-7949

Fax: +55-11-5572-0052

TAITRON COMPONETS INCORPORATED, SHANGHAI REPRESENTATIVE OFFICE

CROSS REGION PLAZA, 899 LINGLING ROAD, SUITE 18C, SHANGHAI, 200030, CHINA

Tel: +86-21-5424-9942

Fax: +86-21-5424-9931