

# NL17SZ125

## Non-Inverting 3-State Buffer

The NL17SZ125 is a high performance non-inverting buffer operating from a 1.65 V to 5.5 V supply.

- Extremely High Speed:  $t_{PD}$  2.6 ns (typical) at  $V_{CC} = 5.0$  V
- Designed for 1.65 V to 5.5 V  $V_{CC}$  Operation
- Overvoltage Tolerant Inputs and Outputs
- LVTTTL Compatible – Interface Capability With 5.0 V TTL Logic with  $V_{CC} = 3.0$  V
- LVC MOS Compatible
- 24 mA Balanced Output Sink and Source Capability
- Near Zero Static Supply Current Substantially Reduces System Power Requirements
- 3-State OE Input is Active-Low
- Replacement for NC7SZ125
- Chip Complexity = 36 FETs
- Pb-Free Packages are Available




Figure 1. Pinout (Top View)




Figure 2. Logic Symbol




**ON Semiconductor®**

<http://onsemi.com>

### MARKING DIAGRAM

  
SC-88A (SOT-353)  
DF SUFFIX  
CASE 419A



SOT-553  
XV5 SUFFIX  
CASE 463B



M0 = Specific Device Code

D = Date Code

■ = Pb-Free Package

(Note: Microdot may be in either location)

\*Date Code orientation and/or position may vary depending upon manufacturing location.

### PIN ASSIGNMENT

|   | PIN ASSIGNMENT  |
|---|-----------------|
| 1 | $\overline{OE}$ |
| 2 | IN A            |
| 3 | GND             |
| 4 | OUT Y           |
| 5 | $V_{CC}$        |

### FUNCTION TABLE

| $\overline{OE}$ Input | A Input | Y Output |
|-----------------------|---------|----------|
| L                     | L       | L        |
| L                     | H       | H        |
| H                     | X       | Z        |

X = Don't Care

### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 6 of this data sheet.

## MAXIMUM RATINGS

| Symbol           | Parameter                                       | Value                                                                                | Unit                   |
|------------------|-------------------------------------------------|--------------------------------------------------------------------------------------|------------------------|
| V <sub>CC</sub>  | DC Supply Voltage                               | −0.5 to +7.0                                                                         | V                      |
| V <sub>IN</sub>  | DC Input Voltage                                | −0.5 to +7.0                                                                         | V                      |
| V <sub>OUT</sub> | DC Output Voltage                               | −0.5 to +7.0                                                                         | V                      |
| I <sub>IK</sub>  | DC Input Diode Current                          | −50                                                                                  | mA                     |
| I <sub>OK</sub>  | DC Output Diode Current                         | −50                                                                                  | mA                     |
| I <sub>OUT</sub> | DC Output Sink Current                          | ± 50                                                                                 | mA                     |
| I <sub>CC</sub>  | DC Supply Current per Supply Pin                | ± 100                                                                                | mA                     |
| T <sub>STG</sub> | Storage Temperature Range                       | −65 to +150                                                                          | °C                     |
| T <sub>L</sub>   | Lead Temperature, 1 mm from Case for 10 Seconds | 260                                                                                  | °C                     |
| T <sub>J</sub>   | Junction Temperature Under Bias                 | + 150                                                                                | °C                     |
| θ <sub>JA</sub>  | Thermal Resistance (Note 1)                     | 350                                                                                  | °C/W                   |
| P <sub>D</sub>   | Power Dissipation in Still Air at 85°C          | 150                                                                                  | mW                     |
| MSL              | Moisture Sensitivity                            | Level 1                                                                              |                        |
| F <sub>R</sub>   | Flammability Rating                             | Oxygen Index: 28 to 34<br>UL 94 V-0 @ 0.125 in                                       |                        |
| V <sub>ESD</sub> | ESD Withstand Voltage                           | Human Body Model (Note 2)<br>Machine Model (Note 3)<br>Charged Device Model (Note 4) | > 2000<br>> 200<br>N/A |

Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.

1. Measured with minimum pad spacing on an FR4 board, using 10 mm-by-1 inch, 2 ounce copper trace with no air flow.
2. Tested to EIA/JESD22-A114-A.
3. Tested to EIA/JESD22-A115-A.
4. Tested to JESD22-C101-A.

## RECOMMENDED OPERATING CONDITIONS

| Symbol                          | Parameter                   | Min                                                                                                                                       | Max                        | Unit |
|---------------------------------|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|------|
| V <sub>CC</sub>                 | DC Supply Voltage           | 1.65                                                                                                                                      | 5.5                        | V    |
| V <sub>IN</sub>                 | DC Input Voltage            | 0                                                                                                                                         | 5.5                        | V    |
| V <sub>OUT</sub>                | DC Output Voltage           | 0                                                                                                                                         | 5.5                        | V    |
| T <sub>A</sub>                  | Operating Temperature Range | −40                                                                                                                                       | +125                       | °C   |
| t <sub>r</sub> , t <sub>f</sub> | Input Rise and Fall Time    | V <sub>CC</sub> = 1.8 V ± 0.15 V<br>V <sub>CC</sub> = 2.5 V ± 0.2 V<br>V <sub>CC</sub> = 3.0 V ± 0.3 V<br>V <sub>CC</sub> = 5.0 V ± 0.5 V | 0<br>20<br>20<br>10<br>5.0 | ns/V |

## DEVICE JUNCTION TEMPERATURE VERSUS TIME TO 0.1% BOND FAILURES

| Junction Temperature °C | Time, Hours | Time, Years |
|-------------------------|-------------|-------------|
| 80                      | 1,032,200   | 117.8       |
| 90                      | 419,300     | 47.9        |
| 100                     | 178,700     | 20.4        |
| 110                     | 79,600      | 9.4         |
| 120                     | 37,000      | 4.2         |
| 130                     | 17,800      | 2.0         |
| 140                     | 8,900       | 1.0         |




Figure 3. Failure Rate vs. Time Junction Temperature

# NL17SZ125

## DC ELECTRICAL CHARACTERISTICS

| Symbol           | Parameter                                                      | V <sub>CC</sub><br>(V)           | T <sub>A</sub> = 25°C                       |                                      |                                             | -40°C ≤ T <sub>A</sub> ≤ 125°C              |                                             | Unit | Condition                                                                                                                              |
|------------------|----------------------------------------------------------------|----------------------------------|---------------------------------------------|--------------------------------------|---------------------------------------------|---------------------------------------------|---------------------------------------------|------|----------------------------------------------------------------------------------------------------------------------------------------|
|                  |                                                                |                                  | Min                                         | Typ                                  | Max                                         | Min                                         | Max                                         |      |                                                                                                                                        |
| V <sub>IH</sub>  | High-Level Input Voltage                                       | 1.65 to 1.95<br>2.3 to 5.5       | 0.75 V <sub>CC</sub><br>0.7 V <sub>CC</sub> |                                      |                                             | 0.75 V <sub>CC</sub><br>0.7 V <sub>CC</sub> |                                             | V    |                                                                                                                                        |
| V <sub>IL</sub>  | Low-Level Input Voltage                                        | 1.65 to 1.95<br>2.3 to 5.5       |                                             |                                      | 0.25 V <sub>CC</sub><br>0.3 V <sub>CC</sub> |                                             | 0.25 V <sub>CC</sub><br>0.3 V <sub>CC</sub> | V    |                                                                                                                                        |
| V <sub>OH</sub>  | High-Level Output Voltage<br>V <sub>IN</sub> = V <sub>IH</sub> | 1.65<br>1.8<br>2.3<br>3.0<br>4.5 | 1.55<br>1.7<br>2.2<br>2.9<br>4.4            | 1.65<br>1.8<br>2.3<br>3.0<br>4.5     |                                             | 1.55<br>1.7<br>2.2<br>2.9<br>4.4            |                                             | V    | I <sub>OH</sub> = -100 μA                                                                                                              |
|                  |                                                                | 1.65<br>2.3<br>3.0<br>3.0<br>4.5 | 1.29<br>1.9<br>2.4<br>2.68<br>3.8           | 1.52<br>2.15<br>2.80<br>2.68<br>4.20 |                                             | 1.29<br>1.9<br>2.4<br>2.3<br>3.8            |                                             | V    | I <sub>OH</sub> = -4 mA<br>I <sub>OH</sub> = -8 mA<br>I <sub>OH</sub> = -16 mA<br>I <sub>OH</sub> = -24 mA<br>I <sub>OH</sub> = -32 mA |
| V <sub>OL</sub>  | Low-Level Output Voltage<br>V <sub>IN</sub> = V <sub>IL</sub>  | 1.65<br>1.8<br>2.3<br>3.0<br>4.5 |                                             | 0.0<br>0.0<br>0.0<br>0.0<br>0.0      | 0.1<br>0.1<br>0.1<br>0.1<br>0.1             |                                             | 0.1<br>0.1<br>0.1<br>0.1<br>0.1             | V    | I <sub>OL</sub> = 100 μA                                                                                                               |
|                  |                                                                | 1.65<br>2.3<br>3.0<br>3.0<br>4.5 |                                             | 0.08<br>0.10<br>0.15<br>0.22<br>0.22 | 0.24<br>0.30<br>0.40<br>0.55<br>0.55        |                                             | 0.24<br>0.30<br>0.40<br>0.55<br>0.55        | V    | I <sub>OL</sub> = 4 mA<br>I <sub>OL</sub> = 8 mA<br>I <sub>OL</sub> = 16 mA<br>I <sub>OL</sub> = 24 mA<br>I <sub>OL</sub> = 32 mA      |
| I <sub>IN</sub>  | Input Leakage Current                                          | 0 to 5.5                         |                                             |                                      | ± 1.0                                       |                                             | ± 1.0                                       | μA   | 0 V ≤ V <sub>IN</sub> ≤ 5.5 V                                                                                                          |
| I <sub>OZ</sub>  | 3-State Output Leakage                                         | 1.65 to 5.5                      |                                             |                                      | ± 0.5                                       |                                             | ± 5.0                                       | μA   | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br>0 V ≤ V <sub>OUT</sub> ≤ 5.5 V                                                 |
| I <sub>OFF</sub> | Power Off Leakage Current                                      | 0.0                              |                                             |                                      | 1.0                                         |                                             | 10                                          | μA   | V <sub>IN</sub> or V <sub>OUT</sub> = 5.5 V                                                                                            |
| I <sub>CC</sub>  | Quiescent Supply Current                                       | 1.65 to 5.5                      |                                             |                                      | 1.0                                         |                                             | 10                                          | μA   | V <sub>IN</sub> = 5.5 V, GND                                                                                                           |

# NL17SZ125

## AC ELECTRICAL CHARACTERISTICS ( $t_R = t_F = 3.0 \text{ ns}$ )

| Symbol                 | Parameter                                                   | Condition                                                                                   | $V_{CC}$<br>(V) | $T_A = 25^\circ\text{C}$ |     |            | $-40^\circ\text{C} \leq T_A \leq 125^\circ\text{C}$ |            | Unit |
|------------------------|-------------------------------------------------------------|---------------------------------------------------------------------------------------------|-----------------|--------------------------|-----|------------|-----------------------------------------------------|------------|------|
|                        |                                                             |                                                                                             |                 | Min                      | Typ | Max        | Min                                                 | Max        |      |
| $t_{PLH}$<br>$t_{PHL}$ | Propagation Delay<br>AN to YN<br>(Figures 4 and 5, Table 1) | $R_L = 1 \text{ M}\Omega$ $C_L = 15 \text{ pF}$                                             | $1.8 \pm 0.15$  | 2.0                      | 9.0 | 10         | 2.0                                                 | 10.5       | ns   |
|                        |                                                             | $R_L = 1 \text{ M}\Omega$ $C_L = 15 \text{ pF}$                                             | $2.5 \pm 0.2$   | 1.0                      |     | 7.5        | 1.0                                                 | 8.0        |      |
|                        |                                                             | $R_L = 1 \text{ M}\Omega$ $C_L = 15 \text{ pF}$<br>$R_L = 500 \Omega$ $C_L = 50 \text{ pF}$ | $3.3 \pm 0.3$   | 0.8<br>1.2               |     | 5.2<br>5.7 | 0.8<br>1.2                                          | 5.5<br>6.0 |      |
|                        |                                                             | $R_L = 1 \text{ M}\Omega$ $C_L = 15 \text{ pF}$<br>$R_L = 500 \Omega$ $C_L = 50 \text{ pF}$ | $5.0 \pm 0.5$   | 0.5<br>0.8               |     | 4.5<br>5.0 | 0.5<br>0.8                                          | 4.8<br>5.3 |      |
| $t_{PZH}$<br>$t_{PZL}$ | Output Enable Time<br>(Figures 6, 7 and 8, Table 1)         | $R_L = 250 \Omega$ $C_L = 50 \text{ pF}$                                                    | $1.8 \pm 0.15$  | 2.0                      | 7.6 | 9.5        | 2.0                                                 | 10         | ns   |
|                        |                                                             |                                                                                             | $2.5 \pm 0.2$   | 1.8                      |     | 8.5        | 1.8                                                 | 9.0        |      |
|                        |                                                             |                                                                                             | $3.3 \pm 0.3$   | 1.2                      |     | 6.2        | 1.2                                                 | 6.5        |      |
|                        |                                                             |                                                                                             | $5.0 \pm 0.5$   | 0.8                      |     | 5.5        | 0.8                                                 | 5.8        |      |
| $t_{PHZ}$<br>$t_{PLZ}$ | Output Disable Time<br>(Figures 6, 7 and 8, Table 1)        | $R_L \text{ and } R_1 = 500 \Omega$ $C_L = 50 \text{ pF}$                                   | $1.8 \pm 0.15$  | 2.0                      | 8.0 | 10         | 2.0                                                 | 10.5       | ns   |
|                        |                                                             |                                                                                             | $2.5 \pm 0.2$   | 1.5                      |     | 8.0        | 1.5                                                 | 8.5        |      |
|                        |                                                             |                                                                                             | $3.3 \pm 0.3$   | 0.8                      |     | 5.7        | 0.8                                                 | 6.0        |      |
|                        |                                                             |                                                                                             | $5.0 \pm 0.5$   | 0.3                      |     | 4.7        | 0.3                                                 | 5.0        |      |

## CAPACITIVE CHARACTERISTICS

| Symbol    | Parameter                                 | Condition                                                          | Typical | Unit |
|-----------|-------------------------------------------|--------------------------------------------------------------------|---------|------|
| $C_{IN}$  | Input Capacitance                         | $V_{CC} = 5.5 \text{ V}$ , $V_I = 0 \text{ V}$ or $V_{CC}$         | 2.5     | pF   |
| $C_{OUT}$ | Output Capacitance                        | $V_{CC} = 5.5 \text{ V}$ , $V_I = 0 \text{ V}$ or $V_{CC}$         | 2.5     | pF   |
| $C_{PD}$  | Power Dissipation Capacitance<br>(Note 5) | 10 MHz, $V_{CC} = 3.3 \text{ V}$ , $V_I = 0 \text{ V}$ or $V_{CC}$ | 9       | pF   |
|           |                                           | 10 MHz, $V_{CC} = 5.5 \text{ V}$ , $V_I = 0 \text{ V}$ or $V_{CC}$ | 11      |      |

5.  $C_{PD}$  is defined as the value of the internal equivalent capacitance which is calculated from the operating current consumption without load. Average operating current can be obtained by the equation:  $I_{CC(OPR)} = C_{PD} \cdot V_{CC} \cdot f_{in} + I_{CC}$ .  $C_{PD}$  is used to determine the no-load dynamic power consumption;  $P_D = C_{PD} \cdot V_{CC}^2 \cdot f_{in} + I_{CC} \cdot V_{CC}$ .






Figure 4. Switching Waveform




\*Includes all probe and jig capacitance.  
A 1 MHz square input wave is recommended for propagation delay tests.

Figure 5.  $T_{PLH}$  or  $T_{PHL}$



A 1 MHz square input wave is recommended for propagation delay tests.

Figure 6.  $T_{PZL}$  or  $T_{PL}$



A 1 MHz square input wave is recommended for propagation delay tests.

Figure 7.  $T_{PZH}$  or  $T_{PHZ}$




Figure 8. AC Output Enable and Disable Waveform

Table 1. Output Enable and Disable Times

$t_R = t_F = 2.5$  ns, 10% to 90%;  $f = 1$  MHz;  $t_W = 500$  ns

| Symbol   | $V_{CC}$                          |                 |                                   |
|----------|-----------------------------------|-----------------|-----------------------------------|
|          | $3.3 \text{ V} \pm 0.3 \text{ V}$ | $2.7 \text{ V}$ | $2.5 \text{ V} \pm 0.2 \text{ V}$ |
| $V_{mi}$ | 1.5 V                             | 1.5 V           | $V_{CC}/2$                        |
| $V_{mo}$ | 1.5 V                             | 1.5 V           | $V_{CC}/2$                        |

## NL17SZ125

### DEVICE ORDERING INFORMATION


| Device          | Package                       | Shipping†          |
|-----------------|-------------------------------|--------------------|
| NL17SZ125DFT2   | SC-88A (SOT-353)              | 3000 / Tape & Reel |
| NL17SZ125DFT2G  | SC-88A (SOT-353)<br>(Pb-Free) | 3000 / Tape & Reel |
| NL17SZ125XV5T2G | SOT-553<br>(Pb-Free)          | 4000 / Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

# NL17SZ125

## PACKAGE DIMENSIONS

SC-88A, SOT-353, SC-70  
CASE 419A-02  
ISSUE J




### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.
3. 419A-01 OBSOLETE. NEW STANDARD 419A-02.
4. DIMENSIONS A AND B DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS.

| DIM | INCHES    |       | MILLIMETERS |      |
|-----|-----------|-------|-------------|------|
|     | MIN       | MAX   | MIN         | MAX  |
| A   | 0.071     | 0.087 | 1.80        | 2.20 |
| B   | 0.045     | 0.053 | 1.15        | 1.35 |
| C   | 0.031     | 0.043 | 0.80        | 1.10 |
| D   | 0.004     | 0.012 | 0.10        | 0.30 |
| G   | 0.026 BSC |       | 0.65 BSC    |      |
| H   | ---       | 0.004 | ---         | 0.10 |
| J   | 0.004     | 0.010 | 0.10        | 0.25 |
| K   | 0.004     | 0.012 | 0.10        | 0.30 |
| N   | 0.008 REF |       | 0.20 REF    |      |
| S   | 0.079     | 0.087 | 2.00        | 2.20 |

## SOLDERING FOOTPRINT\*





\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

# NL17SZ125

## PACKAGE DIMENSIONS

SOT-553, 5 LEAD  
CASE 463B-01  
ISSUE B




### NOTES:

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: MILLIMETERS
3. MAXIMUM LEAD THICKNESS INCLUDES LEAD FINISH THICKNESS. MINIMUM LEAD THICKNESS IS THE MINIMUM THICKNESS OF BASE MATERIAL.

| DIM | MILLIMETERS |      |      | INCHES    |       |       |
|-----|-------------|------|------|-----------|-------|-------|
|     | MIN         | NOM  | MAX  | MIN       | NOM   | MAX   |
| A   | 0.50        | 0.55 | 0.60 | 0.020     | 0.022 | 0.024 |
| b   | 0.17        | 0.22 | 0.27 | 0.007     | 0.009 | 0.011 |
| c   | 0.08        | 0.13 | 0.18 | 0.003     | 0.005 | 0.007 |
| D   | 1.50        | 1.60 | 1.70 | 0.059     | 0.063 | 0.067 |
| E   | 1.10        | 1.20 | 1.30 | 0.043     | 0.047 | 0.051 |
| e   | 0.50 BSC    |      |      | 0.020 BSC |       |       |
| L   | 0.10        | 0.20 | 0.30 | 0.004     | 0.008 | 0.012 |
| HE  | 1.50        | 1.60 | 1.70 | 0.059     | 0.063 | 0.067 |

## SOLDERING FOOTPRINT\*



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor  
P.O. Box 61312, Phoenix, Arizona 85082-1312 USA  
Phone: 480-829-7710 or 800-344-3860 Toll Free USA/Canada  
Fax: 480-829-7709 or 800-344-3867 Toll Free USA/Canada  
Email: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

N. American Technical Support: 800-282-9855 Toll Free  
USA/Canada

Japan: ON Semiconductor, Japan Customer Focus Center  
2-9-1 Kamimeguro, Meguro-ku, Tokyo, Japan 153-0051  
Phone: 81-3-5773-3850

ON Semiconductor Website: <http://onsemi.com>

Order Literature: <http://www.onsemi.com/litorder>

For additional information, please contact your local Sales Representative.