

Op - Amp. & Comparators

Features:

- Two independent, high gain, internally frequency compensated op amps
- Wide Supply Voltage Range Single & Split Supply
- Very Low Supply Current Drain typ 0.4 mA independent of supply voltage
- Low Input Biasing current and offset current
- High precision comparators
- Allows sensing near ground and Output voltage near to GND
- Compatible with all forms of logic
- Power Drain suitable for battery operation

Application:

Battery Charger, Switching Power Supply, Consumer Product, Industrial Application, PC & PC Peripheral, Telecommunication

Part No.	V _{CC} (V)	Supply Current	Channels	Slew rate	Input Offset Voltage	Gain Bandwith	Package
GM358	± 16	2.0mA	2	0.1V/ μS	9.0mV	1MHz	SOP-8, DIP-8
GM393	± 18	0.4mA	2	0.4V/ μS	3mV	1MHz	SOP-8, DIP-8

Op - Amp. & Voltage References

Features:

- Space and cost saving for power management and power supply
- Wide Supply Voltage Range typ 3V to 32V
- High Precision 0.4% of Programmable or 2.5V Voltage Reference
- Low Input Offset Voltage typ 0.5mV
- Low Supply Current typ 350μA
- Large output voltage swing

Application:

Switching Mode Power Supply, Power Management, Data Acquisition, Battery Charger, Linear Regulator

Part No.	Supply Range (V)	V _{REF} (V)	Op-Amps V _{io} (max)	I _{CC} (Typ.)	Precision (%)	GBP MHz. (Typ)	SR V/ μS (Typ)	I _{OUT} sink	Current Generator	Package
GMA101A	4.5 to 36	1.24	5mV	2mA	2 - 1 - 4	1	-	15mA	1.4mA	SOP-8, DIP-8
GMA102A	4.5 to 36	2.5	4.5mV Comp: 5mV	0.8mA	0.4	2.1	2	-	-	SOP-16
GMA103A	3.0 to 36	2.5	3mV/ 5mV	0.7mA	0.02	0.9	0.4	-	-	SOP-8, DIP-8
GMA104A	3.0 to 36	2.5	3mV/ 5mV	1.4mA	0.4	0.9	0.3	-	-	SOP-16, DIP-16

* For more information about new product, please contact our sales office or distributors .

Audio Amplifier

Features:

- 2W+2W Class AB Audio Amplifier
- Very Low THD with Stable Output
- Standby & Mute Function
- Low Turn-On/Turn-Off POP Noise
- Single Supply Voltage upto 15V
- Linear Volume Control
- Short Circuit and Thermal Overload Protection
- Improved Thermal Capability
- Minimum External Component Required

Application:

LCD Monitor/TV, Multimedia Speaker, Desktop PC, Portable Media Player/DVD Player

Part No.	Supply Voltage (V _{CC})			Supply Mode (Def)	Output Power Single Ended (Typ.)	THD (Max.)	Standby Current	Gain	Output Channels Mode	Package
	MIN	TYP	MAX							
GMA7496L	10	-	18	Single	2	0.4%	1mA	30dB	Single Ended	DIP20

Typical Application Circuit

