


0.2A High Voltage Fast Recovery Rectifiers

Features

- Fast recovery times
- Low cost
- Designed for photo flash application
- Beveled round chip, avalanche operation
- RoHS compliance



DO-15



Mechanical Data

Case:	JEDEC DO-15 molded plastic body
Epoxy:	Plastic package has UL flammability classification 94V-0
Terminals:	Plated axial leads, solderable per MIL-STD-202, Method 208
Polarity:	Color band denotes cathode end
Weight:	0.015 ounces, 0.4 gram

Maximum Ratings and Electrical Characteristics ($T_A=25^\circ\text{C}$ unless noted otherwise)

Symbol	Description	GF235	GF240	GF250	GF260	Unit	Conditions
VRRM	Maximum Recurrent Peak Reverse Voltage	3500	4000	5000	6000	V	
VRMS	Maximum RMS Voltage	2450	2800	3500	4200	V	
VDC	Maximum DC Blocking Voltage	3500	4000	5000	6000	V	
IF(AV)	Maximum Average Forward Rectified Current	0.2				A	L=10mm, TA=55° C
IFSM	Peak Forward Surge Current	25		20		A	8.3ms single half sine-wave superimposed on rated load (JEDEC Method)
VF	Maximum Instantaneous Forward Voltage	8.0		12.0		V	IF=0.2A
IR	Maximum DC Reverse Current at Rated DC Blocking Voltage	5.0				μA	TA=25° C
Trr	Typical Reverse Recovery Time	500				nS	IF=0.5A, IR=1A, Irr=0.25A

0.2A High Voltage Fast Recovery Rectifiers

GF235 - GF260

Symbol	Description	GF235	GF240	GF250	GF260	Unit	Conditions
C _J	Typical Junction Capacitance	6.0		4.0		pF	VR=4V, f=1MHz
T _J	Operating Temperature range	-65 to +125				° C	
T _{STG}	Storage Temperature Range	-65 to +150				° C	

Typical Characteristics Curves

Fig.1-Max. Forward Current Rating Effect of Copper Area. Resistive/Inductive Load




Fig.2-Max. Non-Repetitive Forward Surge Current




Fig.3- Typical Forward Characteristics






Fig.4-Typical Reverse Characteristics




0.2A High Voltage Fast Recovery Rectifiers

GF235 - GF260

Fig.5- Typical Junction Capacitance



Dimensions in inches (mm)



DO-15

0.2A High Voltage Fast Recovery Rectifiers

GF235 - GF260

How to contact us:

US HEADQUARTERS

28040 WEST HARRISON PARKWAY, VALENCIA, CA 91355-4162

Tel: (800) TAITRON (800) 824-8766 (661) 257-6060

Fax: (800) TAITFAX (800) 824-8329 (661) 257-6415

Email: taitron@taitroncomponents.com

Http://www.taitroncomponents.com

TAITRON COMPONENTS MEXICO, S.A .DE C.V.

BOULEVARD CENTRAL 5000 INTERIOR 5 PARQUE INDUSTRIAL ATITALAQUIA, HIDALGO C.P.
42970 MEXICO

Tel: +52-55-5560-1519

Fax: +52-55-5560-2190

TAITRON COMPONETS INCORPORATED E REPRESENTAÇÕES DO BRASIL LTDA

RUA DOMINGOS DE MORAIS, 2777, 2.ANDAR, SALA 24 SAÚDE - SÃO PAULO-SP 04035-001 BRAZIL

Tel: +55-11-5574-7949

Fax: +55-11-5572-0052

TAITRON COMPONETS INCORPORATED, SHANGHAI REPRESENTATIVE OFFICE

METROBANK PLAZA, 1160 WEST YAN' AN ROAD, SUITE 1503, SHANGHAI, 200052, CHINA

Tel: +86-21-5424-9942

Fax: +86-21-5424-9931