

# DATA SHEET

**RC02/12/22/32**

**1%**

Precision chip resistors  
sizes 1206, 0805, 0603 and 0402

Product specification  
Supersedes data of 27th March 2001

2002 Apr 09 Rev.9

# Precision chip resistors

## sizes 1206, 0805, 0603 and 0402

# RC02/12/22/32

## 1%

### FEATURES

- Low assembly costs
- High component and equipment reliability
- Excellent performance at high frequency, especially the RC32.
- TC 50 in thick film technology
- Complete precision SMD family.

### APPLICATIONS

- All general purpose applications.

### DESCRIPTION

The resistors are constructed on a high grade ceramic body (aluminium oxide). Internal metal electrodes are added at each end and connected by a resistive paste which is applied to the top surface of the substrate. The composition of the paste is adjusted to give the approximate resistance required and the value is trimmed to within tolerance, by laser cutting of this resistive layer.

The resistive layer is covered with a protective coat and printed with the resistance value (no printing on RC22H and RC32). Finally, the two external end terminations are added. For ease of soldering the outerlayer of these end terminations is a lead/tin alloy.

### QUICK REFERENCE DATA

| DESCRIPTION                                                                   | VALUE                |                    |                      |                    |                     |                     |
|-------------------------------------------------------------------------------|----------------------|--------------------|----------------------|--------------------|---------------------|---------------------|
|                                                                               | RC02H                | RC02G              | RC12H                | RC12G              | RC22H               | RC32                |
| Size code                                                                     | 1206 (3216)          |                    | 0805 (2012)          |                    | 0603 (1608)         | 0402 (1005)         |
| Resistance range                                                              | 1 Ω to<br>10 MΩ      | 90 Ω to<br>2.74 MΩ | 1 Ω to<br>10 MΩ      | 90 Ω to<br>2.74 MΩ | 1 Ω to<br>10 MΩ     | 1 Ω to<br>10 MΩ     |
| Resistance tolerance and<br>E-series                                          | ±1%; E24/E96 series  |                    |                      |                    |                     |                     |
| Temperature coefficient;<br>note 1:<br><br>1 Ω ≤ R ≤ 10 Ω<br>10 Ω < R ≤ 10 MΩ | ≤250 ±250<br>≤±100   | –<br>≤±50          | ≤250 ±250<br>≤±100   | –<br>≤±50          | ≤250 ±250<br>≤±100  | ≤250 ±250<br>≤±200  |
| Maximum dissipation at<br>T <sub>amb</sub> = 70 °C                            | 0.25 W               |                    | 0.125 W              |                    | 0.1 W               | 0.063 W             |
| Maximum permissible voltage                                                   | 200 V<br>(DC or RMS) |                    | 150 V<br>(DC or RMS) |                    | 50 V<br>(DC or RMS) | 50 V<br>(DC or RMS) |
| Climatic category<br>(IEC 60068)                                              | 55/155/56            |                    |                      |                    |                     | 55/125/56           |
| Basic specification                                                           | IEC 60115-8          |                    |                      |                    |                     |                     |

### Note

1. All TC values should be multiplied by  $10^{-6}/\text{K}$ .

# Precision chip resistors sizes 1206, 0805, 0603 and 0402

RC02/12/22/32  
1%

## ORDERING INFORMATION

**Table 1** Ordering code indicating type and packing

| TYPE                                | ORDERING CODE 2322 ... .. |             |             |             |
|-------------------------------------|---------------------------|-------------|-------------|-------------|
|                                     | PAPER TAPE ON REEL        |             |             |             |
|                                     | 5000 units                | 10000 units | 20000 units | 50000 units |
| RC02H                               | 724 6....                 | 724 7....   | 724 8....   | –           |
| RC02G                               | 722 2....                 | 722 3....   | –           | –           |
| RC12H                               | 734 6....                 | 734 7....   | 734 8....   | –           |
| RC12G                               | 732 6....                 | 732 7....   | –           | –           |
| RC22H                               | 704 6....                 | 704 7....   | 704 8....   | –           |
| RC32                                | –                         | 706 7....   | –           | 706 8....   |
| <b>Jumper 0 <math>\Omega</math></b> |                           |             |             |             |
| RC02H; note 1                       | 724 92006                 | 724 92007   | –           | –           |
| RC12H; note 1                       | 734 92006                 | 734 92007   | –           | –           |
| RC22H; note 2                       | 704 92006                 | 704 92007   | –           | –           |

### Notes

1. The jumper has a maximum resistance  $R_{\max} = 50 \text{ m}\Omega$  and a rated current  $I_R = 2 \text{ A}$ .
2. The jumper has a maximum resistance  $R_{\max} = 50 \text{ m}\Omega$  and a rated current  $I_R = 1 \text{ A}$ .

### Ordering code (12NC)

- The resistors have a 12-digit ordering code starting with 2322.
- The subsequent 4 digits indicate the resistor type and packing; see Table 1.
- The remaining 4 digits indicate the resistance value:
  - The first 3 digits indicate the resistance value.
  - The last digit indicates the resistance decade in accordance with Table 2.

**Table 2** Last digit of 12NC

| RESISTANCE DECADE     | LAST DIGIT |
|-----------------------|------------|
| 1 to 9.1 $\Omega$     | 8          |
| 10 to 91.0 $\Omega$   | 9          |
| 100 to 910 $\Omega$   | 1          |
| 1 to 9.1 k $\Omega$   | 2          |
| 10 to 91.0 k $\Omega$ | 3          |
| 100 to 910 k $\Omega$ | 4          |
| 1 to 9.1 M $\Omega$   | 5          |
| 10 M $\Omega$         | 6          |

### ORDERING EXAMPLE

The ordering code of a RC02H resistor, value 4750  $\Omega$ , supplied on paper tape of 5000 units per reel is: 2322 724 64752.

Precision chip resistors  
sizes 1206, 0805, 0603 and 0402

RC02/12/22/32  
1%

FUNCTIONAL DESCRIPTION

Product characterization

Standard values of nominal resistance are taken from the E24/E96 series for resistors with a tolerance of  $\pm 1\%$ . The values of the E24/96 series are in accordance with “IEC publication 60063”.

Limiting values


| TYPE | LIMITING VOLTAGE <sup>(1)</sup><br>(V) | LIMITING POWER<br>(W) |
|------|----------------------------------------|-----------------------|
| RC02 | 200                                    | 0.25                  |
| RC12 | 150                                    | 0.125                 |
| RC22 | 50                                     | 0.063/0.1             |
| RC32 | 50                                     | 0.063                 |

Note


1. This is the maximum voltage that may be continuously applied to the resistor element, see “IEC publication 60115-8”.

DERATING

The power that the resistor can dissipate depends on the operating temperature; see Fig.1.




PULSE LOADING CAPABILITIES




# Precision chip resistors sizes 1206, 0805, 0603 and 0402

RC02/12/22/32  
1%



These pulses may not be applied on a regular basis.

Fig.3 Maximum permissible peak pulse voltage without failing to 'open circuit' in accordance with DIN IEC 60040 (CO) 533 for type: **RC12**.



These pulses may not be applied on a regular basis.

Fig.4 Maximum permissible peak pulse voltage without failing to 'open circuit' in accordance with DIN IEC 60040 (CO) 533 for type: **RC22**.

# Precision chip resistors

## sizes 1206, 0805, 0603 and 0402

RC02/12/22/32  
1%




Fig.5 Pulse on a regular basis for type: **RC02**; maximum permissible peak pulse power ( $\hat{P}_{max}$ ) as a function of pulse duration for single pulse and repetitive pulse  $t_p/t_i = 1000$ .




Fig.6 Pulse on a regular basis for type: **RC02**; maximum permissible peak pulse voltage ( $\hat{V}_{max}$ ) as a function of pulse duration.

# Precision chip resistors sizes 1206, 0805, 0603 and 0402

RC02/12/22/32  
1%




Fig.7 Pulse on a regular basis for type: **RC12**; maximum permissible peak pulse power ( $\hat{P}_{max}$ ) as a function of pulse duration for single pulse and repetitive pulse  $t_p/t_i = 1000$ .




Fig.8 Pulse on a regular basis for type: **RC12**; maximum permissible peak pulse voltage ( $\hat{V}_{max}$ ) as a function of pulse duration.

# Precision chip resistors sizes 1206, 0805, 0603 and 0402

RC02/12/22/32  
1%




Fig.9 Pulse on a regular basis for type: **RC22**; maximum permissible peak pulse power ( $\hat{P}_{max}$ ) as a function of pulse duration for single pulse and repetitive pulse  $t_p/t_i = 1000$ .




Fig.10 Pulse on a regular basis for type: **RC22**; maximum permissible peak pulse voltage ( $\hat{V}_{max}$ ) as a function of pulse duration.

# Precision chip resistors sizes 1206, 0805, 0603 and 0402

RC02/12/22/32  
1%




Fig.11 Pulse on a regular basis for type: **RC32**; maximum permissible peak pulse power ( $\hat{P}_{max}$ ) as a function of pulse duration for single pulse and repetitive pulse  $t_p/t_i = 1000$ .




Fig.12 Pulse on a regular basis for type: **RC32**; maximum permissible peak pulse voltage ( $\hat{V}_{max}$ ) as a function of pulse duration.

Precision chip resistors  
sizes 1206, 0805, 0603 and 0402

RC02/12/22/32  
1%

MECHANICAL DATA

Mass per 100 units

| TYPE | MASS (g) |
|------|----------|
| RC02 | 1.0      |
| RC12 | 0.55     |
| RC22 | 0.25     |
| RC32 | 0.058    |

Marking

All resistors except RC22 and RC32 are marked with a four digit code on the protective coat to designate the nominal resistance value.

4-DIGIT MARKING

For values up to 976 Ω the R is used as a decimal point. For values of 1 kΩ or greater the first 3 digits apply to the resistance value and the fourth indicates the number of zeros to follow.

Example

| MARKING | RESISTANCE |
|---------|------------|
| 220R    | 220 Ω      |
| 4021    | 4.02 kΩ    |
| 1503    | 150 kΩ     |

PACKAGE MARKING

The packing is marked with the resistance value, tolerance, catalogue number, quantity, production period, batch number and source code.

Outlines




Table 3 Chip resistor types and relevant physical dimensions; see Fig.13

| TYPE | L (mm)              | W (mm)              | T (mm)     | t <sub>t</sub> (mm) | t <sub>b</sub> (mm) |
|------|---------------------|---------------------|------------|---------------------|---------------------|
| RC02 | 3.20<br>+0.10/-0.20 | 1.60 ±0.15          | 0.55 ±0.10 | 0.45 ±0.25          | 0.50 ±0.25          |
| RC12 | 2.00 ±0.15          | 1.25 ±0.15          | 0.55 ±0.10 | 0.40 ±0.20          | 0.40 ±0.20          |
| RC22 | 1.60 ±0.10          | 0.80<br>+0.15/-0.05 | 0.45 ±0.10 | 0.30 ±0.20          | 0.30 ±0.20          |
| RC32 | 1.00 ±0.05          | 0.50 ±0.05          | 0.35 ±0.05 | 0.20 ±0.10          | 0.25 ±0.10          |

Precision chip resistors  
sizes 1206, 0805, 0603 and 0402

RC02/12/22/32  
1%

TESTS AND REQUIREMENTS

Essentially all tests are carried out in accordance with the schedule of “IEC publication 60115-8”, category **LCT/UCT/56** (rated temperature range: Lower Category Temperature, Upper Category Temperature; damp heat, long term, **56** days). The testing also covers the requirements specified by EIA and EIAJ.

The tests are carried out in accordance with IEC publication 60068, “Recommended basic climatic and mechanical robustness testing procedure for electronic components” and under standard atmospheric conditions according to “IEC 60068-1”, subclause 5.3.

Unless otherwise specified the following values apply:

- Temperature: 15 °C to 35 °C
- Relative humidity: 45% to 75%
- Air pressure: 86 kPa to 106 kPa (860 mbar to 1060 mbar).

In Table 4 the tests and requirements are listed with reference to the relevant clauses of “IEC publications 60115-8 and 60068”; a short description of the test procedure is also given. In some instances deviations from the IEC recommendations were necessary for our method of specifying.

All soldering tests are performed with mildly activated flux.

Table 4 Test procedures and requirements

| IEC<br>60115-8<br>CLAUSe                                         | IEC<br>60068-2<br>TEST<br>METHOD | TEST                       | PROCEDURE                                                                                                                                                                                           | REQUIREMENTS                               |       |       |       |       |
|------------------------------------------------------------------|----------------------------------|----------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------|-------|-------|-------|-------|
|                                                                  |                                  |                            |                                                                                                                                                                                                     | RC02H                                      | RC02G | RC12H | RC12G | RC22H |
| Tests in accordance with the schedule of IEC publication 60115-8 |                                  |                            |                                                                                                                                                                                                     |                                            |       |       |       |       |
| 4.4.1                                                            |                                  | visual<br>examination      |                                                                                                                                                                                                     | no holes; clean surface; no visible damage |       |       |       |       |
| 4.4.2                                                            |                                  | dimensions<br>(see Fig.13) | gauge (mm)                                                                                                                                                                                          | see Table 3                                |       |       |       |       |
| 4.5                                                              |                                  | resistance                 | applied voltage (+0/−10%):<br>R < 10 Ω: 0.1 V<br>10 Ω ≤ R < 100 Ω: 0.3 V<br>100 Ω ≤ R < 1 kΩ: 1 V<br>1 kΩ ≤ R < 10 kΩ: 3 V<br>10 kΩ ≤ R < 100 kΩ: 10 V<br>100 kΩ ≤ R < 1 MΩ: 25 V<br>R ≥ 1 MΩ: 50 V | R − R <sub>nom</sub> : max. ±1%            |       |       |       |       |

# Precision chip resistors

## sizes 1206, 0805, 0603 and 0402

RC02/12/22/32  
1%

| IEC<br>60115-8<br>CLAUSE | IEC<br>60068-2<br>TEST<br>METHOD | TEST                               | PROCEDURE                                                                                                                                                                                      | REQUIREMENTS |       |       |       |       |                                                                                 |
|--------------------------|----------------------------------|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-------|-------|-------|-------|---------------------------------------------------------------------------------|
|                          |                                  |                                    |                                                                                                                                                                                                | RC02H        | RC02G | RC12H | RC12G | RC22H | RC32                                                                            |
| 4.18                     | 20 (Tb)                          | resistance to<br>soldering heat    | unmounted chips;<br>10 ±1 s; 260 ±5 °C                                                                                                                                                         |              |       |       |       |       | no visible damage<br>$\Delta R/R$ max.: ±(1% +0.05 Ω)                           |
| 4.29                     | 45 (Xa)                          | component<br>solvent<br>resistance | isopropyl alcohol or H <sub>2</sub> O<br>followed by brushing in<br>accordance with "MIL 202 F"                                                                                                |              |       |       |       |       | no visible damage<br>$\Delta R/R$ max.: ±(0.5% +0.05 Ω)                         |
| 4.17                     | 20 (Ta)                          | solderability                      | unmounted chips completely<br>immersed for 2 ±0.5 s in a<br>solder bath at 235 ±2 °C                                                                                                           |              |       |       |       |       | no visible damage                                                               |
| 4.7                      |                                  | voltage proof<br>on insulation     | maximum voltage (RMS)<br>during 1 minute, metal block<br>method                                                                                                                                |              |       |       |       |       | good tinning (≥95% covered); no visible damage<br><br>no breakdown or flashover |
| 4.13                     |                                  | short time<br>overload             | room temperature;<br>$P = 6.25 \times P_n$ ; 5 s<br>( $V \leq 2 \times V_{max}$ )                                                                                                              |              |       |       |       |       | $\Delta R/R$ max.: ±(1% +0.05 Ω)<br><br>$\Delta R/R$ max.: ±(2% +0.1 Ω)         |
| 4.33                     |                                  | bending                            | resistors mounted on a 90 mm<br>glass epoxy resin PCB (FR4),<br>bending:<br>3 mm for <b>RC02H</b> and <b>RC02G</b> ;<br>5 mm for <b>RC12H</b> , <b>RC12G</b> ,<br><b>RC22H</b> and <b>RC32</b> |              |       |       |       |       | no visible damage<br>$\Delta R/R$ max.: ±(1% +0.05 Ω)                           |
| 4.19                     | 14 (Na)                          | rapid change of<br>temperature     | 30 minutes at LCT and<br>30 minutes at UCT; 5 cycles                                                                                                                                           |              |       |       |       |       | no visible damage<br>$\Delta R/R$ max.: ±(2% +0.1 Ω)                            |

Precision chip resistors  
sizes 1206, 0805, 0603 and 0402

RC02/12/22/32  
1%

| IEC<br>60115-8<br>CLAUSE                                                          | IEC<br>60068-2<br>TEST<br>METHOD | TEST                                          | PROCEDURE                                                                                                                                   | REQUIREMENTS                                             |                |                                                          |                |                              |                    |
|-----------------------------------------------------------------------------------|----------------------------------|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------|----------------|----------------------------------------------------------|----------------|------------------------------|--------------------|
|                                                                                   |                                  |                                               |                                                                                                                                             | RC02H                                                    | RC02G          | RC12H                                                    | RC12G          | RC22H                        | RC32               |
| 4.24.2                                                                            | 3 (Ca)                           | damp heat<br>(steady state)                   | 56 days; 40 ±2 °C;<br>93 +2/-3% RH;<br>loaded with 0.01 P <sub>n</sub> ;<br>R ≤ 1 MΩ<br>R > 1 MΩ                                            | ΔR/R max.: ±(1.0% +0.05 Ω)<br>ΔR/R max.: ±(1.5% +0.05 Ω) |                | ΔR/R max.: ±(1.0% +0.05 Ω)<br>ΔR/R max.: ±(1.5% +0.05 Ω) |                | ΔR/R max.: ±(2% +0.1 Ω)<br>– |                    |
| 4.25.1                                                                            |                                  | endurance                                     | 1000 +48/-0 hours; 70 ±2 °C;<br>loaded with P <sub>n</sub> or V <sub>max</sub> ;<br>1.5 hours on and 0.5 hours off:<br>R ≤ 1 MΩ<br>R > 1 MΩ | ΔR/R max.: ±(1.0% +0.05 Ω)<br>ΔR/R max.: ±(1.5% +0.05 Ω) |                | ΔR/R max.: ±(1.0% +0.05 Ω)<br>ΔR/R max.: ±(1.5% +0.05 Ω) |                | ΔR/R max.: ±(2% +0.1 Ω)<br>– |                    |
| 4.23.2                                                                            | 27 (Ba)                          | endurance at<br>upper category<br>temperature | 1000 +48/-0 hours; no load:<br>R ≤ 1 MΩ<br>R > 1 MΩ                                                                                         | ΔR/R max.: ±(1.0% +0.05 Ω)<br>ΔR/R max.: ±(1.5% +0.05 Ω) |                | ΔR/R max.: ±(1.0% +0.05 Ω)<br>ΔR/R max.: ±(1.5% +0.05 Ω) |                | ΔR/R max.: ±(2% +0.1 Ω)<br>– |                    |
| 4.8.4.2                                                                           |                                  | temperature<br>coefficient                    | at 20/LCT/20 °C and<br>20/UCT/20 °C:<br>1 Ω ≤ R ≤ 10 Ω<br>10 Ω < R ≤ 10 MΩ                                                                  | ≤250<br>±250<br>≤±100                                    | –<br>–<br>≤±50 | ≤250<br>±250<br>≤±100                                    | –<br>–<br>≤±50 | ≤250<br>±250<br>≤±100        | ≤250 ±250<br>≤±200 |
| <b>Other tests in accordance with IEC 60115 clauses and IEC 60068 test method</b> |                                  |                                               |                                                                                                                                             |                                                          |                |                                                          |                |                              |                    |
| 4.17                                                                              | 20 (Ta)                          | solderability<br>(after ageing)               | 8 hours steam or 16 hours<br>155 °C; unmounted chips<br>completely immersed for<br>2 ±0.5 s in a solder bath at<br>235 ±2 °C                | good tinning (≥95% covered); no visible damage           |                |                                                          |                |                              |                    |
| 4.6.1.1                                                                           |                                  | insulation<br>resistance                      | voltage (DC) after 1 minute,<br>metal block method:<br>100 V for RC02H, RC02G,<br>RC12H and RC12G,<br>50 V for RC22H and RC32               | R <sub>ins</sub> min.: 10 <sup>3</sup> MΩ                |                |                                                          |                |                              |                    |

Precision chip resistors  
sizes 1206, 0805, 0603 and 0402

RC02/12/22/32  
1%

|                          |                                  | REQUIREMENTS                          |                                                                                                                                                                                                               |                                                                                                                                                                          |       |       |      |
|--------------------------|----------------------------------|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|-------|------|
|                          |                                  | RC02H                                 | RC02G                                                                                                                                                                                                         | RC12H                                                                                                                                                                    | RC12G | RC22H | RC32 |
| IEC<br>60115-8<br>CLAUSE | IEC<br>60068-2<br>TEST<br>METHOD | TEST                                  | PROCEDURE                                                                                                                                                                                                     |                                                                                                                                                                          |       |       |      |
| 4.12                     |                                  | noise                                 | IEC publication 60195<br>(measured with<br>Quantech - equipment):<br><br>R ≤ 100 Ω<br><br>100 Ω < R ≤ 1 kΩ<br><br>1 kΩ < R ≤ 10 kΩ<br><br>10 kΩ < R ≤ 100 kΩ<br><br>100 kΩ < R ≤ 1 MΩ<br><br>1 MΩ < R ≤ 10 MΩ | max. 0.316 μV/V (−10 dB)<br><br>max. 1 μV/V (0 dB)<br><br>max. 3 μV/V (9.54 dB)<br><br>max. 6 μV/V (15.56 dB)<br><br>max. 10 μV/V (20 dB)<br><br>max. 32 μV/V (30.10 dB) |       |       |      |
| Other applicable tests   |                                  |                                       |                                                                                                                                                                                                               |                                                                                                                                                                          |       |       |      |
| (JIS) C<br>5205 7.9      |                                  | endurance<br>(under damp<br>and load) | 1000 +48/−0 hours; 40 ±2 °C;<br>93 +2/−3% RH;<br>loaded with P <sub>n</sub> or V <sub>max</sub> ;<br>1.5 hours on and 0.5 hours off:<br><br>R ≤ 1 MΩ<br><br>R > 1 MΩ                                          | ΔR/R max.: ±(2% +0.1 Ω)<br>ΔR/R max.: ±(3% +0.1 Ω)                                                                                                                       |       |       |      |
| EIA<br>575 3.13          |                                  | leaching                              | unmounted chips 60 ±1 s;<br>260 ±5 °C                                                                                                                                                                         | good tinning; no leaching                                                                                                                                                |       |       |      |
| EIA/IS<br>703 4.5        |                                  | load humidity                         | 1000 +48/−0 hours; 85 ±2 °C;<br>85 ±5% RH;<br>loaded with 0.01 P <sub>n</sub> or V <sub>max</sub> ;<br><br>R ≤ 1 MΩ<br><br>R > 1 MΩ                                                                           | ΔR/R max.: ±(2% +0.1 Ω)<br>ΔR/R max.: ±(3% +0.1 Ω)                                                                                                                       |       |       |      |

---

Precision chip resistors  
sizes 1206, 0805, 0603 and 0402

---

RC02/12/22/32  
1%

---

**REVISION HISTORY**

| Revision | Date        | Change Notification | Description                                                                                                           |
|----------|-------------|---------------------|-----------------------------------------------------------------------------------------------------------------------|
| Rev.8    | 2001 Mar 07 | –                   | - Converted to Phycomp brand<br>- Pulse duration limit for $R \leq 10 \text{ k}\Omega$ removed in Figs.5, 7, 9 and 11 |
| Rev.9    | 2002 Apr 09 | –                   | - Maximum dissipation for RC22H changed from 0.063 W/0.1 W to 0.1 W                                                   |
|          |             |                     |                                                                                                                       |