

# FDP8447L

## N-Channel PowerTrench® MOSFET 40V, 50A, 8.7mΩ

### Features

- Max  $r_{DS(on)}$  = 8.7mΩ at  $V_{GS} = 10V$ ,  $I_D = 14A$
- Max  $r_{DS(on)}$  = 11.2mΩ at  $V_{GS} = 4.5V$ ,  $I_D = 11A$
- Fast Switching
- RoHS Compliant





### General Description

This N-Channel MOSFET has been produced using Fairchild Semiconductor's proprietary PowerTrench technology to deliver low  $r_{DS(on)}$  and optimized  $BV_{DSS}$  capability to offer superior performance benefit in the application.

### Applications

- Inverter
- Power Supplies



### MOSFET Maximum Ratings $T_C = 25^\circ\text{C}$ unless otherwise noted

| Symbol         | Parameter                                                            | Ratings     | Units            |
|----------------|----------------------------------------------------------------------|-------------|------------------|
| $V_{DS}$       | Drain to Source Voltage                                              | 40          | V                |
| $V_{GS}$       | Gate to Source Voltage                                               | $\pm 20$    | V                |
| $I_D$          | Drain Current -Continuous (Package limited) $T_C = 25^\circ\text{C}$ | 50          | A                |
|                | -Continuous (Silicon limited) $T_C = 25^\circ\text{C}$               | 65          |                  |
|                | -Continuous $T_A = 25^\circ\text{C}$ (Note 1)                        | 12          |                  |
|                | -Pulsed                                                              | 100         |                  |
| $E_{AS}$       | Drain-Source Avalanche Energy (Note 3)                               | 153         | mJ               |
| $P_D$          | Power Dissipation $T_C = 25^\circ\text{C}$                           | 60          | W                |
|                | Power Dissipation $T_A = 25^\circ\text{C}$ (Note 1)                  | 2           |                  |
| $T_J, T_{STG}$ | Operating and Storage Junction Temperature Range                     | -55 to +150 | $^\circ\text{C}$ |

### Thermal Characteristics

|                 |                                                  |      |                    |
|-----------------|--------------------------------------------------|------|--------------------|
| $R_{\theta JC}$ | Thermal Resistance, Junction to Case             | 2.1  | $^\circ\text{C/W}$ |
| $R_{\theta JA}$ | Thermal Resistance, Junction to Ambient (Note 1) | 62.5 |                    |

### Package Marking and Ordering Information

| Device Marking | Device   | Package  | Reel Size | Tape Width | Quantity |
|----------------|----------|----------|-----------|------------|----------|
| FDP8447L       | FDP8447L | TO-220AB | Tube      | N/A        | 50units  |

**Electrical Characteristics**  $T_J = 25^\circ\text{C}$  unless otherwise noted

| Symbol | Parameter | Test Conditions | Min | Typ | Max | Units |
|--------|-----------|-----------------|-----|-----|-----|-------|
|--------|-----------|-----------------|-----|-----|-----|-------|

**Off Characteristics**

|                                      |                                           |                                                           |    |    |           |                      |
|--------------------------------------|-------------------------------------------|-----------------------------------------------------------|----|----|-----------|----------------------|
| $BV_{DSS}$                           | Drain to Source Breakdown Voltage         | $I_D = 250\mu\text{A}$ , $V_{GS} = 0\text{V}$             | 40 |    |           | V                    |
| $\frac{\Delta BV_{DSS}}{\Delta T_J}$ | Breakdown Voltage Temperature Coefficient | $I_D = 250\mu\text{A}$ , referenced to $25^\circ\text{C}$ |    | 34 |           | mV/ $^\circ\text{C}$ |
| $I_{DSS}$                            | Zero Gate Voltage Drain Current           | $V_{DS} = 32\text{V}$ ,                                   |    |    | 1         | $\mu\text{A}$        |
| $I_{GSS}$                            | Gate to Source Leakage Current            | $V_{GS} = \pm 20\text{V}$ , $V_{DS} = 0\text{V}$          |    |    | $\pm 100$ | nA                   |

**On Characteristics**

|                                        |                                                          |                                                                        |   |      |      |                      |
|----------------------------------------|----------------------------------------------------------|------------------------------------------------------------------------|---|------|------|----------------------|
| $V_{GS(th)}$                           | Gate to Source Threshold Voltage                         | $V_{GS} = V_{DS}$ , $I_D = 250\mu\text{A}$                             | 1 | 1.7  | 3    | V                    |
| $\frac{\Delta V_{GS(th)}}{\Delta T_J}$ | Gate to Source Threshold Voltage Temperature Coefficient | $I_D = 250\mu\text{A}$ , referenced to $25^\circ\text{C}$              |   | -6   |      | mV/ $^\circ\text{C}$ |
| $r_{DS(on)}$                           | Static Drain to Source On Resistance                     | $V_{GS} = 10\text{V}$ , $I_D = 14\text{A}$                             |   | 7.7  | 8.7  | m $\Omega$           |
|                                        |                                                          | $V_{GS} = 4.5\text{V}$ , $I_D = 11\text{A}$                            |   | 8.9  | 11.2 |                      |
|                                        |                                                          | $V_{GS} = 10\text{V}$ , $I_D = 14\text{A}$ , $T_J = 125^\circ\text{C}$ |   | 12.1 | 13.7 |                      |
| $g_{FS}$                               | Forward Transconductance                                 | $V_{DD} = 5\text{V}$ , $I_D = 14\text{A}$                              |   | 74   |      | S                    |

**Dynamic Characteristics**

|           |                              |                                                                     |  |      |      |          |
|-----------|------------------------------|---------------------------------------------------------------------|--|------|------|----------|
| $C_{iss}$ | Input Capacitance            | $V_{DS} = 20\text{V}$ , $V_{GS} = 0\text{V}$ ,<br>$f = 1\text{MHz}$ |  | 1880 | 2500 | pF       |
| $C_{oss}$ | Output Capacitance           |                                                                     |  | 245  | 325  | pF       |
| $C_{rss}$ | Reverse Transfer Capacitance |                                                                     |  | 150  | 225  | pF       |
| $R_g$     | Gate Resistance              | $f = 1\text{MHz}$                                                   |  | 1.4  |      | $\Omega$ |

**Switching Characteristics**

|              |                               |                                                                                             |                                               |     |    |    |
|--------------|-------------------------------|---------------------------------------------------------------------------------------------|-----------------------------------------------|-----|----|----|
| $t_{d(on)}$  | Turn-On Delay Time            | $V_{DD} = 20\text{V}$ , $I_D = 14\text{A}$ ,<br>$V_{GS} = 10\text{V}$ , $R_{GEN} = 6\Omega$ |                                               | 9   | 18 | ns |
| $t_r$        | Rise Time                     |                                                                                             |                                               | 7   | 14 | ns |
| $t_{d(off)}$ | Turn-Off Delay Time           |                                                                                             |                                               | 28  | 45 | ns |
| $t_f$        | Fall Time                     |                                                                                             |                                               | 4   | 10 | ns |
| $Q_g$        | Total Gate Charge             | $V_{GS} = 0\text{V}$ to $10\text{V}$                                                        | $V_{DD} = 20\text{V}$ ,<br>$I_D = 14\text{A}$ | 35  | 49 | nC |
| $Q_g$        | Total Gate Charge             | $V_{GS} = 0\text{V}$ to $5\text{V}$                                                         |                                               | 19  | 27 | nC |
| $Q_{gs}$     | Gate to Source Charge         |                                                                                             |                                               | 4.7 |    | nC |
| $Q_{gd}$     | Gate to Drain "Miller" Charge |                                                                                             |                                               | 6.2 |    | nC |

**Drain-Source Diode Characteristics**

|          |                                       |                                                        |  |     |     |    |
|----------|---------------------------------------|--------------------------------------------------------|--|-----|-----|----|
| $V_{SD}$ | Source to Drain Diode Forward Voltage | $V_{GS} = 0\text{V}$ , $I_S = 14\text{A}$ (Note 2)     |  | 0.8 | 1.2 | V  |
| $t_{rr}$ | Reverse Recovery Time                 | $I_F = 14\text{A}$ , $di/dt = 100\text{A}/\mu\text{s}$ |  | 28  | 42  | ns |
| $Q_{rr}$ | Reverse Recovery Charge               |                                                        |  | 22  | 33  | nC |

## NOTES:

- $R_{\theta JA}$  is the sum of the junction-to-case and case-to-ambient thermal resistance where the case thermal reference is defined as the solder mounting surface of the drain pins.  $R_{\theta JC}$  is guaranteed by design while  $R_{\theta JA}$  is determined by the user's board design.
- Pulse Test: Pulse Width  $< 300\mu\text{s}$ , Duty cycle  $< 2.0\%$ .
- Starting  $T_J = 25^\circ\text{C}$ ,  $L = 1\text{mH}$ ,  $I_{AS} = 17.5\text{A}$ ,  $V_{DD} = 40\text{V}$ ,  $V_{GS} = 10\text{V}$ .

# Typical Characteristics $T_J = 25^\circ\text{C}$ unless otherwise noted




Figure 1. On-Region Characteristics




Figure 2. Normalized On-Resistance vs Drain Current and Gate Voltage




Figure 3. Normalized On-Resistance vs Junction Temperature




Figure 4. On-Resistance vs Gate to Source Voltage




Figure 5. Transfer Characteristics




Figure 6. Source to Drain Diode Forward Voltage vs Source Current

# Typical Characteristics $T_J = 25^\circ\text{C}$ unless otherwise noted




Figure 7. Gate Charge Characteristics




Figure 8. Capacitance vs Drain to Source Voltage




Figure 9. Unclamped Inductive Switching Capability




Figure 10. Maximum Continuous Drain Current vs Case Temperature




Figure 11. Forward Bias Safe Operating Area





Figure 12. Single Pulse Maximum Power Dissipation

**Typical Characteristics**  $T_J = 25^\circ\text{C}$  unless otherwise noted





## TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

|                                     |                    |                                                                                     |                 |
|-------------------------------------|--------------------|-------------------------------------------------------------------------------------|-----------------|
| ACEx®                               | HiSeC™             | Power-SPM™                                                                          | TinyBuck™       |
| Across the board. Around the world™ | i-Lo™              | PowerTrench®                                                                        | TinyLogic®      |
| ActiveArray™                        | ImpliedDisconnect™ | Programmable Active Droop™                                                          | TINYOPTO™       |
| Bottomless™                         | IntelliMAX™        | QFET®                                                                               | TinyPower™      |
| Build it Now™                       | ISOPANAR™          | QS™                                                                                 | TinyWire™       |
| CoolFET™                            | MICROCOUPLER™      | QT Optoelectronics™                                                                 | TruTranslation™ |
| CorePLUS™                           | MicroPak™          | Quiet Series™                                                                       | µSerDes™        |
| CROSSVOLT™                          | MICROWIRE™         | RapidConfigure™                                                                     | UHC®            |
| CTL™                                | Motion-SPM™        | RapidConnect™                                                                       | UniFET™         |
| Current Transfer Logic™             | MSX™               | ScalarPump™                                                                         | VCX™            |
| DOME™                               | MSXPro™            | SMART START™                                                                        | Wire™           |
| E <sup>2</sup> CMOS™                | OCX™               | SPM®                                                                                |                 |
| EcoSPARK®                           | OCXPro™            | STEALTH™                                                                            |                 |
| EnSigna™                            | OPTOLOGIC®         | SuperFET™                                                                           |                 |
| FACT Quiet Series™                  | OPTOPLANAR®        | SuperSOT™-3                                                                         |                 |
| FACT®                               | PACMAN™            | SuperSOT™-6                                                                         |                 |
| FAST®                               | PDP-SPM™           | SuperSOT™-8                                                                         |                 |
| FASTr™                              | POP™               | SyncFET™                                                                            |                 |
| FPS™                                | Power220®          | TCM™                                                                                |                 |
| FRFET®                              | Power247®          | The Power Franchise®                                                                |                 |
| GlobalOptoisolator™                 | PowerEdge™         |  ™ |                 |
| GTO™                                | PowerSaver™        | TinyBoost™                                                                          |                 |

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.

2. A critical component in any component of a life support device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

| Datasheet Identification | Product Status         | Definition                                                                                                                                                                                               |
|--------------------------|------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Advance Information      | Formative or In Design | This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.                                                                       |
| Preliminary              | First Production       | This datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design. |
| No Identification Needed | Full Production        | This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.                                                   |
| Obsolete                 | Not In Production      | This datasheet contains specifications on a product that has been discontinued by Fairchild Semiconductor. The datasheet is printed for reference information only.                                      |

Rev. I27