



NINGBO FORYARD OPTO  
ELECTRONICS CO.,LTD.


# LED DIGIT DISPLAY

PartNO.: FYS-10012E/FXX-XX

## DESCRIPTION

- 26.00mm (1.0") Single digit numeric display series.
- Standard brightness.
- Low current operation.
- Excellent character appearance.
- Easy mounting on P.C.boards or sockets

## Package Dimensions & Internal Circuit Diagram



### Notes:

- All dimensions are in millimeters (inches)
- Tolerance is  $\pm 0.25(0.01)$  unless otherwise noted.
- Specifications are subject to change without notice.

ADD: NO.115 QiXin Road NingBo Zhejiang China ZIP.: 315051  
TEL: 0086-574-87927870 87933652 FAX: 0086-574-87927917  
[Http://www.foryard.com](http://www.foryard.com) E-mail: sales@foryard.com



**PartNO.: FYS-10012E/FXX-XX**

: Absolute maximum ratings (Ta=25℃)

| Parameter             | Symbol | Test Condition      | Value |       | Unit |
|-----------------------|--------|---------------------|-------|-------|------|
|                       |        |                     | Min   | Max   |      |
| Reverse Voltage       | VR     | IR=30μA             | 5     | ----- | V    |
| Forward Current       | IF     | -----               | ----- | 30    | mA   |
| Power Dissipation     | Pd     | -----               | ----- | 100   | mW   |
| Pulse Current         | Ipeak  | Duty=0.1mS,<br>1KHz | ----- | 150   | mA   |
| Operating Temperature | Topr   | -----               | -40   | +85   | ° C  |
| Storage Temperature   | Tstr   | -----               | -40   | +85   | ° C  |

■ **Description:**

• Color Code & Chip characteristics: (Test Condition: IF=20mA)

| Emitting Color |           | Dice Material       | Peak Wave Length (λp) | Spectral Line halfwidth(Δλ1/2) | Forward Voltage(VF)<br>Unit:V |      | Luminous Intensity (Iv)<br>Unit:ucd |
|----------------|-----------|---------------------|-----------------------|--------------------------------|-------------------------------|------|-------------------------------------|
|                |           |                     |                       |                                | Typ                           | Max  |                                     |
| H              | Red       | GaP/GaP             | 700nm                 | 90nm                           | 2.25                          | 2.50 | 500                                 |
| S              | Hi Red    | GaAlAs/GaAs,SH      | 660nm                 | 20nm                           | 1.85                          | 2.20 | 3500                                |
| D              | Super Red | GaAlAs/GaAs,DH      | 660nm                 | 20nm                           | 1.85                          | 2.20 | 6000                                |
| UR             | Ultra Red | GaAlAs/GaAs,DD<br>H | 660nm                 | 20nm                           | 1.85                          | 2.20 | 12000                               |
| E              | Orange    | GaAsP/GaP           | 635nm                 | 35nm                           | 2.10                          | 2.50 | 2500                                |
| Y              | Yellow    | GaAsP/GaP           | 585nm                 | 35nm                           | 2.10                          | 2.50 | 2000                                |
| G              | Green     | GaP/GaP             | 570nm                 | 30nm                           | 2.20                          | 2.50 | 2500                                |

• -XX: Surface / Lens color:


| Number            | 0           | 1              | 2            | 3              | 4               | 5 |
|-------------------|-------------|----------------|--------------|----------------|-----------------|---|
| Ref Surface Color | White       | Black          | Gray         | Red            | Green           |   |
| Epoxy Color       | Water clear | White diffused | Red Diffused | Green Diffused | Yellow Diffused |   |



NINGBO FORYARD OPTO  
ELECTRONICS CO.,LTD.


# LED DIGIT DISPLAY

PartNO.: FYS-10012E/FXX-XX




- (1) - GaAsP/GaAs 655nm/Red
- (2) - GaP 570nm/Yellow Green
- (3) - GaAsP/GaP 585nm/Yellow
- (4) - GaAsP/GaP 635nm/Orange & Hi-Eff Red
- (5) - GaP 700nm/Bright Red
- (6) - GaAlAs/GaAs 660nm/Super Red
- (8) - GaAsP/GaP 610nm/Super Red


- (9) - GaAlAs 880nm
- (10) - GaAs/GaAs & GaAlAs/GaAs 940nm
- (A) - GaN/SiC 430nm/Blue
- (B) - InGaN/SiC 470nm/Blue
- (C) - InGaN/SiC 505nm/Ultra Green
- (D) - InGaAl/SiC 525nm/Ultra Green




FORWARD VOLTAGE (V)  
FORWARD CURRENT VS.  
FORWARD VOLTAGE





FORWARD CURRENT (mA)  
RELATIVE LUMINOUS  
INTENSITY VS. FORWARD  
CURRENT



AMBIENT TEMPERATURE Ta (°C)  
FORWARD CURRENT VS. AMBIENT  
TEMPERATURE



AMBIENT TEMPERATURE Ta (°C)



NOTE: 25°C free air temperature unless otherwise specified


ADD: NO.115 QiXin Road NingBo Zhejiang China ZIP.: 315051

TEL: 0086-574-87927870 87933652

[Http://www.foryard.com](http://www.foryard.com)

FAX: 0086-574-87927917

E-mail: sales@foryard.com

**PartNO.: FYS-10012E/FXX-XX**

E-mail:sales@foryard.com