

Si PIN photodiode S3994-01

Si PIN photodiode for optical power meters



S3994-01 is a Si PIN photodiode designed for optical power meters. Compared to the previous type (S3994), S3994-01 has an improved anti-reflection film and sensitivity optimized for detection of violet laser beams. The flat glass used as the light input window is less susceptible to scratches than resin windows, allowing easy handling.

Features

- Thin package (1.4 mm Max.)
- High sensitivity: 0.28 A/W Typ. ($\lambda=410$ nm)
- Large active area: 10×10 mm

Applications

- Violet laser detection


■ Absolute maximum ratings ($T_a=25^\circ\text{C}$)

Parameter	Symbol	Value	Unit
Reverse voltage	V_R Max.	50	V
Operating temperature	T_{opr}	-20 to +60	$^\circ\text{C}$
Storage temperature	T_{stg}	-20 to +80	$^\circ\text{C}$


■ Electrical and optical characteristics ($T_a=25^\circ\text{C}$)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Spectral response range	λ		-	320 to 1100	-	nm
Peak sensitivity wavelength	λ_p		-	960	-	μm
Photo sensitivity	S	$\lambda=410$ nm	0.24	0.28	-	A/W
Dark current	I_D	$V_R=30$ V	-	3	10	nA
Terminal capacitance	Ct	$V_R=30$ V, $f=1$ MHz	-	40	-	pF
Cut-off frequency	f_c	$V_R=30$ V, $R_L=50 \Omega$ -3 dB	-	20	-	MHz


■ Spectral response




■ Dark current vs. reverse voltage



■ Terminal capacitance vs. reverse voltage



■ Dimensional outline (unit: mm)

**HAMAMATSU**

Information furnished by HAMAMATSU is believed to be reliable. However, no responsibility is assumed for possible inaccuracies or omissions. Specifications are subject to change without notice. No patent rights are granted to any of the circuits described herein. ©2001 Hamamatsu Photonics K.K.

HAMAMATSU PHOTONICS K.K., Solid State Division

1126-1 Ichino-cho, Higashi-ku, Hamamatsu City, 435-8558 Japan, Telephone: (81) 53-434-3311, Fax: (81) 53-434-5184, <http://www.hamamatsu.com>

U.S.A.: Hamamatsu Corporation: 360 Foothill Road, P.O.Box 6910, Bridgewater, N.J. 08807-0910, U.S.A., Telephone: (1) 908-231-0960, Fax: (1) 908-231-1218

Germany: Hamamatsu Photonics Deutschland GmbH: Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49) 08152-3750, Fax: (49) 08152-2658

France: Hamamatsu Photonics France S.A.R.L.: 19, Rue du Saule Trapu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: 33-(1) 69 53 71 00, Fax: 33-(1) 69 53 71 10

United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Tewin Road, Welwyn Garden City, Hertfordshire AL7 1BW, United Kingdom, Telephone: (44) 1707-294888, Fax: (44) 1707-325777

North Europe: Hamamatsu Photonics Norden AB: Smidesvägen 12, SE-171 41 Solna, Sweden, Telephone: (46) 8-509-031-00, Fax: (46) 8-509-031-01

Italy: Hamamatsu Photonics Italia S.R.L.: Strada della Moia, 1/E, 20020 Arese, (Milano), Italy, Telephone: (39) 02-935-81-733, Fax: (39) 02-935-81-741

Cat. No. KPIN1057E01
Jan. 2001 DN