


Si photodiode array

S7978

5 × 5 element array for X-ray detector



Features

- High reliability photodiode with ceramic scintillator
High X-ray sensitivity: 1.8 times higher than CWO scintillator
Less afterglow: <0.1 %/3 ms, <0.01 %/30 ms
No deliquescence
- 5 × 5 element photodiode array
- Number of channels can be increased by connecting several S7978 together.

Applications

- X-ray analysis, X-ray detection

■ Absolute maximum ratings (Ta=25 °C)

Parameter	Symbol	Value	Unit
Reverse voltage	VR Max.	5	V
Operating temperature	Topr	-10 to +60	°C
Storage temperature	Tstg	-20 to +70	°C

■ Electrical and optical characteristics (Ta=25 °C, per 1 element, without scintillator)



Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Spectral response range	λ	With resin	-	220 to 1000	-	nm
Peak sensitivity wavelength	λ_p		-	720	-	μm
Photo sensitivity	S	$\lambda=500\text{ nm}$, with resin	-	0.36	-	A/W
Dark current	ID	VR=10 mV	-	0.1	10	pA
Terminal capacitance	Ct	VR=5 V, f=10 kHz	-	30	50	pF

■ X-ray sensitivity (reference value, per 1 element, tube current: 1.0 mA, aluminum filter: t=6 mm, distance=830 mm)

X-ray tube voltage	Typ.	Unit
120 kV	2.1	nA

Note) Depends on equipment and measurement conditions.

■ Dimensional outline (unit: mm)



B-side		A-side	
Pin No.	Element No.	Pin No.	Element No.
1	Cathode	1	Cathode
2	e1	2	Shield
3	d1	3	b1
4	c1	4	a1
5	e2	5	b2
6	d2	6	a2
7	c2	7	a3
8	e3	8	b3
9	d3	9	b4
10	c3	10	c4
11	e4	11	c5
12	d4	12	a4
13	d5	13	b5
14	e5	14	a5

KSPDA0146EA

HAMAMATSU

HAMAMATSU PHOTONICS K.K., Solid State Division

1126-1 Ichino-cho, Higashi-ku, Hamamatsu City, 435-8558 Japan, Telephone: (81) 53-434-3311, Fax: (81) 53-434-5184, <http://www.hamamatsu.com>

U.S.A.: Hamamatsu Corporation, 360 Foothill Road, P.O.Box 6910, Bridgewater, N.J. 08807-0910, U.S.A., Telephone: (1) 908-231-0960, Fax: (1) 908-231-1218

Germany: Hamamatsu Photonics Deutschland GmbH, Arzbergerstr. 10, D-82211 Herrsching am Ammersee, Germany, Telephone: (49) 08152-3750, Fax: (49) 08152-2658

France: Hamamatsu Photonics France S.A.R.L.: 19, Rue du Saule Traipu, Parc du Moulin de Massy, 91882 Massy Cedex, France, Telephone: 33-(1) 69 53 71 00, Fax: 33-(1) 69 53 71 10

United Kingdom: Hamamatsu Photonics UK Limited: 2 Howard Court, 10 Tewin Road, Welwyn Garden City, Hertfordshire AL7 1BW, United Kingdom, Telephone: (44) 1707-294888, Fax: (44) 1707-325777

North Europe: Hamamatsu Photonics Norden AB: Smidesvägen 12, SE-171 41 Solna, Sweden, Telephone: (46) 8-509-031-00, Fax: (46) 8-509-031-01

Italy: Hamamatsu Photonics Italia S.R.L.: Strada della Moia, 1/E, 20020 Arese, (Milano), Italy, Telephone: (39) 02-935-81-733, Fax: (39) 02-935-81-741

Information furnished by HAMAMATSU is believed to be reliable. However, no responsibility is assumed for possible inaccuracies or omissions. Specifications are subject to change without notice. No patent rights are granted to any of the circuits described herein. ©2004 Hamamatsu Photonics K.K.