

# 60 Watts

## DPS50 Series

Total Power: 30 - 60 Watts  
Input Voltage: 127 - 300 VDC, 90 - 264 VAC  
# of Outputs: Single



### Special Features

- CE Mark EMC & LVD
- Universal AC input
- Fully regulated output
- Overload and short circuit protection
- Internal remote sense
- Constant voltage
- High efficiency
- High MTBF
- IEC320 AC receptacle, 3 pin (type C14)
- Built in EMI filter (CISPR 22 Class B)
- LED power good indicator
- Input power <74 watts
- Complies with EN61000-3-2

### Environmental

Operating temperature: 0°C to +40°C ambient. Derate each output as 2.5% per degree from 40° to 60°C. -20°C start up.

Storage temperature: -40°C to +85°C

Electromagnetic susceptibility designed to meet EN61000-4; -2, -3, -4, -5, -6, -8, -11, level 3

Humidity: Operating; non-condensing; 10% to 95% RH

Vibration: Three orthogonal axes, 3 sweeps per axe at 1 oct/min. 2G peak 8 Hz to 500 Hz, operational

MTBF demonstrated: >550,000 hours at full load and 25°C ambient conditions

### Electrical Specs

#### Input

|                               |                                                                |
|-------------------------------|----------------------------------------------------------------|
| Input range                   | 90 - 264 VAC (wide range),<br>127 - 300 VDC                    |
| Frequency                     | 47 - 440 Hz                                                    |
| Inrush current                | <50A @ 230 VAC, cold start @ 25C                               |
| Input current                 | <2.0A rms @ 115 VAC; <1A @ 230 VAC                             |
| Efficiency                    | >80% @ full load typical, @115VAC                              |
| EMI/RFI                       | FCC Part 15, Subpart B Class B &<br>EN55022 (CISPR 22) Class B |
| Safety ground leakage current | <0.5mA @ 50/60 Hz, 264 VAC input                               |

#### Output

|                             |                                                                                                     |
|-----------------------------|-----------------------------------------------------------------------------------------------------|
| Maximum Power (Po)          | 60W (DPS52, 30W)                                                                                    |
| Hold-up time                | 10 ms. typical at full load @ 115VAC                                                                |
| Overvoltage protection      | 20% - 45% above nominal output maximum.<br>Latching type, recycle AC to reset.                      |
| Overload protection         | Output short circuit protection auto recover. Overload protected @ 120 - 150% above maximum rating. |
| Cable/connector barrel type | DC cable with 2.5 mm center plug<br>DC plug center +v<br>DC plug outer -v                           |

### Safety

|       |                        |
|-------|------------------------|
| UL    | UL 60950-1             |
| CSA   | CSA-C22.2 No. 60950-1  |
| NEMKO | IEC/EN60950-1          |
| VDE   | EN60950-1              |
| CE    | EMC & LVD              |
| CB    | Certificate and report |
| CCC   | GB4943                 |

# AMERICAS

5810 Van Allen Way  
Carlsbad, CA 92008  
Telephone: 760-930-4600  
Facsimile: 760-930-0698

# EUROPE

Astec House, Waterfront Business Park  
Merry Hill, Dudley  
West Midlands, DY5 1LX, UK  
Telephone: 44 (1384) 842-211  
Facsimile: 44 (1384) 843-355

# ASIA


Units 2111-2116, Level 21  
Tower1, Metrolaza  
223, Hing Fong Road  
Kwai Fong, New Territories  
Hong Kong  
Telephone: 852-2437-9662  
Facsimile: 852-2402-4426



## Ordering Information

| Model Number | Maximum Power | Output Voltage | Maximum Load | Peak Load <sup>1</sup> | Regulation <sup>2</sup> | Ripple P/P (PARD) <sup>3</sup> |
|--------------|---------------|----------------|--------------|------------------------|-------------------------|--------------------------------|
| DPS52        | 30W           | 5V             | 6A           | 6.5A                   | ±2%                     | 50mV                           |
| DPS53        | 60W           | 12V            | 5A           | 5.4A                   | ±2%                     | 120mV                          |
| DPS54        | 60W           | 15V            | 4A           | 4.3A                   | ±2%                     | 150mV                          |
| DPS55        | 60W           | 24V            | 2.5A         | 2.7A                   | ±2%                     | 240mV                          |
| DPS58        | 60W           | 48V            | 1.25A        | 1.35A                  | ±2%                     | 480mV                          |

1. Peak-to-peak with 20 MHz bandwidth and 10  $\mu$ F tantalum capacitor in parallel with a 0.1  $\mu$ F capacitor.



### NOTES:

- Specifications subject to change without notice.
- All dimensions in inches (mm), tolerance is  $\pm 0.02$ " ( $\pm 0.5$ mm)
- Warranty: 1 year
- Weight: 1.06 lb./ .48 kg
- AC input power cord sold separately.
- Specifications are for convection rating at factory settings at 115VAC input, 25°C unless otherwise stated