

Linear Systems replaces discontinued Intersil IT124

The LS124 is a monolithic pair of Super-Beta NPN transistors mounted in a single TO-78 package. The monolithic dual chip design reduces parasitics and gives better performance while ensuring extremely tight matching. The LS124 is a direct replacement for discontinued Intersil IT124.

The hermetically sealed TO-78 is well suited for hi-rel and harsh environment applications.

(See Packaging Information).

LS124 Features:

- Very high gain
- Tight matching
- Low Output Capacitance

FEATURES

Direct Replacement for INTERSIL IT124

HIGH GAIN $h_{FE} \geq 1500$ @ 1 AND 10 μ A

LOW OUTPUT CAPACITANCE ≤ 2.0 pF

V_{BE} tracking ≤ 5.0 μ V/°C

ABSOLUTE MAXIMUM RATINGS¹
@ 25°C (unless otherwise noted)

Maximum Temperatures

Storage Temperature -65°C to +200°C

Operating Junction Temperature -55°C to +150°C

Maximum Power Dissipation

Continuous Power Dissipation (One side) 250mW

Continuous Power Dissipation (Both sides) 500mW

Linear Derating factor (One side) 2.3mW/°C

Linear Derating factor (Both sides) 4.3mW/°C

Maximum Currents

Collector Current 10mA

MATCHING CHARACTERISTICS @ 25°C (unless otherwise stated)

SYMBOL	CHARACTERISTIC	MIN	TYP	MAX	UNITS	CONDITIONS
$ V_{BE1} - V_{BE2} $	Base Emitter Voltage Differential	--	2	5	mV	$I_C = 10\mu A, V_{CE} = 1V$
$\Delta (V_{BE1} - V_{BE2}) / \Delta T$	Base Emitter Voltage Differential Change with Temperature	--	5	15	$\mu V/^\circ C$	$I_C = 10\mu A, V_{CE} = 1V$ $T_A = -55^\circ C$ to $+125^\circ C$
$ I_{B1} - I_{B2} $	Base Current Differential	--	--	0.6	nA	$I_C = 10\mu A, V_{CE} = 1V$

ELECTRICAL CHARACTERISTICS @ 25°C (unless otherwise noted)

SYMBOL	CHARACTERISTICS	MIN.	TYP.	MAX.	UNITS	CONDITIONS
BV_{CBO}	Collector to Base Voltage	2	--	--	V	$I_C = 10\mu A, I_E = 0$
BV_{CEO}	Collector to Emitter Voltage	2	--	--	V	$I_C = 10\mu A, I_B = 0$
BV_{EBO}	Emitter-Base Breakdown Voltage	6.2	--	--	V	$I_E = 10\mu A, I_C = 0$
BV_{CCO}	Collector to Collector Voltage	100	--	--	V	$I_C = 10\mu A, I_E = 0$
h_{FE}	DC Current Gain	1500	--	--		$I_C = 1\mu A, V_{CE} = 1V$
		1500	--	--		$I_C = 10\mu A, V_{CE} = 1V$
$V_{CE(SAT)}$	Collector Saturation Voltage	--	--	0.5	V	$I_C = 1mA, I_B = 0.1mA$
I_{EBO}	Emitter Cutoff Current	--	--	100	pA	$I_C = 0, V_{EB} = 3V$
I_{CBO}	Collector Cutoff Current	--	--	100	pA	$I_E = 0, V_{CB} = 1V$
C_{OBO}	Output Capacitance	--	--	2	pF	$I_E = 0, V_{CB} = 1V$
C_{C1C2}	Collector to Collector Capacitance	--	--	2	pF	$V_{CC} = 0V$
I_{C1C2}	Collector to Collector Leakage Current	--	--	10	nA	$V_{CC} = \pm 50V$
f_T	Current Gain Bandwidth Product	100	--	--	MHz	$I_C = 100\mu A, V_{CE} = 1V$
NF	Narrow Band Noise Figure	--	--	3	dB	$I_C = 10\mu A, V_{CE} = 3V, BW = 200Hz, R_G = 10K\Omega, f = 1KHz$

Notes:

- Absolute Maximum ratings are limiting values above which serviceability may be impaired
- The reverse base-to-emitter voltage must never exceed 6.2 volts; the reverse base-to-emitter current must never exceed 10 μ A.

Available Packages:

LS124 in TO-78
LS124 available as bare die



Please contact Micross for full package and die dimensions:

Email: chipcomponents@micross.com
Web: www.micross.com/distribution.aspx

TO-78 (Bottom View)

