

Description


The TOKO DAL5250CT17T is a compact, vertically polarized dielectric antenna specifically designed for 5.250 GHz applications including IEEE 802.11a wireless networking. The antenna unit consists of a dielectric element with a 50Ω center terminal permitting direct connection to a 50Ω printed circuit board pattern without a matching circuit.



Features


- Center Frequency: 5250 MHz
- Bandwidth: ± 100 MHz
- Miniature footprint: 10mm diameter
- Low profile: 3.4mm
- Peak Gain: 2.0 dBi (typ.)
- SWR: 2.0 max.
- Impedance: 50 Ω
- Weight: 1.0 gram
- Operation temperature: - 20°C to + 85°C
- Storage temperature: - 40°C to + 90°C

Dimensions




Typical Characteristics

Horizontal Pattern



Vertical Pattern



NOTE: All characteristics measured with antenna centered on a 50.0mm x 50.0mm ground plane of 0.3mm thickness.



The information furnished by TOKO, Inc. is believed to be accurate and reliable. However, TOKO reserves the right to make changes or improvements in the design, specification or manufacture of its products without further notice. TOKO does not assume any liability arising from the application or use of any product or circuit described herein, nor for any infringements of patents or other rights of third parties which may result from the use of its products. No license is granted by implication or otherwise under any patent or patent rights of TOKO, Inc.