

*Excellence in Electronics***TYPE
CK6437/
CK1037**

The CK6437/CK1037 is a cold cathode, corona-discharge tube of subminiature construction, designed for use as a voltage regulator in high voltage low current supplies. It has an operating current range of 5 to 125 μ a. over which it maintains a substantially constant operating voltage of 700 volts. Two cathode leads are provided which may be used to disconnect the load when the tube is removed from the socket. The flexible terminal leads may be soldered or welded directly to the terminals of circuit components without the use of sockets. Standard inline subminiature sockets may be used by cutting the leads to a suitable length.

MECHANICAL DATA

ENVELOPE: T-3 Glass

BASE: None (0.016" tinned flexible leads. Length: 1.5" min.
Spacing: 0.096" center-to-center)

TERMINAL CONNECTIONS:

Lead 1 Cathode
Lead 3 Anode
Lead 5 Cathode

MOUNTING POSITION: Any

ELECTRICAL DATA

RATINGS - ABSOLUTE MAXIMUM VALUES:


DC Anode Supply Voltage
Minimum DC Anode Supply Voltage ▲
DC Operating Current
Ambient Temperature Range

2000 volts
800 volts
5 to 125 μ a
-55 to +70 °C

CHARACTERISTICS AND TYPICAL OPERATION:

DC Starting Voltage (approx.)
DC Operating Voltage (approx.) at 25 μ a
Regulation (5 to 100 μ a.)
Leakage current at 500 volts

800 volts max.
700 volts
15 volts max.
0.5 μ a max.



▲ Not less than indicated supply voltage should be provided to insure "starting" throughout tube life.

Tentative Data