



SANYO Semiconductors

DATA SHEET

An ON Semiconductor Company

TIG110BF — High Power High Speed Switching Applications

N-Channel Non Punch Through IGBT

Features

- Low-saturation voltage
- Ultrahigh speed switching
- Enhansment type

Specifications

Absolute Maximum Ratings at Ta=25°C, Unless otherwise specified

Parameter	Symbol	Conditions		Ratings	Unit
Collector-to-Emitter Voltage	V _{CES}			600	V
Gate-to-Emitter Voltage	V _{GES}			±30	V
Collector Current (DC)	I _{Cc} *1	Limited by Tjmax		27	A
	I _C *2	Limited by Tjmax	@Tc=25°C*3	14	A
			@Tc=100°C*3	6	A
Collector Current (Pulse)	I _{CP}	Pulse width Limited by Tjmax		108	A
Allowable Power Dissipation	P _D			2	W
		Tc=25°C (SANYO's ideal heat dissipation condition)*3		30	W
Junction Temperature	T _j			150	°C
Storage Temperature	T _{stg}			-55 to +150	°C

Note : *1 Shows chip capability

*2 Collector current is calculated from the following for mula

$$I_C(T_C) = \frac{T_{jmax} - T_C}{R_{th(j-c)} \times V_{CE(sat)max}(T_{jmax}, I_C(T_C))}$$


*3 SANYO's condition is radiation from backside.

The method is applying silicone grease to the backside of the device and attaching the device to water-cooled radiator made of aluminium.

Package Dimensions

unit : mm (typ)


7509-005




Product & Package Information

- Package : TO-220FI(LS)
- JEITA, JEDEC : SC-67, SOT-186A, TO-220F
- Minimum Packing Quantity : 100 pcs./bag, 50 pcs./magazine

Marking



Electrical Connection



SANYO Semiconductor Co., Ltd.

<http://semicon.sanyo.com/en/network>

TIG110BF


Electrical Characteristics at Tj=25°C, Unless otherwise specified

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Collector-to-Emitter Breakdown Voltage	V(BR)CES	IC=1mA, VGE=0V	600			V
Collector-to-Emitter Cutoff Current	ICES	VCE=600V, VGE=0V			100	μA
					1	mA
Gate-to-Emitter Leakage Current	IGES	VGE=±30V, VCE=0V			±100	nA
Gate-to-Emitter Threshold Voltage	VGE(off)	VCE=10V, IC=1mA	4.0	5.0	6.0	V
Collector-to-Emitter Saturation Voltage	VCE(sat)1	VGE=15V, IC=15A		1.6	2.0	V
	VCE(sat)2	Tj=25°C		1.75		V
		Tj=125°C		2.2		V
Input Capacitance	Cies	VCE=30V, f=1MHz		2880		pF
Output Capacitance	Coes			45		pF
Reverse Transfer Capacitance	Cres			38		pF
Turn-ON Delay Time	td(on)			65		ns
Rise Time	tr	L=200μH, VGE=15V, IC=15A, VCC=300V, Rg=30Ω, See specified Test Circuit.		30		ns
Turn-ON Time	ton			300		ns
Turn-OFF Delay Time	td(off)			250		ns
Fall Time	tf			120		ns
Turn-OFF Time	toff			450		ns
Total Gate Charge	Qg	VCE=300V, VGE=15V, IC=15A		95		nC
Gate-to-Source Charge	Qgs			20		nC
Gate-to-Drain "Miller" Charge	Qgd			30		nC


Thermal Characteristics at Ta=25°C, Unless otherwise specified

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Thermal Resistance (Junction- Case)	Rth(j-c)	Tc=25°C (SANYO's ideal heat dissipation condition)*3			4.17	°C / W
Thermal Resistance (Junction- at mosphere)	Rth(j-a)				62.5	°C / W









Switching Time Test Circuit












Timing Chart



TIG110BF







- Any and all SANYO Semiconductor Co.,Ltd. products described or contained herein are, with regard to "standard application", intended for the use as general electronics equipment. The products mentioned herein shall not be intended for use for any "special application" (medical equipment whose purpose is to sustain life, aerospace instrument, nuclear control device, burning appliances, transportation machine, traffic signal system, safety equipment etc.) that shall require extremely high level of reliability and can directly threaten human lives in case of failure or malfunction of the product or may cause harm to human bodies, nor shall they grant any guarantee thereof. If you should intend to use our products for new introduction or other application different from current conditions on the usage of automotive device, communication device, office equipment, industrial equipment etc. , please consult with us about usage condition (temperature, operation time etc.) prior to the intended use. If there is no consultation or inquiry before the intended use, our customer shall be solely responsible for the use.
- Specifications of any and all SANYO Semiconductor Co.,Ltd. products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- SANYO Semiconductor Co.,Ltd. assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all SANYO Semiconductor Co.,Ltd. products described or contained herein.
- SANYO Semiconductor Co.,Ltd. strives to supply high-quality high-reliability products, however, any and all semiconductor products fail or malfunction with some probability. It is possible that these probabilistic failures or malfunction could give rise to accidents or events that could endanger human lives, trouble that could give rise to smoke or fire, or accidents that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all SANYO Semiconductor Co.,Ltd. products described or contained herein are controlled under any of applicable local export control laws and regulations, such products may require the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written consent of SANYO Semiconductor Co.,Ltd.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the SANYO Semiconductor Co.,Ltd. product that you intend to use.
- Upon using the technical information or products described herein, neither warranty nor license shall be granted with regard to intellectual property rights or any other rights of SANYO Semiconductor Co.,Ltd. or any third party. SANYO Semiconductor Co.,Ltd. shall not be liable for any claim or suits with regard to a third party's intellectual property rights which has resulted from the use of the technical information and products mentioned above.

This catalog provides information as of September, 2011. Specifications and information herein are subject to change without notice.