

### Features

Very Low Forward Voltage Drop

High Conductance

For Use in DC-DC Converter, PCMCIA,  
and Mobile Telecommunications Applications

**Lead Free by Design/RoHS Compliant (Note 3)**

### Mechanical Data

Case: SOT-23

Case Material: Molded Plastic. UL Flammability  
Classification Rating 94V-0

Moisture Sensitivity: Level 1 per J-STD-020C

Terminals: Solderable per MIL-STD-202, Method 208


Lead Free Plating (Matte Tin Finish annealed over Alloy 42  
leadframe).

Polarity: See Diagram

Marking: K79 and Date Code, See Page 3

Ordering Information: See Page 3

Weight: 0.008 grams (approximate)



SOT-23		
Dim	Min	Max
A	0.37	0.51
B	1.20	1.40
C	2.30	2.50
D	0.89	1.03
E	0.45	0.60
G	1.78	2.05
H	2.80	3.00
J	0.013	0.10
K	0.903	1.10
L	0.45	0.61
M	0.085	0.180
	0	8
All Dimensions in mm		

### Maximum Ratings @ T<sub>A</sub> = 25 °C unless otherwise specified

Characteristic	Symbol	Value	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V <sub>RRM</sub> V <sub>RWM</sub> V <sub>R</sub>	40	V
RMS Reverse Voltage	V <sub>R(RMS)</sub>	28	V
Average Rectified Current	I <sub>O</sub>	1.0	A
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load	I <sub>FSM</sub>	5.5	A
Power Dissipation (Note 1)	P <sub>d</sub>	500	mW
Typical Thermal Resistance, Junction to Ambient Air (Note 1)	R <sub>JA</sub>	200	°C/W
Operating Temperature Range	T <sub>J</sub>	-40 to +125	°C
Storage Temperature Range	T <sub>STG</sub>	-40 to +150	°C

### Electrical Characteristics @ T<sub>A</sub> = 25 °C unless otherwise specified

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Breakdown Voltage (Note 2)	V <sub>(BR)R</sub>	40			V	I <sub>R</sub> = 300uA
Forward Voltage	V <sub>F</sub>		225 235 290 340 390 420 475	270 290 340 400 450 500 600	mV	I <sub>F</sub> = 50mA I <sub>F</sub> = 100mA I <sub>F</sub> = 250mA I <sub>F</sub> = 500mA I <sub>F</sub> = 750mA I <sub>F</sub> = 1000mA I <sub>F</sub> = 1500mA
Reverse Current (Note 2)	I <sub>R</sub>			100	A	V <sub>R</sub> = 30V
Total Capacitance	C <sub>T</sub>		175 25		pF pF	V <sub>R</sub> = 0V, f = 1.0MHz V <sub>R</sub> = 25V, f = 1.0MHz

- Notes:
- Part mounted on FR-4 board with recommended pad layout, which can be found on our website at <http://www.diodes.com/datasheets/ap02001.pdf>.
  - Short duration pulse test used to minimize self-heating effect.
  - No purposefully added lead.




Fig. 1 Forward Current Derating Curve




Fig. 2 Typical Forward Characteristics




Fig. 3 Typ. Total Capacitance vs Reverse Voltage




Fig. 4 Typical Safe Operating Area


Note: 1. Assumed application thermal conditions.  
 $R_{JA}$  varies depending on application.

## Ordering Information (Note 4)

Device	Packaging	Shipping
BAT1000-7-F	SOT-23	3000/Tape & Reel

Notes: 4. For Packaging Details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

## Marking Information



K79 = Product Type Marking Code  
 YM = Date Code Marking  
 Y = Year ex: N = 2002  
 M = Month ex: 9 = September

### Date Code Key

Year	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012
Code	N	P	R	S	T	U	V	W	X	Y	Z

Month	Jan	Feb	March	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	O	N	D

### IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

### LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.