



SAW Components

Data Sheet B9000

Data Sheet

An abstract graphic featuring the word "EPCOS" in large, glowing, 3D letters. The letters are white with a blue glow and are positioned diagonally across the frame. In the background, there is a faint, stylized globe with circuitry patterns, suggesting a global network or technological theme. The overall color scheme is dark with blue and white highlights.



SAW Components

B9000

Low-Loss Filter for Mobile Communication

1575,42 MHz

Data Sheet






Chip sized SAW package

Features

- Low-loss RF filter for GPS
- Low amplitude ripple
- No matching network required for operation at 50 Ω
- Ceramic package for Surface Mounted Technology (SMT)

Terminals


- Gold-plated Ni



Dimensions in mm, approx. weight 0,007 g

Pin configuration

- 4 Input, unbalanced
- 1 Output, unbalanced
- 2,5 Case ground
- 3 to be grounded



Type	Ordering code	Marking and Package according to	Packing according to
B9000	B39162-B9000-C710	C61157-A7-A82	F61074-V8151-Z000

Electrostatic Sensitive Device (ESD)

Maximum ratings

Operating temperature range	T	- 40/+ 85	$^{\circ}\text{C}$	824...956, 1710...2170 MHz elsewhere
Storage temperature range	T_{stg}	- 40/+ 85	$^{\circ}\text{C}$	
DC voltage	V_{DC}	3	V	
Input Power max. (source impedance 50 Ω)	P_{IN}	25,0 10,0	dBm	



SAW Components

B9000

Low-Loss Filter for Mobile Communication

1575,42 MHz

Data Sheet



Characteristics

Operating Temperature Range: $T = -40^{\circ}\text{C}$ to 85°C
Terminating source impedance: $Z_S = 50\Omega$
Terminating load impedance: $Z_L = 50\Omega$

		min.	typ.	max.	
Center frequency	f_C	—	1575,42	—	MHz
Maximum insertion attenuation	$\alpha_{\max}$				
	1574,42 ... 1576,42 MHz*)	—	0,5	0,8	dB
	1574,42 ... 1576,42 MHz	—	0,5	0,9	dB
Amplitude ripple	$\Delta\alpha$				
	1574,42 ... 1576,42 MHz	—	0,0	0,3	dB
Absolute attenuation	α				
	500,0MHz ... 894,0 MHz	16	18	—	dB
	894,0MHz ... 1500,0 MHz	15	17	—	dB
	1650,0MHz ... 4000,0 MHz	18	20	—	dB
	4000,0MHz ... 6000,0 MHz	15	20	—	dB
VSWR					
	1574,42MHz ... 1576,42MHz*)	—	1,1	1,5	
	1574,42MHz ... 1576,42 MHz	—	1,1	1,6	

*) $T_A = -30 \dots +70^{\circ}\text{C}$



SAW Components

B9000



Low-Loss Filter for Mobile Communication

1575,42 MHz

Data Sheet



Transfer function





SAW Components	B9000
Low-Loss Filter for Mobile Communication	1575,42 MHz
Data Sheet	SMD

Published by EPCOS AG

SAW MC WT, P.O. Box 80 17 09, 81617 Munich, GERMANY

TEL ++49 89 636 09, FAX ++49 89 636 2 26 89

© EPCOS AG 2002. Reproduction, publication and dissemination of this brochure and the information contained therein without EPCOS' prior express consent is prohibited.

Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise agreed.

This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.