


PHASE NOISE (1 Hz BW, typical)




FEATURES
- Frequency Range: 850 - 896 MHz - Tuning Voltage: 0.5-4.5 Vdc - MINI-14MS- - Style Package
APPLICATIONS
- Digital Cellular - VHF Communications - Base Stations

PERFORMANCE SPECIFICATIONS	VALUE	UNITS
Oscillation Frequency Range	850 - 896	MHz
Phase Noise @ 10 kHz offset (1 Hz BW, typ.)	-109	dBc/Hz
Harmonic Suppression (2nd, typ.)	-30	dBc
Tuning Voltage	0.5-4.5	Vdc
Tuning Sensitivity (avg.)	27	MHz/V
Power Output	3±3	dBm
Load Impedance	50	Ω
Input Capacitance (max.)	100	pF
Pushing	2	MHz/V
Pulling (14dB Return Loss, Any Phase)	3	MHz
Operating Temperature Range	-40 to 85	°C
Package Style	MINI-14MS-LOW	
POWER SUPPLY REQUIREMENTS		
Supply Voltage (Vcc, nom.)	5	Vdc
Supply Current (Icc, typ.)	23	mA


All specifications are typical unless otherwise noted and subject to change without notice.

APPLICATION NOTES
- AN-100/1 : Mounting and Grounding of VCOs - AN-102 : Proper Output Loading of VCOs - AN-107 : How to Solder Z-COMM VCOs
NOTES:

TUNING CURVE, typ.



POWER CURVE, typ.



PHYSICAL DIMENSIONS

