

PART NUMBER: VAD6 series

DESCRIPTION: DC/DC converter

features

- 6W isolated output
- efficiency to 82%
- regulated outputs
- Pi input filter
- low ripple and noise
- 24-Pin DIP package
- continuous short circuit protection



model number ^{1, 2, 3}	input voltage	output voltage	output current	input current		efficiency
				no load	full load	
VAD6-D12-S3R3	9-18VDC	3.3VDC	1000mA	7.5mA	393mA	70%
VAD6-D12-S5	9-18VDC	5VDC	1000mA	7.5mA	545mA	76%
VAD6-D12-S12	9-18VDC	12VDC	470mA	7.5mA	585mA	80%
VAD6-D12-S15	9-18VDC	15VDC	400mA	7.5mA	625mA	80%
VAD6-D12-D5	9-18VDC	±5VDC	±500mA	12mA	545mA	76%
VAD6-D12-D12	9-18VDC	±12VDC	±230mA	12mA	575mA	80%
VAD6-D12-D15	9-18VDC	±15VDC	±190mA	12mA	590mA	80%
VAD6-D24-S3R3	18-36VDC	3.3VDC	1000mA	5mA	197mA	70%
VAD6-D24-S5	18-36VDC	5VDC	1000mA	5mA	265mA	78%
VAD6-D24-S12	18-36VDC	12VDC	470mA	5mA	285mA	82%
VAD6-D24-S15	18-36VDC	15VDC	400mA	5mA	305mA	82%
VAD6-D24-D5	18-36VDC	±5VDC	±500mA	7.5mA	265mA	78%
VAD6-D24-D12	18-36VDC	±12VDC	±230mA	7.5mA	285mA	81%
VAD6-D24-D15	18-36VDC	±15VDC	±190mA	7.5mA	295mA	81%
VAD6-D48-S3R3	36-72VDC	3.3VDC	1000mA	2mA	98mA	70%
VAD6-D48-S5	36-72VDC	5VDC	1000mA	2mA	133mA	78%
VAD6-D48-S12	36-72VDC	12VDC	470mA	2mA	145mA	81%
VAD6-D48-S15	36-72VDC	15VDC	400mA	2mA	154mA	81%
VAD6-D48-D5	36-72VDC	±5VDC	±500mA	3mA	133mA	78%
VAD6-D48-D12	36-72VDC	±12VDC	±230mA	3mA	142mA	81%
VAD6-D48-D15	36-72VDC	±15VDC	±190mA	3mA	147mA	81%

NOTES:

1. suffix "HM" for 1.5K Vdc isolation
2. suffix "H" for 3K Vdc isolation
3. suffix "-SMT" for SMT case style



PART NUMBER: VAD6 series

DESCRIPTION: DC/DC converter

INPUT

input voltage range	12V	9-18V
	24V	18-36
	48V	36-72
input filter		Pi Type

OUTPUT

voltage accuracy		±2.0% max.
voltage balance(dual)		±1.0% max.
temperature coefficient		±0.05% / °C max.
ripple and noise, 20MHz BW	3.3V / 5V	100mV p-p max.
	12V / 15V	1% p-p max.
short circuit protection		continuous
line regulation	single/dual ¹	±0.5%
load regulation	single ²	±0.5%
	dual ³	±1.0%

GENERAL SPECIFICATIONS

efficiency		see table
isolation resistance		10 ⁹ Ohms
switching frequency		100kHz min.
isolation resistance		10 ⁹ Ohms
operating temperature range		-25°C to +71°C
storage temperature		-40°C to +100°C
case temp.(plastic case)		95°C max.
(copper case)		100°C max.
cooling		free air convection
dimensions		1.25x0.8x0.4 inches (31.8x20.3x10.2mm)

ISOLATION VOLTAGE

500 VDC min	standard models
1.5K VDC min	suffix "HM" models
3K VDC min ⁴	suffix "H" models

CASE MATERIAL

standard models	non-conductive black plastic
suffix "HM" models	black coated copper with non-conductive base

NOTES:


1. measured from high line to low line
2. measured from full load to 10% load
3. measured from full load to 1/4 load
4. non-conductive black plastic only

PART NUMBER: VAD6 series

DESCRIPTION: DC/DC converter

DIMENSIONS (mm)

NOTE: Pin Size is 0.02" Inch (0.5mm) DIA
All Dimensions In Inches(mm)
Tolerance .xx= ±.02, .xxx= ±.010



PIN CONNECTION

Pin	500 VDC		Pin	1.5K & 3K VDC	
	Single Output	Dual Output		Single Output	Dual Output
1	+V Input	+V Input	1	NP	NP
2	NC	-V Output	2	-V Input	-V Input
3	NC	Common	3	-V Input	-V Input
9	NP	NP	9	NC	Common
10	-V Output	Common	10	NC	NC
11	+V Output	+V Output	11	NC	-V Output
12	-V Input	-V Input	12	NP	NP
13	-V Input	-V Input	13	NP	NP
14	+V Output	+V Output	14	+V Output	+V Output
15	-V Output	Common	15	NC	NC
16	NP	NP	16	-V Output	Common
22	NC	Common	22	+V Input	+V Input
23	NC	-V Output	23	+V Input	+V Input
24	+V Input	+V Input	24	NP	NP

*NP-NO PIN

*NC-NO CONNECTION WITH PIN

DERATING CURVE

