



SAW Components

Data Sheet B4230

Data Sheet

An abstract graphic featuring the word "EPCOS" in large, glowing, 3D letters. The letters are white with a blue glow and are positioned diagonally across the frame. In the background, there is a faint, stylized globe with circuitry patterns, suggesting a global network or technological theme. The overall color scheme is dark with blue and white highlights.



SAW Components

B4230

Low-Loss Dual Band Filter for Mobile Communication

942,5 / 1842,5 MHz


Data Sheet



Features

- Low-loss RF filter for mobile telephone EGSM and PCN system , receive path
- Usable passband:
Filter 1 (EGSM): 35 MHz
Filter 2 (PCN): 75 MHz
- Suitable for GPRS class 1 to 12
- Ceramic package for Surface Mounted Technology (SMT)

Ceramic package QCC8E




Terminals

- Ni, gold-plated

Dimensions in mm, approx. weight 0,037 g

Pin configuration

- | | |
|------|---------------------|
| 1 | Input [Filter 1] |
| 3 | Input [Filter 2] |
| 5 | Output [Filter 2] |
| 7 | Output [Filter 1] |
| 2, 6 | to be grounded |
| 4, 8 | Case ground |



Type	Ordering code	Marking and Package according to	Packing according to
B4230	B39182-B4230-H410	C61157-A7-A92	F61074-V8129-Z000

Electrostatic Sensitive Device (ESD)

Maximum ratings

Operable temperature range	T	- 20 / + 70	°C	
Storage temperature range	T_{stg}	- 40 / + 85	°C	
DC voltage	V_{DC}	3	V	
Input power max.	P_{IN}			
EGSM:		15	dBm	
PCN:		12	dBm	



SAW Components

B4230

Low-Loss Dual Band Filter for Mobile Communication

942,5 / 1842,5 MHz

Data Sheet



Characteristics Filter 1 (EGSM)

Operating temperature range: $T = 25 \pm 2^{\circ}\text{C}$

Terminating source impedance: $Z_S = 50 \Omega$

Terminating load impedance: $Z_L = 50 \Omega$

		min.	typ.	max.	
Center frequency	f_c	—	942,50	—	MHz
Maximum insertion attenuation	$\alpha_{\max}$				
925,0 ... 960,0 MHz		—	2,8	3,2	dB
Amplitude ripple (p-p)	$\Delta\alpha$				
925,0 ... 960,0 MHz		—	1,7	1,9	dB
Input VSWR					
925,0 ... 960,0 MHz		—	1,9	2,2	
Output VSWR					
925,0 ... 960,0 MHz		—	1,9	2,2	
Attenuation	$\alpha_{\min}$				
0,0 ... 800,0 MHz		18	21	—	dB
800,0 ... 880,0 MHz		20	23	—	dB
880,0 ... 905,0 MHz		25	31	—	dB
905,0 ... 915,0 MHz		15	23	—	dB
980,0 ... 1005,0 MHz		23	28	—	dB
1005,0 ... 2000,0 MHz		20	25	—	dB
2000,0 ... 3000,0 MHz		15	19	—	dB
3000,0 ... 6000,0 MHz		10	15	—	dB
Input reflection coefficient @ 1842,5 MHz					
Phase		-160	-150	-140	°



SAW Components

B4230

Low-Loss Dual Band Filter for Mobile Communication

942,5 / 1842,5 MHz

Data Sheet



Characteristics Filter 1 (EGSM)

Operating temperature range: $T = -20$ to $+70^{\circ}\text{C}$

Terminating source impedance: $Z_S = 50\ \Omega$

Terminating load impedance: $Z_L = 50\ \Omega$

		min.	typ.	max.	
Center frequency	f_c	—	942,50	—	MHz
Maximum insertion attenuation	$\alpha_{\max}$				
925,0 ... 960,0 MHz		—	3,3	3,9	dB
Amplitude ripple (p-p)	$\Delta\alpha$				
925,0 ... 960,0 MHz		—	1,9	2,1	dB
Input VSWR					
925,0 ... 960,0 MHz		—	2,0	2,3	
Output VSWR					
925,0 ... 960,0 MHz		—	2,0	2,3	
Attenuation	$\alpha_{\min}$				
0,0 ... 800,0 MHz		18	21	—	dB
800,0 ... 880,0 MHz		20	23	—	dB
880,0 ... 905,0 MHz		25	30	—	dB
905,0 ... 915,0 MHz		15	19	—	dB
980,0 ... 1005,0 MHz		23	27	—	dB
1005,0 ... 2000,0 MHz		20	25	—	dB
2000,0 ... 3000,0 MHz		15	19	—	dB
3000,0 ... 6000,0 MHz		10	15	—	dB
Input reflection coefficient @ 1842,5 MHz					
Phase		-160	-150	-140	$^{\circ}$



SAW Components

B4230

Low-Loss Dual Band Filter for Mobile Communication

942,5 / 1842,5 MHz

Data Sheet



Characteristics Filter 2 (PCN)

Operating temperature range: $T = 25 \pm 2^{\circ}\text{C}$

Terminating source impedance: $Z_S = 50 \Omega$

Terminating load impedance: $Z_L = 50 \Omega$

			min.	typ.	max.	
Center frequency	f_c		—	1842,5	—	MHz
Maximum insertion attenuation	$\alpha_{\max}$					
	1805,0 ...1880,0 MHz		—	2,7	3,0	dB
Amplitude ripple (p-p)	$\Delta\alpha$					
	1805,0 ...1880,0 MHz		—	1,3	1,6	dB
Input VSWR						
	1805,0 ...1880,0 MHz		—	2,1	2,3	
Output VSWR						
	1805,0 ...1880,0 MHz		—	2,1	2,3	
Attenuation	$\alpha_{\min}$					
	0,0 ...1480,0 MHz		33	37	—	dB
	1480,0 ...1765,0 MHz		25	29	—	dB
	1765,0 ...1785,0 MHz		10	12	—	dB
	1920,0 ...1980,0 MHz		20	24	—	dB
	1980,0 ...4000,0 MHz		23	27	—	dB
	4000,0 ...5000,0 MHz		15	22	—	dB
	5000,0 ...6000,0 MHz		6	9	—	dB
Input reflection coefficient @ 942,5 MHz						
	Phase		-150	-140	-130	°



SAW Components

B4230

Low-Loss Dual Band Filter for Mobile Communication

942,5 / 1842,5 MHz

Data Sheet



Characteristics Filter 2 (PCN)

Operating temperature range: $T = -20$ to $+70^{\circ}\text{C}$
Terminating source impedance: $Z_S = 50\ \Omega$
Terminating load impedance: $Z_L = 50\ \Omega$

			min.	typ.	max.	
Center frequency	f_c		—	1842,5	—	MHz
Maximum insertion attenuation	$\alpha_{\max}$					
	1805,0 ...1880,0	MHz	—	3,0	3,5	dB
Amplitude ripple (p-p)	$\Delta\alpha$					
	1805,0 ...1880,0	MHz	—	1,5	1,8	dB
Input VSWR						
	1805,0 ...1880,0	MHz	—	2,1	2,3	
Output VSWR						
	1805,0 ...1880,0	MHz	—	2,1	2,3	
Attenuation	$\alpha_{\min}$					
	0,0 ...1480,0	MHz	33	37	—	dB
	1480,0 ...1765,0	MHz	25	29	—	dB
	1765,0 ...1785,0	MHz	9	11	—	dB
	1920,0 ...1980,0	MHz	20	24	—	dB
	1980,0 ...4000,0	MHz	23	26	—	dB
	4000,0 ...5000,0	MHz	15	22	—	dB
	5000,0 ...6000,0	MHz	6	9	—	dB
Input reflection coefficient @ 942,5 MHz						
	Phase		-150	-140	-130	°



SAW Components

B4230


Low-Loss Dual Band Filter for Mobile Communication

942,5 / 1842,5 MHz


Data Sheet



Transfer function Filter 1 (EGSM)- spec at 25 °C



Transfer function Filter 1 (EGSM) - wideband





SAW Components

B4230


Low-Loss Dual Band Filter for Mobile Communication

942,5 / 1842,5 MHz


Data Sheet



Transfer function Filter 2 (PCN) - spec at 25 °C



Transfer function Filter 2 (PCN) - wideband





SAW Components	B4230
Low-Loss Dual Band Filter for Mobile Communication	942,5 / 1842,5 MHz
Data Sheet	SMD

Published by EPCOS AG

Corporate Communications, P.O. Box 80 17 09, 81617 Munich, GERMANY

TEL ++49 89 636 09, FAX (0 89) 636-2 26 89

© EPCOS AG 2002. Reproduction, publication and dissemination of this brochure and the information contained therein without EPCOS' prior express consent is prohibited.

Purchase orders are subject to the General Conditions for the Supply of Products and Services of the Electrical and Electronics Industry recommended by the ZVEI (German Electrical and Electronic Manufacturers' Association), unless otherwise agreed.

This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.