






The information contained in this document is proprietary to VARTTRONIX LTD. and shall be protected from any reproduction in part or as a whole without Varttronix's written approval.



PIN ASSIGNMENT										
1	2	3	4	5	6	7	8	9	10	11
VDD	VSS	XCK	FR	LP1	LP2	FLM	/DISPFF	V0	V1	V2
12	13	14	15	16	17	18	19	20	21	22
V3	V4	D0	D1	D2	D3	D4	D5	D6	D7	NC



DISPLAY TYPE	64K 286+ COLOR STN, -VE, TRANSMISSIVE
DISPLAY RESOLUTION	160 X BGR X 120 DOTS
VIEWING ANGLE	6° CLCCK
MUX RATIO AND BIAS RATIO	1/120 DUTY, 1/12 BIAS
LCD DRIVER	ST8024 X 2 (COG) + ST8016 (TAB)
LOGIC VOLTAGE	3V
LCD DRIVING VOLTAGE	TBD
OPERATING TEMPERATURE	0°C TO +50°C
STORAGE TEMPERATURE	-20°C TO +60°C
BACKLIGHT	LED05 WHITE

NOTES:

1. ◇ : SPECIAL CHARACTERISTIC
2. + : SAFETY CHARACTERISTIC
3. ▽ : CRITICAL DIMENSION
4. (.) : REFERENCE DIMENSION



VARTTRONIX LIMITED

TITLE: SPECIFICATION OF MODULE

PROJECT NO: COG-C286MVJ-01

TOLERANCE UNLESS OTHERWISE SPECIFIED:	X.X ±0.3
DIMENSIONS IN MM	X.XX ±0.1
	ANGULAR ±1°

MATERIAL: N/A	FINISH: N/A
SCALE: DO NOT IN SCALE	OVERALL THK: N/A

THIRD ANGLE PROJECTION	
------------------------	--

DRAWN: SAMUEL	SIGN	DATE
---------------	------	------

CHECKED: LIU ZHI QIANG		
------------------------	--	--

APPROVED: YL LAW		
------------------	--	--

ITEM NO.: COG-C286MVJ-01

DESCRIPTION: COG-C286MVJ-01 (RHS COMPLIANCE)

FILE NO: COG-C286MVJ-01 R1.DWG/REV: 1

SHEET 1 OF 1