


Power Metal Strip® Resistors, High Temperature (275 °C) Low Value (down to 0.01 Ω), Surface Mount



FEATURES

- Ideal for all types of current sensing, voltage division and pulse applications including switching and linear power supplies, instruments and power amplifiers
- Proprietary processing technique produces extremely low resistance values
- Specially selected and stabilized materials allow for high temperature derating (to + 275 °C)
- All welded construction
- Solid metal Nickel-Chrome alloy resistive element with low TCR (< 20 ppm/°C)
- Very low inductance (< 5 nH)
- Excellent frequency response to 50 MHz
- Low thermal EMF (< 3 μV/°C)


RoHS
COMPLIANT

STANDARD ELECTRICAL SPECIFICATIONS

GLOBAL MODEL	POWER RATING $P_{70^{\circ}\text{C}}$ W	RESISTANCE RANGE Ω		WEIGHT (Typical) g/1000 pcs
		$\pm 0.5 \%$	$\pm 1.0 \%$	
WSLT2512	1.0	0.01 - 0.50	0.01 - 0.50	63.6

* Part Marking: DALE, Value, Tolerance Code

TECHNICAL SPECIFICATIONS


PARAMETER	UNIT	WSLT2512
Temperature Coefficient	ppm/°C	± 75
Inductance	nH	< 5
Operating temperature range	°C	- 65/+ 275
Max. Continuous Current	A	$(P/R)^{1/2}$

GLOBAL PART NUMBER INFORMATION


New Global Part Numbering: WSLT2512R0100FEA

W S L T 2 5 1 2 R 0 1 0 0 F E A


GLOBAL MODEL	RESISTANCE VALUE	TOLERANCE CODE	PACKING CODE	SPECIAL
WSLT2512	L = Milliohm* R = Decimal 4L000 = 0.004 Ω R0100 = 0.01 Ω * use "L" for resistance values < 0.01 Ω	D = $\pm 0.5 \%$ F = $\pm 1.0 \%$	EA = Lead (Pb)-free, Tape/Reel EK = Lead (Pb)-free, Bulk	Reserved for future specials

**DIMENSIONS**

MODEL	DIMENSIONS in inches [millimeters]			
	L	W	H	T
WSLT2512	0.250 ± 0.010 [6.35 ± 0.254]	0.125 ± 0.010 [3.18 ± 0.254]	0.025 ± 0.010 [0.635 ± 0.254]	0.030 ± 0.010 [0.762 ± 0.254]



MODEL	SOLDER PAD DIMENSIONS in inches [millimeters]		
	a	b	l
WSLT2512	0.083 [1.65]	0.145 [3.68]	0.160 [4.06]



PERFORMANCE		
TEST	CONDITIONS OF TEST	TEST LIMITS
Thermal Shock	- 55 °C to + 150 °C, 1000 cycles, 15 minutes at each extreme	± 0.5 % ΔR
Short Time Overload	5 × rated power for 5 seconds	± 0.5 % ΔR
Low Temperature Operation	- 65 °C for 45 minutes	± 0.5 % ΔR
High Temperature Exposure	1000 hours at + 275 °C	± 1.0 % ΔR
Bias Humidity	+ 85 °C, 85 % RH, 10 % Bias, 1000 hours	± 0.5 % ΔR
Mechanical Shock	100 g's for 6 milliseconds, 5 pulses	± 0.5 % ΔR
Vibration	Frequency varied 10 to 2000 Hz in one minute, 3 directions, 12 hours	± 0.5 % ΔR
Load Life at 70 °C	1000 hours, 1.5 hrs "ON", 0.5 hours "OFF"	± 1.0 % ΔR
Load Life at 150 °C	1000 hours, 1.5 hrs "ON", 0.5 hours "OFF"	± 1.0 % ΔR
Resistance to Solder Heat	260 °C Solder, 10 - 12 second dwell, 25 mm/second emergence	± 0.5 % ΔR
Moisture Resistance	MIL-STD-202, Method 106, 0 % power, 7b not required	± 1.0 % ΔR

PACKING				
MODEL	REEL			
	TAPE WIDTH	DIAMETER	PIECES/REEL	CODE
WSLT2512	12 mm/Embossed Plastic	178 mm/7"	2000	EA

Embossed Carrier Tape per EIA-481-2



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.