




[2 YEAR WARRANTY]



BXA75 SERIES

Single output

- 3.5 x 2.4 x 0.5 inch package with stand-offs
- 19 Watts/in³ power density
- Efficiency up to 87%
- CISPR 22 and EN55022 conducted emissions level A
- UL, VDE and CSA safety approvals
- Indefinite short circuit protection
- Baseplate operating temperature range of -25°C to +85°C

The BXA75 series are high density DC/DC converters ideally suited for a wide variety of communications, industrial, computer and distributed power applications. With up to 80 Watts of power in a 3.5 x 2.4 x 0.5 inch package and efficiencies as high as 87%, the BXA75 can address a host of demanding power requirements, offering a wide input range of 36-75VDC with industry standard outputs of 3.3V, 5V, 12V and 15V. Approval to EN60950 and EN41003 coupled with conducted emissions compliance to CISPR 22, FCC and EN55022 level A, facilitate easy and cost effective design-in for communications systems. The demands of industrial systems are met by a baseplate operating temperature range of -25°C to 85°C, overvoltage, overtemperature and short circuit protection, along with tight load and line regulation and output ripple as low as 15mV rms. Other standard features include remote enable, remote sense and external trim.

SPECIFICATION

All specifications are typical at nominal input, full load at 25°C unless otherwise stated

OUTPUT SPECIFICATIONS		
Voltage adjustability	3.3V and 15V 5V and 12V	+10%, -3.0% +10%, -5.0%
Voltage accuracy		±0.5%
Remote sense	0.5V line drop compensation	
Total error band	(See Note 2)	±2.0%
Line regulation	Typical	±0.15%
Load regulation	Typical	±0.3%
Ripple and noise	5Hz-20MHz, (See Note 3) No external capacitor	50mV pk-pk 15mV rms max. 100mV pk-pk, 25mV rms max.
Transient response (75% to 100% load step)		±4.0% max. dev. 100µs recovery to within 1% Vo
Temperature coefficient		±0.02%/°C Max.
Overvoltage protection	(See Note 5)	Yes, see table
Short circuit protection		Continuous automatic recovery
INPUT SPECIFICATIONS		
Input voltage range		36 to 75VDC
Input filter	(See Note 4)	Yes
Remote ON/OFF Logic compatibility	(Ref. to -Vin)	CMOS/TTL >3.5VDC or open circuit <0.8VDC
Shutdown idle current		Less than 50mA

EMC CHARACTERISTICS		
Conducted noise	EN55022, FCC (See Note 4)	Level A
Surge susceptibility	100V	No damage
GENERAL SPECIFICATIONS		
Efficiency		See table
Isolation voltage		1500VDC
Switching frequency		500kHz ±5.0%
Approvals and standards		VDE0805, EN60950 IEC950, UL1950 CSA C22.2 No. 950
Case material		Plastic with aluminum baseplate
Material flammability		UL94V-0
Weight		160g (5.65oz)
MTBF	Bellcore, 25°C baseplate	2,600,000 hours minimum
ENVIRONMENTAL SPECIFICATIONS		
Thermal performance (See Note 6)	Operating, See curves Non-operating Over temperature shutdown	-25°C to +85°C -55°C to +125°C 115°C internal temperature auto. recovery
Altitude	Operating Non operating	10,000 feet max. 40,000 feet max.
Vibration	5Hz to 500Hz	2.4G RMS (approx.)

Data Sheet © Artesyn Technologies® 2000
The information and specifications contained in this data sheet are believed to be correct at time of publication. However, Artesyn Technologies accepts no responsibility for consequences arising from printing errors or inaccuracies. Specifications are subject to change without notice. No rights under any patent accompany the sale of any such product(s) or information contained herein.

International Safety Standard Approvals

VDE0805/EN60950/IEC950 File No. 10401-3336-1073

UL1950 File No. E136005

CSA C22.2 No. 950 File No. LR41062C

DS_BXA75_19980401.PDF