


● 80BL Series

Part No.	Nominal dc spark-over voltage	Gas Discharge Tube dc spark-over voltage	Impulse spark-over voltage at 1Kv/ μ s	Nominal impulse discharge current 8/20 μ s	Nominal impulse discharge current 10/1000 μ s	Nominal Alternating discharge current at 50Hz, 1s	Insulation resistance		Capacitance at 1kHz
	V _{sdc} (V)	V _{sdc} (V)	V _{sl} (V)	i _{dl} (KA)	i _{dl} (A)	i _{da} (A)	V (V)	R _{is} (Ω)	C (Pf)
80B75L	75	60~90	≤ 700	10	100	10	50	$\geq 10^9$	≤ 2
80B90L	90	72~108	≤ 700				50		
80B150L	150	120~180	≤ 700				50		
80B230L	230	184~276	≤ 800				100		
80B250L	250	200~300	≤ 800				100		
80B300L	300	240~360	≤ 900				100		
80B350L	350	280~420	≤ 900				100		
80B400L	400	320~480	≤ 1000				100		
80B420L	420	336~504	≤ 1100				100		
80B470L	470	376~564	≤ 1100				100		
80B600L	600	480~720	≤ 1500				150		



80BXXXL Series

Series	W3	W5	L3	L4	L5
80BL	$\phi 8.0 \pm 0.3$	14.6 $\pm$ 0.5	$\phi 1.0 \pm 0.1$	10.0 $\pm$ 0.3	4.4 $\pm$ 0.2