






Part Number	Emitting Color	Emitting Material	Luminous Intensity (IF=10mA) ucd		Wavelength nm λ P	Description
			min.	typ.		
ZFMYK07C2	Yellow	InGaAlP	8000	35390	590	Common Cathode. Rt. Hand Decimal
Published Date : MAR 04,2008		Drawing No : SDSA5333			V4	Checked : B.L.LIU P.1/4



❖ **MYK**




Remarks:

If special sorting is required (e.g. binning based on forward voltage, luminous intensity/ luminous flux or wavelength), the typical accuracy of the sorting process is as follows:

1. Wavelength: $\pm 1\text{nm}$
2. Luminous Intensity/ Luminous Flux: $\pm 15\%$
3. Forward Voltage: $\pm 0.1\text{V}$

Note: Accuracy may depend on the sorting parameters.


Reflow Soldering Profile For Lead-free SMT Process.




Notes:

1. Maximum soldering temperature should not exceed 260°C.
2. Recommended reflow temperature: 145°C-260°C.
3. Do not put stress to the epoxy resin during high temperatures conditions.


❖ Recommended Soldering Pattern (Units : mm;Tolerance:± 0.15)



❖ Tape Specification (Units : mm)




PACKING & LABEL SPECIFICATIONS ZFMYK07C2




Outside LABEL Paste On The BAG

Inside LABEL Paste On The TAPE




Date
Number OF FQC




Date
Number OF FQC

Outside LABEL Paste On The 19#Box

Outside LABEL Paste On The 12#Box



BIN CODE
Number OF QA
Date



Number OF QA
Date