

MPC565/MPC566

Product Brief

MPC565/MPC566 RISC MCU with Code Compression Option

Features

The MPC565 / MPC566 key features are as follows. The information inside boxes are optional features.

- **40 MHz / 56 MHz operation**

- **56 MHz operation is available as an option.**

- -40° – 125 °C ambient temperature
- 2.6 V $\pm$ 0.1 V external bus
 - External bus is compatible with external memory devices operating from 2.5 V to 3.4 V.
 - Extended voltage range (2.7 – 3.4 V) degrades data drive timing by 1.1 ns on data writes.
- 2.6 $\pm$ 0.1 V internal logic
- 5-V I/O (5.0 $\pm$ 0.25 V)

- **High performance RISC CPU system**

- High performance core
 - Single issue integer core
 - Instruction set compatible with PowerPC instruction set architecture
 - Precise exception model
 - Floating point

- Code compression supported on the MPC566
 - Compression reduces usage of internal or external flash memory
 - Compression optimized for automotive (non-cached) applications
 - New compression scheme increases compression performance to 40% – 50% compression

- 4-Kbyte static DECRAM can be used as memory if Compression is not used.
- General-purpose I/O support
 - On address (24) and data (32) pins
 - 16 GPIO in MIOS14
 - Many peripheral pins can be used as GPIO when not used as primary functions
 - 2.6-V outputs on external bus pins
 - Extensive system development support
 - On-chip watchpoints and breakpoints
 - Program flow tracking
 - Background debug mode (BDM)

Key Feature Details

MPC500 System Interface (USIU, BBC, L2U)

- Periodic interrupt timer, bus monitor, clocks, decremter and time base
- Clock synthesizer, power management, reset controller
- External bus tolerates 5-V inputs, provides 3.3-V outputs
- Enhanced interrupt controller supports a separate interrupt vector for up to eight external and 40 Internal interrupts

- IEEE 1149.1 JTAG test access port
- Bus supports multiple master designs
- Flexible memory protection units in BBC (IMPU) and L2U (DMPU)
- Flexible chip selects via memory controller
 - 24-bit address and 32-bit data buses
 - Four- to 16-Mbyte (data) or 4-Gbyte (instruction) region size support
 - Four-beat transfer bursts, two-clock minimum bus transactions
 - Use with SRAM, EPROM, flash and other peripherals
 - Byte selects or write enables
 - 32-bit address decodes with bit masks
 - Four instruction regions
 - Four data regions
- Default attributes available in one global entry
- Attribute support for speculative accesses
- Exception vector table relocation features allow exception table to be relocated to following locations:
 - 0x0000 0100 (normal MPC5xx exception table location)
 - 0x0001 0000 (0 + 64 Kbytes; second page of internal flash)
 - Second internal flash module
 - Internal SRAM
 - 0xFFFF_0100 (external memory space; normal MPC5xx exception table location)
- USIU supports dual-mapping of flash to move part of internal flash memory to external bus for development

One Mbyte Flash

- Two UC3F modules, 512 Kbytes each
- Page mode read
- Block (64-Kbyte) erasable
- External 4.75- to 5.25-V V_{PP} program, erase, and read power supply

36-Kbyte Static RAM (CALRAM)

- Composed of four- and 32-Kbyte CALRAM modules
- Fast access: one clock
- Keep-alive power
- Soft defect detection (SDD)
- 4-Kbyte calibration (overlay) RAM per module (eight Kbytes total)
- Eight 512-byte overlay regions per module (16 regions total)

IEEE – ISTO Nexus 5001-1999 Debug Port (Class 3)

- Address (24) and data (32) pins can be used as GPIO in single chip mode
- Reduced-port mode (1 MDI, 2 MDo) or full-port mode (2 MDI, 8 MDO)
- Many peripheral pins can be used as GPIO when not used as primary functions
- 5-V outputs with slew rate control

Integrated I/O System

- True 5-V I/O
- Three time processing units (TPU3)
 - 16 channels each
 - Each TPU3 is a microcoded timer subsystem
 - One 6-Kbyte and one 4-Kbyte dual port TPU RAM (DPTRAM), one (6-Kbyte) shared by two TPU3 modules for TPU microcode and the 4-Kbyte dedicated to the third TPU3 for microcode.

22-Channel MIOS timer (MIOS14)

- Six modulus counter sub-module (MCSM)
 - Four additional MCSM submodules compared to MIOS1
- 10 double action sub-module (DASM).
- 12 dedicated PWM sub-modules (PWMSM)
 - Four additional PWM submodules compared to MIOS1 (shared with MIOS GPIO pins)
- Real-time clock sub-module (MRTCSCM) provides low power clock/counter
 - Requires external 32-KHz crystal
 - Uses four pins: two for 32-KHz crystal, two for power/ground.

Two Queued Analog-to-Digital Converter Modules (QADC64E_A, QADC64E_B)

- AMUXes providing a total of 40 analog channels.
- 40 total input channels on the two modules with internal multiplexing (AMUXes)
- Each QADC64E can see all 40 input channels
- 10 bit A/D converter with internal sample/hold
- Typical conversion time is 4 μ s (250-Kbyte samples/sec)
- Two conversion command queues of variable length
- Automated queue modes initiated by:
 - External edge trigger/level gate
 - Software command
 - Periodic/interval timer, assignable to both queue 1 and 2
- 64 result registers in each QADC64E module
- Conversions alternate reference (ALTREF) pin. This pin can be connected to a different reference voltage
- Output data is right or left justified, signed or unsigned

Message Data Link Controller (DLCMD2) Module

- Two pins muxed with QSMCM_B pins. Muxing controlled by QSMCM_B PCS3 pin assignment register
- SAE J1850 Class B data communications network interface compatible and ISO compatible for low-speed (< 125 Kbps) serial data communications in automotive applications
- 10.4 Kbps variable pulse width (VPW) bit format
- Digital noise filter, collision detection
- Hardware cyclical redundancy check (CRC) generation and checking
- Block mode receive and transmit supported
- 4X receive mode supported (41.6 Kbps)
- Digital loopback mode
- In-frame response (IFR) types 0, 1, 2, and 3 supported
- Dedicated register for symbol timing adjustments
- Inter-module bus 3 (IMB3) slave interface
- Power-saving IMB3 stop mode with automatic wakeup on network activity
- Power-saving IMB3 CLOCKDIS mode
- Debug mode available through IMB3 FREEZE signal or user controllable SOFT_FRZ bit
- Polling and IMB3 interrupt generation with vector lookup available

Three TouCAN™ Modules (TOUCAN_A, TOUCAN_B, TOUCAN_C)

- 16 message buffers each, programmable I/O modes
- Maskable interrupts
- Programmable loop-back for self test operation
- Independent of the transmission medium (external transceiver is assumed)
- Open network architecture, multimaster concept
- High immunity to EMI
- Short latency time for high-priority messages
- Low power sleep mode, with programmable wake up on bus activity

- TOUCAN_C pins shared with MIOS14 GPIO pins

Two Queued Serial Modules with One Queued-SPI and two SCI Each (QSMCM_A, QSMCM_B)

- QSMCM_A matches full MPC555/MPC556 QSMCM functionality
- QSMCM_B has pins muxed with DLCMD2 module
 - Two pins are muxed with DLCMD2 (J1850) transmit and receive pins (B_PCS3_J1850_TX and B_RXD2_J1850_RX)
 - QSMCM_B vs J1850 mux control provided by QPAPCS3 bit in QSMCM pin assignment register (PQSPAR)
- Queued-SPI
 - Provides full-duplex communication port for peripheral expansion or interprocessor communication
 - Up to 32 preprogrammed transfers, reducing overhead
 - Synchronous serial interface with baud rate of up to system clock / 4
 - Four programmable peripheral-selects pins support up to 16 devices
 - Special wrap-around mode allows continuous sampling of a serial peripheral for efficient interfacing to serial analog-to-digital (A/D) converters
- SCI
 - UART mode provides NRZ format and half- or full-duplex interface
 - 16 register receive buffer and 16 register transmit buffer on one SCI
 - Advanced error detection, and optional parity generation and detection
 - word length programmable as eight or nine bits
 - Separate transmitter and receiver enable bits, and double buffering of data
 - Wake-up functions allow the CPU to run uninterrupted until either a true idle line is detected, or a new address byte is received
 - External source clock for baud generation
- **Available in package**
 - **Plastic ball grid array (PBGA) packaging**
 - 352/388 ball PBGA
 - 27 mm x 27 mm body size
 - 1.0 mm ball pitch




Figure 1 MPC565/MPC566 Block Diagram




Figure 2 MPC565 / MPC566 Internal Memory Block




Figure 3 MPC565 / MPC566 Ball Diagram

Ordering Information

Table 1 MPC565 / MPC566

Device Name	Order Part Number ¹	Package Info	Temperature Range	Maximum Frequency	Code Compression
MPC565	MPC565MZP40	388 PBGA	-40 – 125° C	40 MHz	No
MPC565	MPC565CZP40	388 PBGA	-40 – 85° C	40 MHz	No
MPC565	MPC565MZP56	388 PBGA	-40 – 125° C	56 MHz	No
MPC565	MPC565CZP56	388 PBGA	-40 – 85° C	56 MHz	No
MPC566	MPC566MZP40	388 PBGA	-40 – 125° C	40 MHz	Yes
MPC566	MPC566CZP40	388 PBGA	-40 – 85° C	40 MHz	Yes
MPC566	MPC566MZP56	388 PBGA	-40 – 125° C	56 MHz	Yes
MPC566	MPC566CZP56	388 PBGA	-40 – 85° C	56 MHz	Yes

NOTES:

1. Add R2 suffix for parts shipped in tape and reel media.

Table 2 lists the documents that provide a complete description of the MPC565/566 and are required to design properly with the part. Documentation is available from a local Motorola distributor, a Motorola semiconductor sales office, a Motorola Literature Distribution Center, or through the Motorola Semiconductor documentation page on the Internet (the source for the latest information).

Table 2 Available Documentation

Document Number	Title
MPC565RM/D	MPC565/MPC566 Reference Manual
AN1821/D	Exception Table Relocation and Multi-Processor Address Mapping in the Embedded MPC5XX Family
AN2002/D	MPC565/566 Nexus Interface Connector Options
AN2109/D	MPC555 Interrupts
AN2127/D	EMC Guidelines for MPC500-Based Automotive Powertrain Systems

OnCE, DigitalDNA, and the DigitalDNA logo are trademarks of Motorola, Inc.

Motorola reserves the right to make changes without further notice to any products herein. Motorola makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does Motorola assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation consequential or incidental damages. "Typical" parameters which may be provided in Motorola data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. Motorola does not convey any license under its patent rights nor the rights of others. Motorola products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support life, or for any other application in which the failure of the Motorola product could create a situation where personal injury or death may occur. Should Buyer purchase or use Motorola products for any such unintended or unauthorized application, Buyer shall indemnify and hold Motorola and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that Motorola was negligent regarding the design or manufacture of the part. Motorola and  are registered trademarks of Motorola, Inc. Motorola, Inc. is an Equal Opportunity/Affirmative Action Employer.

How to reach us:

USA/EUROPE

Motorola Literature Distribution

P.O. Box 5405
Denver, Colorado 80217
1-303-675-2140
1-800-441-2447

Technical Information Center

1-800-521-6274

JAPAN

Motorola Japan Ltd.
SPS, Technical Information Center
3-20-1, Minami-Azabu, Minato-ku
Tokyo 106-8573 Japan
81-3-3440-3569

ASIA/PACIFIC

Motorola Semiconductors H.K. Ltd.
Silicon Harbour Centre
2 Dai King Street
Tai Po Industrial Estate
Tai Po, N.T., Hong Kong
852-26668334

Home Page

<http://www.motorola.com/semiconductors>



MOTOROLA

Order Number MPC565PB/D