International
IOR Rectifier

PD-95739

HFA16TA60CPbF

HEXFRED™

Ultrafast, Soft Recovery Diode

Features

- Ultrafast Recovery
- Ultrasoft Recovery
- Very Low I_{RRM}
- Very Low Q_{rr}
- Specified at Operating Conditions
- Lead-Free



V_R = 600V
V_F(typ.)* = 1.7V
Q_{rr} *= 65nC
$di_{(rec)M}/dt$ * = 240A/µs
*125°C



TO-220AB

Benefits

- Reduced RFI and EMI
- Reduced Power Loss in Diode and Switching Transistor
- Higher Frequency Operation
- Reduced Snubbing
- Reduced Parts Count

Description

International Rectifier's HFA16TA60C is a state of the art center tap ultra fast recovery diode. Employing the latest in epitaxial construction and advanced processing techniques it features a superb combination of characteristics which result in performance which is unsurpassed by any rectifier previously available. With basic ratings of 600 volts and 15 amps per Leg continuous current, the HFA16TA60C is especially well suited for use as the companion diode for IGBTs and MOSFETs. In addition to ultra fast recovery time, the HEXFRED product line features extremely low values of peak recovery current (I_{RRM}) and does not exhibit any tendency to "snap-off" during the t_b portion of recovery. The HEXFRED features combine to offer designers a rectifier with lower noise and significantly lower switching losses in both the diode and the switching transistor. These HEXFRED advantages can help to significantly reduce snubbing, component count and heatsink sizes. The HEXFRED HFA16TA60C is ideally suited for applications in power supplies and power conversion systems (such as inverters), motor drives, and many other similar applications where high speed, high efficiency is needed.

Absolute Maximum Ratings (per Leg)

	Parameter	Max	Units
V_R	Cathode-to-Anode Voltage	600	V
I_F @ T_C = 100°C	Continuous Forward Current	8.0	A
I_{FSM}	Single Pulse Forward Current	60	
I_{FRM}	Maximum Repetitive Forward Current	24	
P_D @ T_C = 25°C	Maximum Power Dissipation	36	C
P_D @ T_C = 100°C	Maximum Power Dissipation	14	
T_J	Operating Junction and	-55 to +150	W
T_{STG}	Storage Temperature Range		

Electrical Characteristics (per Leg) @ T_J = 25°C (unless otherwise specified)

	Parameter	Min	Typ	Max	Units	Test Conditions
V_{BR}	Cathode Anode Breakdown Voltage	600			V	I_R = 100µA
V_{FM}	Max Forward Voltage		1.4	1.7	V	I_F = 8A
			1.7	2.1		I_F = 16A See Fig. 1
			1.4	1.7		I_F = 8A, T_J = 125°C
I_{RM}	Max Reverse Leakage Current		0.3	5	µA	V_R = V_R Rated See Fig. 2
			100	500		T_J = 125°C, V_R = 0.8 x V_R Rated
C_T	Junction Capacitance		10	25	pF	V_R = 200V See Fig. 3
L_S	Series Inductance		8.0		nH	Measured lead to lead 5mm from package body

Dynamic Recovery Characteristics (per Leg) @ T_J = 25°C (unless otherwise specified)

	Parameter	Min	Typ	Max	Units	Test Conditions	
t_{rr}	Reverse Recovery Time		18		ns	I_F = 1.0A, di_f/dt = 200A/µs, V_R = 30V	
t_{rr1}	See Fig. 5, 10		37	55		T_J = 25°C	I_F = 8A
t_{rr2}			55	90		T_J = 125°C	
I_{RRM1}	Peak Recovery Current		3.5	5.0	A	T_J = 25°C	V_R = 200V
I_{RRM2}	See Fig. 6		4.5	8		T_J = 125°C	
Q_{rr1}	Reverse Recovery Charge		65	138	nC	T_J = 25°C	di_f/dt = 200A/µs
Q_{rr2}	See Fig. 7		124	360		T_J = 125°C	
$di_{(rec)M}/dt1$	Peak Rate of Fall of Recovery Current		240		A/µs	T_J = 25°C	
$di_{(rec)M}/dt2$	During t_b See Fig. 8		210			T_J = 125°C	

Thermal - Mechanical Characteristics (per Leg)

	Parameter	Min	Typ	Max	Units
T_{lead}①	Lead Temperature			300	°C
R_{thJC}	Junction-to-Case, Single Leg Conducting			3.5	K/W
	Junction-to-Case, Both Legs Conducting			1.75	
R_{thJA}②	Thermal Resistance, Junction to Ambient			80	
R_{thCS}③	Thermal Resistance, Case to Heat Sink		0.5		
Wt	Weight		2.0		g
			0.07		(oz)
	Mounting Torque	6.0		12	Kg-cm
		5.0		10	lbf•in

① 0.063 in. from Case (1.6mm) for 10 sec
② Typical Socket Mount
③ Mounting Surface, Flat, Smooth and Greased



Fig. 1 - Maximum Forward Voltage Drop vs. Instantaneous Forward Current, (per Leg)



Fig. 2 - Typical Reverse Current vs. Reverse Voltage, (per Leg)



Fig. 3 - Typical Junction Capacitance vs. Reverse Voltage, (per Leg)



Fig. 4 - Maximum Thermal Impedance Z_{thjc} Characteristics, (per Leg)



Fig. 5 - Typical Reverse Recovery vs. di_f/dt, (per Leg)



Fig. 6 - Typical Recovery Current vs. di_f/dt, (per Leg)



Fig. 7 - Typical Stored Charge vs. di_f/dt, (per Leg)



Fig. 8 - Typical $di_{(rec)M}/dt$ vs. di_f/dt, (per Leg)



Fig. 9 - Reverse Recovery Parameter Test Circuit



Fig. 10 - Reverse Recovery Waveform and Definitions

TO-220AB Package Outline

Dimensions are shown in millimeters (inches)



Conform to JEDEC outline TO-220AB
Dimensions in millimeters and (inches)

TO-220AB Part Marking Information



Data and specifications subject to change without notice.

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7903
Visit us at www.irf.com for sales contact information. 10/04