



DB ELECTRO
COMPOSANTS ÉLECTRONIQUES
ELECTRONIC COMPONENTS



- Single Turn/ Cermet/ Industrial /sealed
- 8 terminal styles
- RoHS Compliant



3386 Square Trimming Potentiometer

Electrical Characteristics

Standard Resistance Range.....50 Ω ~2M Ω
Resistance Tolerance..... $\pm 10\%$
Absolute Minimum Resistance..... $\leq 1\%R$ or 10 Ω
Contact Resistance VariationCRV $\leq 3\%$
Insulation Resistance..... $R_1 \geq 1G \Omega$ (100Vac)
Withstand Voltage.....600Vac
Effective Travel.....300°

Environmental Characteristics


(Power Rating) (315 volts max)
.....0.5W@70°C, 0W@125°C
Temperature Range.....-55°C~125°C
Temperature Coefficient..... ± 250 ppm/°C
Temperature Variation...-55°C, 30min, +125°C
.....30min、3cycles
..... $\Delta R \leq 5\%R$, $\Delta(U_{ab}/U_{ac}) \leq 10\%$
Collision ...100m/s², 1000cycles, $\Delta R \leq 2\%R$
..... $\Delta(U_{ab}/U_{ac}) \leq 10\%$
Electrical Endurance at 70°C...0.5W@70°C, 1000h
... $\Delta R \leq 10\%R$, $\Delta(U_{ab}/U_{ac}) \leq 10\%$, CRV $\leq 3\%$ or 5 Ω
Rotational Life.....200cycles
..... $\Delta R \leq 10\%R$, CRV $\leq 3\%$ or 5 Ω

Physical Characteristics






Starting Torque..... ≤ 35 mN·m
Marking.....Resistance Tolerance
... (when no identification, it is of $\pm 10\%$)
.....Resistance Code、Model
Standard Packaging...50pcs, per tube

RoHS Compliant

Common Dimensions



Common Dimensions




Standard Resistance Table

Resistance (Ohms)	Resistance Code
10	100
20	200
50	500
100	101
200	201
500	501
1,000	102
2,000	202
5,000	502
10,000	103
20,000	203
25,000	253
50,000	503
100,000	104
200,000	204
250,000	254
500,000	504
1,000,000	105
2,000,000	205

How To Order

3386--P--103
Model Style Resistance Code



Tolerance is ± 0.25
If no identification