


## 1030D, 1031D, 1033D and 1090D Series Non-Relampable Neon-Incandescent Indicator Lights

### DESCRIPTION AND FEATURES



Mounting: Will snap-fit into Ø.500/.505 hole in panels .020/.100 thick. Push-on speednut SN0461 also available.

Mounting hole pattern on page SP2.

Wire Leads: No.22 AWG (105°C) 4.40/4.80 long, stripped .430/.570

Lens: Polycarbonate

Bezel: Polished stainless steel.  
For black finish add "X" after the series letter(s).

Housing: White Nylon

| Lens Color | Neon                      |                           | Incandescent       |                    |
|------------|---------------------------|---------------------------|--------------------|--------------------|
|            | Model No.<br>(105-125VAC) | Model No.<br>(208-250VAC) | Model No.<br>(12V) | Model No.<br>(28V) |
| Red        | 1030D1                    | 1031D1                    | 1090D1-12V         | 1090D1-28V         |
| Amber      | 1030D3                    | 1031D3                    | 1090D3-12V         | 1090D3-28V         |
| White      | 1030D4                    | 1031D4                    | 1090D4-12V         | 1090D4-28V         |
| Green      | 1032D5*                   | 1033D5*                   | 1090D5-12V         | 1090D5-28V         |
| Lamp used  | C 2A+R resistor           |                           | #2162              | #2187              |
| Lead Color | Black                     | One Black/One Red         | Yellow             | Purple             |
| "A"        | 1.130                     | 1.130                     | .910               | .910               |

\* Incorporates G2B lamp and resistor.

Underwriters Laboratories (UL) File No. E20325

Canadian Standards Association (CSA) File No. LR13346